

**Missouri Department of Transportation**  
*Kevin Keith, Director*

573.751.2551  
Fax: 573.751.6555  
1.888.ASK MODOT (275.6636)

September 9, 2011

Addendum to Bid Request 3-111013WB – Multimodal  
Addendum 3-111013WB-001

## **ADDENDUMS AND CLARIFICATIONS**

### **TRANSIT VEHICLES 2012 MODEL YEAR**

---

#### ALL VEHICLES WITH WHEELCHAIR POSITIONS

---

Hand-tensioned knobs are required on all wheelchair securement tie-down belt retractors.

#### ALL CUTAWAY VEHICLES (WIDE BODY, NARROW BODY, AND MEDIUM DUTY)

---

Rear Heaters to have two-speed fan switches-(off, low, high)

As-Built wiring diagrams to be provided with each vehicle delivered. (no wiring diagram with the bid)

Tire Valve Stem Extensions will be installed so operators can check tire pressure on BOTH rear duals with gauge while kneeling by rear tires.

#### CUTAWAY VEHICLES (WIDE BODY & NARROW BODY)

---

Alternator rating to be 220 amp. minimum.



---

*Our mission is to provide a world-class transportation experience that delights our customers and promotes a prosperous Missouri.*

[www.modot.org](http://www.modot.org)

### *WIDE BODY CUTAWAYS*

---

Ford Chassis to 14,500 GVWR, Chevrolet 14,200 GVWR minimum.

### *NARROW BODY CUTAWAY*

---

Floor Plan OO will have the wheelchair securement tracks run the **WIDTH** of the securement position.

Tires – There shall be seven (7) tires and wheels; size 225/75R16.

### *MEDIUM DUTY CUTAWAY*

---

Freightliner Chassis is acceptable

Front Axle: 10,000 lb. rating

Rear Axle: 17,500 lb. rating

Alternator: 270 Amp. minimum.

OEM driver's door armrest is acceptable for LH side

6-Speed Automatic transmission

Wheel Size 22.5X7.5

LOWERED FLOOR MINI VAN

---

Manufacturer's OEM Brakes are acceptable

6-Speed Automatic Transmission: (MFG. Standard)

Alternator: MFG. Standard.

Flooring: 3/8" thick marine grade minimum.

Thank you for your attention to this matter.

Warren Blanchard

**If you have any questions about this addendum, please feel free to contact me at 573-526-2529.**

---