



### Cargo Trailer Specifications

The Cargo Trailer needs to meet the minimum specifications. We will only be accepting bids with roof-mounted air conditioner. All Trailers will have insulated walls, roof and floor. We do not desire bids on trailers with “V nose” or “Tapered Nose”. All Trailers will have a minimum of 7-foot high interior ceilings.

Trailer	
Interior Dimensions	7' wide x 12' long
Axle Capacity, Tandem Axle	5,200 lbs each
Tire Size	15" with 2 spares mounted on the tongue
Stabilizer Jacks	4. One on each corner
Recessed Floor Tie Down Points	4 Interior Floor
Wall Cargo Tie Down Strips	2 Per Interior Wall
Man Door with bar lock 30"	1 Passenger Side
Rear Ramp-style door with 2 bar locks	1 rear of trailer
Electric tongue jack	4,000 Pounds, 12 Volts
Rooftop Air Conditioner	15,000 BTU
Shore Power Electric Wiring	50 Amp 120/240 Volt A/C Twist Lock Receptacle
Exterior Wiring	2 weather tight duplex receptacles, mounted, one each, on each side of the trailer
Interior Wiring	<p><b>1</b> service panel sized to accommodate:  <b>8</b>, 120 volt 15 amp A/C circuit breakers,  <b>1</b>, 120 volt 20 amp circuit breaker  <b>1</b>, circuit adequate for the air conditioner.  The capability of adding <b>4</b> 120 volt A/C or <b>2</b>, 240 volt A/C circuits for future use. The trailer shall come with <b>6</b> duplex interior receptacles, <b>2</b> per interior sidewall/front wall each on its own circuit @ 15 amp each. <b>1</b> 120Volt 20-amp receptacle in center of front wall, 2 interior florescent light fixtures, mounting TBD.</p>

Firm prices shall be required for the following options:

Roof Mounted Ladder/pipe Racks

Shore Power Cable with 50 amp twist lock ends, one each male and female

Work bench installed on front wall.