

(13) Regulations for the movement of loads over twelve feet four inches (12'4") to fourteen feet (14') wide. The following requirements in addition to the requirements of oversize and overweight permit regulations for movement of loads up to twelve feet four inches (12'4") in width shall apply to all loads over twelve feet four inches (12'4") to fourteen feet (14') in overall width.

(A) Restrictions and Requirements. Bridge crossings may require stopping traffic on two- (2-) lane highways where bridge width is less than twenty-eight feet (28'); a distance of at least one thousand feet (1,000') between oversize vehicles is required; escorts may act as flaggers.

1. Travel on interstate and other divided highways allowed from one-half (1/2) hour before sunrise to one-half (1/2) hour after sunset except where restricted in tourist and urban areas (see subsections (9)(D) and (9)(E)) and as prohibited by holiday restrictions in subsection (1)(I).

2. No movement Monday through Friday from 6:30 a.m. to 9:00 a.m. and 3:30 p.m. to 6:00 p.m. on all other routes on the state highway system and no movement allowed on Saturday and Sunday in tourist areas (see subsection (9)(D)).

(B) Escort Requirements. One (1) escort is required for each oversize unit on the interstate and designated route system. This escort shall be in the rear on dual-lane, divided, or multi-lane pavement and in the front on two- (2-) lane pavement. Travel on routes off interstate and designated route system will require two (2) escorts (one (1) front and one (1) rear). Continuous, uninterrupted two-way communication is required between the power unit and all escort vehicles.