EFFECTIVE: 07/01/2018

POST NUMBER	PULL BOX NUMBER	LOCATION: APPROACH	LOCATION: STATION	LOCATION: OFFSET	BASE A 9	BASE A 9.5	BASE A 10	BASE A 10.5	BASE A 11	BASE A 12	BASE F 9	BASE F 9.5	BASE F 10	BASE F 10.5	BASE F 11	BASE F 12	BASE C	CONCRETE** (CU. YDS.)
			CONTROLLER	(AS REQ'D)														
				SUBTOTAL														
				TOTAL														

POST NUMBER	PULL BOX NUMBER	PULL BOX: PREFORMED CONCRETE CLASS 1	CLASS 2	CLASS 3	CLASS 5	STANDARD	DOUBLE, TYPE A	DOUBLE, TYPE B	DRAIN TYPE* I	DRAIN TYPE* II A	DRAIN TYPE* II B	DRAIN TYPE* II C

POST NUMBER	PULL BOX NUMBER	TOP MOUNT POST 8 FT.	TOP MOUNT POST 15 FT.	TYPE C & CL ARM LENGTH A	ARM LENGTH A	ARM LENGTH A	ARM LENGTH A	SIGNAL SPACING B	SIGNAL SPACING C	SIGNAL SPACING D	SIGNAL SPACING D'	SIGN SPACING B	SIGN SPACING C	SIGN SPACING D	SIGN SPACING D'

POST NUMBER	PULL BOX NUMBER	TYPE B & BL ARM LENGTH E	ARM LENGTH K	ARM LENGTH E	ARM LENGTH E	ARM LENGTH K	LEFT ARM E SIGNAL SPACING F	SIGNAL SPACING G	SIGNAL SPACING H	SIGNAL SPACING H'	LEFT ARM E SIGN SPACING F	SIGN SPACING G	SIGN SPACING H	SIGN SPACING H'	RIGHT ARM K SIGNAL SPACING L	SIGNAL SPACING M	SIGNAL SPACING N	SIGNAL SPACING N'	RIGHT ARM K SIGN SPACING L	SIGN SPACING M	SIGN SPACING N	SIGN SPACING N'	INCLUDED ANGLE	LUMINAIRE BRACKET ARM* 4 FT.	6 FT.	8 FT.	10 FT.	12 FT.	15 FT.

SIGNAL HEADS

| SPAN NUMBER | POST NUMBER | FACE NUMBER | LUMINAIRE 150W SODIUM | INDICATIONS * 12" LENS CONVENTIONAL R | Y | YL | YRt | FYL | FYR | G | S | L | Rt | 🚶 | 12" LENS OPTICAL LIMITING R | Y | YL | YRt | YL | YRt | G | S | L | Rt | VISORS * 12" LENS | PED. | LOUVERS * A | B | C | D | E | F | BACKPLATE* LENSES 1 | 2 | 3 | 4 | 5 | RETROREFLECTIVE BACKPLATE* LENSES 1 | 2 | 3 | 4 | 5 | BRACKET* TYPE I | II | III | ONE-FACE SECTION 1- T | S | C | B | 3- T | S | C | B | 4- T | S | C | B | 5- T | S | C | B | TWO-FACE SECTIONS 11- T | S | B | 33- T | S | C | B | 34- S | B | 35- S | B | 44- S | B | 45- S | B |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---