

Steven V. Stenger
County Executive



Daniel W. Dreisewerd, P.E., PTOE
Acting Director

Stephanie Leon Streeter, P.E.
Deputy Director

January 26, 2018

ADDENDUM NO. 3

Notice to All Persons and Firms Proposing to Submit a Bid or Furnish Materials for
Hanley Road (B) Resurfacing
St. Louis County Project No. AR-1484
Federal Project No. STP-5613(604)

The construction contract for this project has been revised as follows:

No. 1

Added Special Provision 400.30.4 FULL DEPTH ASPHALT BASE REPAIR as follows:

400.30.4 FULL DEPTH ASPHALT BASE REPAIR

Description

- A. This work shall consist of saw cutting, full depth asphalt pavement removal, subgrade preparation, and placement and compaction of full depth type 'X' asphalt base pavement in lifts in accordance with section 405.12.1 of the "Standard Specifications for Road and Bridge Construction Manual".
- B. Locations to be repaired shall be as indicated in the construction plan or as determined by the Engineer.
- C. Repair thickness shall match the existing pavement section. Approximate pavement thicknesses have been included in the construction plans.
- D. Where the existing subgrade has been determined by the engineer to be acceptable to use in place, the contractor shall level and prepare the subgrade material prior to placement of asphalt base material.
- E. Where the existing subgrade has been determined by the engineer to be unacceptable to use in place, the contractor shall remove the existing subgrade and place and compact 4" of type 5 aggregate base prior to placement of asphalt base material.

Method of Measurement

- A. Measurement shall be taken to the nearest (0.1) Ton for the item 405.30.30 TYPE "X" BITUMINOUS CONCRETE (BASE).
- B. Thickness will be measured to the nearest inch by the Engineer after preparation of the subgrade has been completed and accepted.

Basis of Payment

- A. Payment for saw cutting, pavement removal, preparation of subgrade to be used in place, type 'X' asphalt pavement, Tack Emulsified Asphalt(SS-1H), and disposal of materials, including any handwork necessary to complete the repair, will be made per ton of completed repair at the contract unit price for Item No. 405.30.30 TYPE "X" BITUMINOUS CONCRETE (BASE).
- B. Removal, replacement, and disposal of unacceptable subgrade material shall be paid for at the contract unit price for 304-05.04 "Type 5 Aggregate Base (4" Thick)".

ATTENTION BIDDERS: THE ADDENDUM ACKNOWLEDGEMENT IN THE BID DOCUMENTS MUST BE COMPLETED AND SUBMITTED WITH ALL BID PROPOSALS.

A handwritten signature in blue ink, appearing to read 'Joseph W. Kulesa', with a long horizontal flourish extending to the right.

Joseph W. Kulesa, P.E.
Division Manager, Design

JWK/HH:nms