

**OMAR N. BRADLEY AIRPORT
MOBERLY, MISSOURI**

MoDOT PROJECT NO. 15-034A-1 & AIR 156-034A

Sanitary Sewer Improvements

ADDENDUM NO. 1

May 22, 2017

TO ALL PROSPECTIVE BIDDERS:

A. You are hereby notified of the following amendments to the Contract Documents/Specifications for the subject project.

1. Section 331203 – Submersible Pump, Part 1 Section 1.1, paragraph B shall be revised as follows:

B. The pumps shall be vertical, submersible, grinder, vertical discharge, close-coupled, centrifugal type pumps suitable for continuous operation in a wet pit installation. Two (2) pump units and all equipment shall be provided, including 60' of manufacturer supplied cable connected to each pump. The pumps shall be as manufactured by Flygt, KSB, Hydromatic, ABS or equal.

Revised Section 33 1203 is included with this addendum for reference.

2. Section 331203 – Submersible Pump, Part 2 Section 2.2, paragraph H shall be revised as follows:

H. Grinder Construction: Grinder assembly shall consist of a single rotating grinder impeller and a single stationary shredding ring/plate mounted directly below pump volute inlet. Grinder impeller shall thread onto shaft and shall be locked with a screw and washer. Shredding ring shall be held in place by a steel retaining clamp. Both shredding ring and grinder impeller shall be removable without dismantling pump. No adjustment of grinder assembly shall be necessary for proper grinder operation. Multiple grinder impeller assemblies requiring initial or periodic axial adjustment for proper operation shall not be considered equal. Grinder impeller and shredding ring shall be made of 440C stainless steel hardened to 56-60 Rockwell.

Revised Section 33 1203 is included with this addendum for reference.

3. Section 33 12 04 Pump Station Construction, Part 2, Section 2.1. paragraph J, paragraph 6 was added:

6. Monitoring: Pump station monitoring shall be supplied by Mission Communications and shall be coordinated with Owner.

Revised Section 33 1204 is included with this addendum for reference.

B. You are hereby notified of the following amendments to the Construction Plans for the subject project.

1. Sheets E1 – E3 Electrical Plans have been revised.

Revised Construction Plan Sheets No. E1-E3 are included with this addendum for reference.

C. All bidders must acknowledge receipt of this addendum in the space provided on page PF-3 of the Proposal Form. **Failure to acknowledge receipt of an addendum may be cause for rejection of the bid.**



SECTION 33 1203 - SUBMERSIBLE PUMP

PART 1 - GENERAL

1.1 SUMMARY

- A. This section covers the furnishing and installation of the submersible pumps complete with mechanical and electrical equipment, electrical services for the pumping station, and all miscellaneous work and appurtenances required to complete the pumping station to be ready for operation, including start-up and check of all equipment and operation.
- B. The pumps shall be vertical, submersible, grinder, vertical discharge, close-coupled, centrifugal type pumps suitable for continuous operation in a wet pit installation. Two (2) pump units and all equipment shall be provided, including 60' of manufacturer supplied cable connected to each pump. The pumps shall be as manufactured by Flygt, KSB, Hydromatic, ABS or equal.

1.2 SUBMITTALS

- A. Drawings and Data: Complete assembly, and installation drawings, together with detailed specifications and data covering material used, parts, devices, and other accessories forming a part of the equipment furnished, shall be submitted in accordance with the procedure set forth in the General Conditions. The data and specifications for each unit shall include, but shall not be limited to, the following:

1. Pump:

- a. Name of manufacturer.
- b. Type and model.
- c. Rotative speed.
- d. Size of pump outlet.
- e. Type of seal.
- f. Net weight of pump only.
- g. Complete performance curves showing capacity, head, NPSH requirements, efficiency, and bhp requirements.

2. Motor:

- a. Name of manufacturer.
- b. Type and model.
- c. Rated size of motor (hp).
- d. Temperature rating.
- e. Full load rotative speed.
- f. Weight.
- g. Input-output efficiency at:
 - 1) Full load.
 - 2) Rated pump condition.
- h. Full load current.
- i. Locked rotor current.
- j. Pump cable length and conductor size.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. Piping, Fittings and Valves: Piping, fittings and valves shall conform to the Sections 331113 and 331216.
- B. The pump manufacturer shall be responsible for and supply of pumps, pump controls, and incidental equipment necessary for an operable system. Items supplied shall in no way void the pump manufacturer's warranty.
- C. Pumps:

- 1. Materials for pump construction shall conform to the following specifications:

Casing	Cast Iron, ASTM A-48 Class 30
Impeller	Cast Brass or Ductile Iron
Shaft	416 Stainless Steel, AISI420
Bearings	Pre Lubricated Ball Bearing
Wear Rings	Cast Iron, ASTM A-48 Class 30
Seals	Silicon/Carbide - Lower and Carbon/Carbide - Upper

2.2 PERFORMANCE REQUIREMENTS

- A. Pumping heads and other terms shall be as defined in the Standards of the Hydraulic Institute. For design and rating purposes, the water to be pumped shall be assumed to have a temperature of 68° F. The pumping units shall be designed for the following operating conditions:

- 1. Pump Information:

<u>Duty Points</u>	<u>Single Operation</u>
Shut-off head, feet	65.0
Design operating capacity, gpm	50
Total head at design capacity, feet	60
Maximum rotative speed of pump, rpm	3450
Maximum bhp requirement at any head above minimum for continuous operation	3.0
Minimum nominal size of discharge flange, inches	3
Minimum shop test pressure, psi	125

2.3 GENERAL REQUIREMENTS

- A. Casing: Shall be manufactured from gray cast iron, ASTM A-48 Class 30. Casing design shall be centerline discharge with large radius on the cut water to prevent clogging.
- B. Pump Impeller: The impeller shall be a recessed vortex type to provide an open unobstructed passage through the volute for the ground solids. Impeller shall be cast brass or ductile iron and shall be threaded onto stainless steel shaft.
- C. Pump Shafting: The pump motor shaft shall be one piece 416 SST, rotating on two permanently lubricated ball bearings.
- D. Bearings: Motor shall have two heavy duty ball bearings to support pump shaft and take radial and thrust loads and a sleeve guide bushing directly above the lower seal to take radial load and act as flame path for seal chamber. Bearings to have a minimum B-10 life of 50,000 hours.
- E. Seals: Motor shall be protected by two mechanical seals mounted in tandem with a seal chamber between the seals. Seal chamber shall be oil filled to lubricate seal face and to transmit heat from shaft to outer shell.

Seal face shall be carbon and ceramic and lapped to a flatness of one light band.

- F. Seal Leak Detection: A mechanical seal failure protection shall be provided by a mechanical float switch located in a chamber above the seal. This switch shall be comprised of a magnetic float that actuates a dry reed switch encapsulated within the stem. Should the mechanical seal fail, liquid shall be directed into the float chamber, in which the rising liquid activates the switch opening the normally closed circuit. The float body and float shall be a polypropylene material with a 316ss stopper.
- G. Temperature Protection: Motor over temperature protection shall be provided by miniature thermal protectors embedded in the windings.
- H. Grinder Construction: Grinder assembly shall consist of a single rotating grinder impeller and a single stationary shredding ring/plate mounted directly below pump volute inlet. Grinder impeller shall thread onto shaft and shall be locked with a screw and washer. Shredding ring shall be held in place by a steel retaining clamp. Both shredding ring and grinder impeller shall be removable without dismantling pump. No adjustment of grinder assembly shall be necessary for proper grinder operation. Multiple grinder impeller assemblies requiring initial or periodic axial adjustment for proper operation shall not be considered equal. Grinder impeller and shredding ring shall be made of 440C stainless steel hardened to 56-60 Rockwell.
- I. Discharge Connection Elbow & Guide System: The discharge connection elbow shall be permanently installed in the basin wet well along with the discharge piping. The pump shall be automatically connected to the discharge connection elbow when lowered into place, and shall be easily removed for inspection or service. Sealing of the pumping unit to the discharge connection elbow shall be accomplished by a simple linear downward motion of the pump. A sliding guide bracket shall be an integral part of the pump unit. The entire weight of the pump unit shall be guided guide bars, pipes or cables, and shall press tightly against the discharge connection elbow creating a zero leakage seal between pump and discharge connection flange. Sealing of the discharge interface shall be by means of metal-to-metal contact without use of bolts, gaskets or o-rings.

Lower guide pipe shall be integral with the discharge connection. Guide apparatus shall be of at least schedule 40 weight 304SS stainless steel of the size indicated on the drawings. The guide apparatus shall not support any portion of the weight of the pump. No portion of the pump shall bear directly on the floor of the wet well. Stainless steel pull chains shall be provided with each pump unit, which allow for removal and reinstallation without the need to enter the wet well, and without removal of bolts, nuts, or other fasteners.

- J. Electric Motors: Submersible pump motor shall be squirrel-cage induction, shell type design, housed in an air-filled, watertight chamber, NEMA MG-1 Design B type, and shall be rated for 240 VAC, 1 phase, 60 Hz. The motor shall have built-in thermal overload protection and a moisture detection system. The motors shall be rated for NEC Class 1, Division 1, Group C & D (explosion proof). Provide 60' of manufacturer supplied cable connected to each pump
- K. Balance: All rotating parts shall be accurately machined and shall be in as nearly perfect rotational balance as practicable. Excessive vibration shall be sufficient cause for rejection of the equipment. The mass of the unit and its distribution shall be such that resonance at normal operating speeds is avoided.
- L. Shop Painting: All iron and steel parts which will be in contact with water after installation, except inside of the bowl assembly, shall be shop cleaned by sandblasting and painted with a suitable coating system. The coating system shall produce a dry film thickness of at least 10 mils and shall consist of a prime coat and one or more finish coats. Finish coat materials shall be furnished with each pump for field touch-up if necessary.
- M. Shop Tests: Each pump shall be tested at the factory for capacity, power requirement, and efficiency at minimum head for continuous operation, rated head, shutoff head, and at as many other points as necessary for accurate performance curve plotting. All tests shall be made in conformity with the requirements and recommendations of the Hydraulic Institute.
- N. Pump Station Controls & Equipment: Shall be as described in Section 331204.

PART 3 - EXECUTION

3.1 INSTALLATION OF PUMPS

- A. After assembly and installation on the concrete foundations, each pump shall be plumbed, aligned, and wedged in place but not grouted until after the initial fitting and alignment of connecting piping. Attention is directed to the requirements of the pipe sections concerning flanged connections to pumps.
- B. The base elbow shall be grouted in place with non-shrinking grout.

3.2 START-UP

- A. After installation of the equipment and prior to operation of the facility, all equipment shall be checked out and calibrated by an authorized factory representative. Installation certifications, test reports and warranties shall be submitted and the operator training session shall be conducted.

END OF SECTION 33 1203

SECTION 33 1204 – PUMP STATION CONSTRUCTION

PART 1 - GENERAL

1.1 SUMMARY

- A. The work in this section shall consist of items of construction for the submersible pump station, specifically including the wet well special coatings, pumps, valves and valve vault, controls and all incidentals necessary for the construction of the pump station.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. The materials shall conform to the respective Specifications described herein.
- B. Pumps: Submersible pumps shall conform to Section 331203.
- C. Pipe: Pipe and fittings shall conform to Section 331113.
- D. Valves: Valves shall conform to Section 331216.
- E. Valve Vault: Precast vault shall conform to Section 331100.
- F. Electrical: Electrical shall conform to Section 261000.
- G. General: Shop drawings for the float equipment and coatings shall be submitted to the Engineer for approval.
- H. Wet Well Coating: The interior surface of the pump station wet well shall receive a protective coating prior to operation. The coating shall conform to Section 099630.
- I. Protective Pipe Coatings: The exterior of all underground and wet pit ductile iron piping shall have a bituminous coating.

Dry pit ductile iron piping shall have a shop coat universal phenolic primer suitable for top coat painting.
- J. Pump Station Controls and Equipment:
 - 1. Motor Starter: Starters shall be rated in accordance with latest published NEMA standards for size and horsepower rating. Starters shall be mounted in a NEMA 1 enclosure unless otherwise indicated. Across-the-line starters shall be equipped with double break silver alloy contacts. Coils shall be of molded construction. All coils shall be replaceable from the front without removing the starter from the panel. Single-phase magnetic starters shall have solid state overload relays.
 - 2. Pump Control Panel: Input voltage shall be 120 VAC. The wet well level shall be monitored and controlled by 4 float switches with intrinsically safe barriers. Each intrinsically safe barrier shall include an input closed LED. Red LEDs shall indicate alarm input closed. An amber LED shall indicate stop float input closed.

Form "C" output contacts shall be provided for high level alarm. Normally open contacts shall be provided for pump control. Red LEDs shall indicate alarm output "ON". Green LEDs shall indicate pump control output "ON". Output contacts shall be rated 10 amps at 240 VAC or 30 VDC. Selector switches shall be provided to select pump sequence (1-2/Auto/2-1) and simplex or duplex operation.

A 0-3 minute adjustable time delay shall be provided to delay the starting of each pump. The primary pump start time delay shall be factory set at 5 seconds. The backup pump start time delay shall be factory set at 10 seconds.

Oil-tight "Hand-Off-Auto" selector switches shall be mounted in the front door of the control panel, one for each pump. A Red "run", push-to-test, 30.5 mm, indicating light shall be mounted in the front door of the control panel, one for each pump, to indicate pump activation.

Under normal conditions the pumps shall cycle between the common stop float and start lead float. If the level rises to the start backup float, the primary pump shall be stopped and the backup pump shall start and run until the stop float opens. If the level rises to the high level float, this will cause the external alarm light to flash and horn to sound along with activation of the auto-dialer. The pumps shall not restart until the primary pump start float closes.

An alarm light and horn reset pushbutton shall be provided to reset the light and horn upon correction of the level problem. The alarm reset pushbutton in the control panel shall silence the alarm horn, but keep the alarm light illuminated if the problem has not been corrected. Refer to SECTION: SUBMERSIBLE PUMPS for additional control panel requirements.

3. Nameplates: Black phenolic plates with engraved white letters shall be attached to the front of panels, starters and disconnects with screws.
4. Float Switch: The float switch for the duplex pump station (only) shall be a sealed float type mercury switch to indicate liquid level. The mercury tube switch shall be sealed in a solid 316 stainless steel float for corrosion and shock resistance. The float shall be Teflon coated and shall be 4-inch diameter (min.). The support wire shall have a heavy neoprene jacket. A weight shall be attached to the cord, or the cord shall be connected to a stainless steel wire rope, with weight, above the float to hold the switch in place.
5. Elapsed Time Meters: The meters shall be of the non-reset type suitable for panel mounting. Operating voltage shall be 120 V CA. The presentation shall be a six digit counter in hours and tenths of hours. The meters shall be equivalent to Redington Model 710-0002.
6. Monitoring: Pump station monitoring shall be supplied by Mission Communications and shall be coordinated with Owner.

PART 3 METHOD OF MEASUREMENT BASIS OF PAYMENT

A. METHOD OF MEASUREMENT

1. **Pump Station**: The installation of the pump station, wet well coating, piping, valve vault and controls shall be measured as a lump sum unit to include the furnishing of the submersible pump station equipment, wet well coating, piping, valves, access cover, fittings, connections, excavating, backfilling, equipment testing, furnishing and placement of concrete and reinforcing steel, startup and all other materials and other incidentals to provide a complete operable unit.

B. BASIS OF PAYMENT

1. The amount of completed and accepted work as provided above shall be paid for at the contract lump sum price bid for "New Pump Station". Price shall be full compensation for all labor, materials, equipment, tools and incidentals necessary to complete the work.


New Pump Station

- Per Lump Sum

END OF SECTION 33 1204

This page intentionally left blank.

Drawing Name: P:\Proj\2017\A17026 - Sanitary Sewer Improvements - Omar N Bradley Airport\CAD\Elec\E1-Electrical Site Plan Addendum#1.dwg May 22, 2017 - 10:52am



GENERAL NOTES:

- THIS IS A GENERAL LEGEND SHEET. SOME SYMBOLS AND ABBREVIATIONS MAY NOT BE USED ON THIS SPECIFIC PROJECT.
- ALL WORK SHALL CONFORM WITH THE 2014 NATIONAL ELECTRICAL CODE AND ALL STATE AND LOCAL CODES AND ORDINANCES AND O.S.H.A. WHERE MINIMUM CODE REQUIREMENTS ARE EXCEEDED BY THE REQUIREMENTS INDICATED IN THE SPECIFICATIONS AND ON THESE DRAWINGS, THE DRAWINGS AND SPECIFICATIONS SHALL TAKE PRECEDENCE. (IN THE CASE OF CODE CONFLICT DIRECTION SHALL BE TAKEN FROM THE MORE STRICT OF THE CONFLICTING CODES).
- CONDUIT ROUTES SHOWN ARE DIAGRAMMATIC ONLY. CONTRACTOR SHALL FIELD VERIFY AND PROVIDE CONDUIT ROUTES AS REQUIRED. CONTRACTOR IS RESPONSIBLE FOR ROUTING ALL CONDUITS NOT SHOWN ON THE DRAWINGS, INCLUDING BUT NOT LIMITED TO CONDUITS SHOWN ON THE ONE-LINE AND CONTROL DIAGRAMS AS WELL AS HOME RUNS SHOWN ON THE PLAN DRAWINGS. CONDUITS SHALL BE ROUTED AS DEFINED IN THE SPECIFICATIONS.
- AT THE CONCLUSION OF THIS PROJECT PROVIDE AN UPDATED TYPEWRITTEN, AS-BUILT DIRECTORY INSIDE EACH PANELBOARD/SWITCHBOARD PROPERLY IDENTIFYING EACH CIRCUIT USED & THE SPECIFIC LOAD SERVED. ALSO PROVIDE SCHEDULES ON CD DISK.
- OPENINGS SHALL BE CUT TO THE EXACT SIZE REQUIRED IN ORDER TO MAINTAIN ANY MATERIAL RATINGS AND SEALED TO MAINTAIN RATING. PROVIDE ALL NECESSARY FLOOR CUTTING/PENETRATIONS AND ALL OF THE RE-PATCHING FOR THE COMPLETE EXECUTION OF THIS WORK.
- CONCEAL ALL ELECTRICAL WIRING AND RACEWAYS WHERE CONSTRUCTION PERMITS. EXPOSED RACEWAY SHALL BE HELD TIGHT TO STRUCTURE & LOCATED SO AS TO KEEP IT AS INCONSPICUOUS AS POSSIBLE.
- INSTALL ANY/ALL CORD SETS SUPPLIED WITH THE EQUIPMENT.
- MOUNT DISCONNECT SWITCHES AND COMBINATION STARTERS AT 65" MAXIMUM ABOVE FINISHED GRADE TO TOP OF ENCLOSURE UNLESS OTHERWISE INDICATED.
- ALL SPARE WIRES SHALL BE TAPED AND COILED.
- PROVIDE FINAL CONNECTION, WIRING, HOOK-UP, ETC. FOR ALL EQUIPMENT AND CONTROLS REQUIRING ELECTRICAL POWER TO OPERATE. REFER TO THE I&C DRAWINGS FOR ADDITIONAL INFORMATION AND REQUIREMENTS.
- FURNISH AND INSTALL ALL WIRE, WIREWAY, CONDUIT, CONNECTORS, OUTLETS, ETC, NECESSARY TO ACHIEVE A COMPLETE AND WORKING INSTALLATION.
- IF EQUIPMENT SUPPLIED BY MANUFACTURER HAS A LARGER LOAD THAN VALUE SHOWN, THE CABLE CONDUIT AND ELECTRICAL EQUIPMENT SHALL BE ENLARGED, AS REQUIRED, TO ACCOMMODATE THE HIGHER VALUE.
- INFORMATION RELATED TO CIRCUIT IDENTIFICATION, WIRE & CONDUIT SIZES, AND ROUTING, IS ON THE FOLLOWING DRAWING TYPES.
 - ONE-LINE DIAGRAMS SHOW CIRCUIT IDENTIFICATION, WIRE QUANTITY AND SIZES, AND CONDUIT SIZE. ONE-LINE DIAGRAMS ALSO INDICATE ORIGIN AND DESTINATION OF CIRCUITS.
 - SITE PLANS INDICATE THE GENERAL ROUTING OF UNDERGROUND CONDUITS AND DUCT BANKS.

ABBREVIATIONS:

A	AMPERE, AMPS	H	HIGH OR HUMIDISTAT	N	NEUTRAL	W	WATTS
AC	ALTERNATING CURRENT	HC	HOT CIRCUIT	O	OPEN	WH	WATTHOUR METER
AF	AMPERE FRAME	HH	HANDHOLE	OD	OUTSIDE DIAMETER	WM	WATT METER
AT	AMPERE TRIP	HMT	HIGH MOTOR TEMPERATURE	OL	OVERLOAD	WP	WEATHERPROOF
AWG	AMERICAN WIRE GAGE	HOA	HAND-OFF-AUTO	OOA	ON-OFF-AUTO	WPI	WEATHERPROOF IN-USE
		HOR	HAND-OFF-REMOTE	OOR	ON-OFF-REMOTE	XP	EXPLOSION PROOF
		HP	HORSEPOWER	P	PRIMARY		
C	CLOSE, CONDUIT OR CONTACTOR	HWCO	HIGH WATER CUTOFF	PB	PULL BOX		
CAP	CAPACITOR	HZ	HERTZ (CYCLE)	PH, Ø	PHASE		
CB	CIRCUIT BREAKER	I/O	INPUT/OUTPUT	PS	PUMP STATION		
CKT	CIRCUIT	INST	INSTANTANEOUS	PVC	POLYVINYL CHLORIDE		
CP	CONTROL PANEL	J	JUNCTION BOX	2P	2 POLE		
		JB	JUNCTION BOX	R	RED, RAISE, RELAY OR REVERSE		
DPDT	DOUBLE POLE DOUBLE THROW	K	KEY INTERLOCK	RECPT.	RECEPTACLE		
DPST	DOUBLE POLE SINGLE THROW	KCMIL	THOUSAND CIRCULAR MIL	RGS	RIGID GALVANIZED STEEL		
DS	DISCONNECT SWITCH	KW	KILOWATT	RVSS	REDUCED VOLTAGE SOLID STATE STARTER		
E	ELECTRIC OPERATOR FOR CONTROL DAMPER OR VALVE	KWH	KILOWATT HOUR				
EC	EMPTY CONDUIT	L	LOW, LEVEL	S/E	SERVICE ENTRANCE RATED		
EX	EXISTING	LA	LIGHTNING ARRESTER	TB	TERMINAL BLOCK		
		LOA	LOCAL-OFF-AUTO	TTB	TELEPHONE TERMINAL BOX		
G	GREEN OR GROUND	LOR	LOCAL-OFF-REMOTE	TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSION		
GEN	GENERATOR	LS	LIMIT OR LEVEL SWITCH				
GFI	GROUND FAULT INTERRUPTER	LWCO	LOW WATER CUTOFF	UG	UNDERGROUND		
		MCB	MAIN CIRCUIT BREAKER	V	VOLTS		
				VA	VOLT AMPERE		
				VM	VOLTMETER		
				VS	VOLTMETER SWITCH		

ONE-LINE DIAGRAM AND DRAWING SYMBOLS:


	EXISTING TRANSFORMER WITH PRIMARY AND SECONDARY VOLTAGE, AND KVA RATING AS NOTED
	LOW VOLTAGE CIRCUIT BREAKER 1 POLE, 20 AMPERE
	FUSED DISCONNECT SWITCH
	DISCONNECT SWITCH
	GENERATOR RECEPTACLE
	DOUBLE THROW SWITCH
	NEW CONDUIT
	EXISTING CONDUIT

AMEREN UTILITY CONTACT INFORMATION:

CONTRACTOR SHALL INCLUDE ALL AMEREN COSTS IN BID.

COORDINATE THE TRENCHING INSPECTION AND CONNECTIONS TO THE EXISTING TRANSFORMER WITH AMEREN ENGINEERING DESIGN SPECIALIST:

DEBBIE L. HALLIBURTON-DERBOVEN
501 FRANKLIN STREET
MOBERLY, MO 65270
PHONE: 660-263-8115 EXT. 50456



LOCHNER

16105 W. 113th Street | Suite 107 | Lenexa, Kansas 66219
P 816.945.5840 | F 816.945.5841

SANITARY SEWER IMPROVEMENTS



OMAR N. BRADLEY AIRPORT
MOBERLY, MISSOURI

PROJECT NO.	000009582
DRAWN BY	DATE
MCC	05-04-17
CHECKED BY	DATE
CKB	05-04-17
DESIGNED BY	DATE
RBJ	05-04-17
REVISIONS	DATE
ADDENDUM #1	05-22-17

ELECTRICAL SITE PLAN

E1

Drawing Name: P:\Proj\2017\A17026 - Sanitary Sewer Improvements - Omar N Bradley Airport\CAD\Elec\E2- Enlarged Electrical Plans Addendum#1.dwg May 22, 2017 - 10:52am





1 ENLARGED ELECTRICAL UTILITY METER AND S/E DISCONNECT PLAN
SCALE: 3/16" = 1'-0"

GENERAL NOTES:

- SEE SHEET E1 FOR LEGEND, ABBREVIATIONS AND GENERAL NOTES.

PLAN NOTES:


- PROVIDE PVC COATED STEEL CONDUIT SEAL OFFS FOR ALL CONDUIT PENETRATIONS ENTERING THE WET WELL AND VALVE VAULT. INSTALL SEAL OFFS IN AN ACCESSIBLE LOCATION INSIDE OR WITHIN 10' OF THE WET WELL AND VALVE VAULT. COMPLY WITH NEC 501.15 FOR CLASS 1 DIVISION 1 SEALING REQUIREMENTS.
- 3"C. FOR AMEREN SECONDARY CABLES. SEE ONE-LINE DIAGRAM ON SHEET E3 FOR CONDUCTOR SIZE AND DETAIL 3 ON SHEET E4 FOR TRANSFORMER TO METER INSTALLATION DETAIL.



2 ENLARGED PUMP STATION ELECTRICAL PLAN
SCALE: 1/4" = 1'-0"



CUSTOM ENGINEERING
MECHANICAL & ELECTRICAL ENGINEERING
12760 East 40 Highway
Independence, Missouri 64055
816.350.1473
www.CUSTOMENGE2.com
MISSOURI CERTIFICATE OF AUTHORITY #000239



LOCHNER

16105 W. 113th Street | Suite 107 | Lenexa, Kansas 66219
P 816.945.5840 | F 816.945.5841

SANITARY SEWER IMPROVEMENTS

OMAR N. BRADLEY AIRPORT

MOBERLY, MISSOURI

PROJECT NO.	000009582
DRAWN BY	DATE
MCC	05-04-17
CHECKED BY	DATE
CKB	05-04-17
DESIGNED BY	DATE
RBJ	05-04-17
REVISIONS	DATE
ADDENDUM #1	05-22-17

ENLARGED
ELECTRICAL PLANS

E2

Drawing Name: P:\Proj\2017\A17026 - Sanitary Sewer Improvements - Omar N Bradley Airport\CAD\Elec\ES Electrical Details Addendum #1.dwg May 22, 2017 - 10:53am

