

LAMAR MUNICIPAL AIRPORT

MODOT PROJECT NO. 16-085A-1

CLEAN AND SEAL CRACKS, SEALCOAT, AND RE-MARK RUNWAY 3-21 AND CONNECTING TAXIWAYS

ADDENDUM NO. 1

March 25th, 2016

TO ALL PROSPECTIVE BIDDERS:

- A. You are hereby notified of the following amendments to the Construction Documents/Specifications for the subject project.
1. SECTION, MO-620 – RUNWAY AND TAXIWAY PAVEMENTS: The following paragraph and table are revised as follows:

620-2.3 REFLECTIVE MEDIA. Glass beads shall meet the requirements for **Federal Specification TT-B-1325D, Type I and Type III.** **Type III Glass Beads must be used on Holding Position Lines all other markings can be Type I.** Glass beads shall be treated with all compatible agents recommended by the manufacturer of the paint and reflective media to ensure adhesion and embedment.

TABLE 1. APPLICATION RATES FOR PAINT AND GLASS BEADS

Paint Type	Paint Square feet per gallon, ft ² /gal	Glass Beads, Type I, Gradation A Pounds per gallon of paint -- lb/gal	Glass Beads, Type III Pounds per gallon of paint—lb/gal	Glass Beads, Type IV Pounds per gallon of paint--lb/gal
Reflectorized White or Yellow	115 ft ² /gal Maximum	7 lb/gal Minimum	10 lb/gal Minimum	-
Non-Reflectorized Yellow or Black	115 ft ² /gal Maximum	-	-	-

- B. **IMPORTANT NOTE:** All bidders must acknowledge receipt of this addendum in the space provided on page PF-3 of the Proposal Form. **Failure to acknowledge receipt of an addendum may be cause for rejection of the bid.**