



# Clay County, Missouri

## Purchasing Department

16 W. Franklin, Suite 16-B ~ Liberty, MO 64068

---

### PURCHASING DEPARTMENT

#### IFB 19-20

### BRIDGE REPLACEMENT ON NE 148TH STREET OVER CARROLL CREEK. BRO-B024 (27) BRIDGE DEMOLITION, BRIDGE RECONSTRUCTION AND ROAD GRADING

#### ADDENDUM No. 1

Dear Vendor,

The original IFB remains in effect except as revised by the following changes, which shall take precedence over anything to the contrary in the specifications.

Except as amended by this Addendum, all terms and conditions of the IFB remain unchanged.

Please Note: The format for this addendum will detail questions asked, answers given and clarifications and statements made. Q = Question, A = Answer, C = Clarification and S = Statement.

**Q:** Are there Plans included with this Project?

**A:** See Attachment No. 1; BRO B024(27) - 148th St Bridge Replacement Sealed Plans 12-30-19.pdf

#### ACKNOWLEDGEMENT

Each bidder shall acknowledge receipt of this Addendum No. 1 of IFB 19-20, Bridge Replacement on NE 148th Street over Carroll Creek. Bro-B024 (27) Bridge Demolition, Bridge Reconstruction and Road Grading by their signature affixed hereto, and shall attach this Addendum to the original IFB.

#### CERTIFICATION BY BIDDER

SIGNATURE \_\_\_\_\_

TITLE \_\_\_\_\_



COMPANY \_\_\_\_\_


DATE \_\_\_\_\_

Cordially,


Clay County Purchasing Department








CONTROL PT #100  
X-E = 2840883.3070 STA 100+46.35  
Y-N = 1163347.8410 OFF 6.98' RT  
Z = 790.22  
CP #100 - 3/8"  
REBAR, NO CAP



CONTROL PT #101  
X-E = 2840881.2490 STA 100+86.39  
Y-N = 1163299.0570 OFF 29.10 RT  
Z = 788.89  
CP #101 - 1/2"  
REBAR & CAP "LS  
174D M&M LAND"



CONTROL PT #102  
X-E = 2840904.7210 STA 100+81.91  
Y-N = 1163317.8370 OFF 0.57 LT  
Z = 790.03  
CP #102 - 1/2"  
REBAR CAP ILL.

HORIZONTAL DATUM: (US SURVEY FEET)  
PID DK7492 CL 45 MISSOURI STATE PLANE (WEST ZONE)  
NORTHING: 355.811.181 METERS  
EASTING: 872.875.069 METERS  
CAF = 0.9999118823

SCALED AROUND 0.0  
1 METER = 3.28083333 U.S. SURVEY FEET  
MAPPING IS IN GROUND COORDINATES.

VERTICAL DATUM: (US SURVEY FEET)  
CL 45 (NGS PID DK7492) (NAVD88).  
ALUMINUM DISK IN CONCRETE STAMPED "MODNR CL-45  
1990", 34.5 FEET WEST OF THE CENTERLINE OF MISSOURI  
HIGHWAY 69, 0.15 MILE NORTH OF THE INTERSECTION WITH  
MISSOURI HIGHWAY 92.

NAVD88 DATUM ELEVATION: 964.6 FEET

148th P1 Curve 1			
P.C. Station	100+00.00	N 1,163,395.3079	E 2,840,880.3062
P.I. Station	100+49.09	N 1,163,346.4323	E 2,840,884.9061
P.T. Station	100+96.28	N 1,163,305.2365	E 2,840,911.5943


148TH P1 Curve 2			
P.C. Station	101+13.71	N 1,163,290.6111	E 2,840,921.0728
P.I. Station	101+63.32	N 1,163,248.9789	E 2,840,948.0538
P.T. Station	102+12.07	N 1,163,218.0440	E 2,840,986.8384

148TH P1 Curve 3			
P.C. Station	102+12.07	N 1,163,218.0440	E 2,840,986.8384
P.I. Station	103+74.94	N 1,163,116.4827	E 2,841,114.1709
P.T. Station	105+19.81	N 1,163,138.6595	E 2,841,275.5289

148TH P1 Curve 4			
P.C. Station	105+85.72	N 1,163,147.6328	E 2,841,340.8191
P.I. Station	106+59.28	N 1,163,157.6484	E 2,841,413.6924
P.T. Station	107+32.65	N 1,163,158.6884	E 2,841,487.2434

EAST ENTRANCE			
P.C. Station	10+29.30	N 1,163,126.2461	E 2,841,416.8616
P.I. Station	10+31.99	N 1,163,123.5752	E 2,841,417.0622
P.T. Station	10+34.62	N 1,163,120.9816	E 2,841,416.3193

WEST ENTRANCE			
P.C. Station	10+46.12	N 1,163,181.9904	E 2,840,958.0818
P.I. Station	10+56.47	N 1,163,173.8931	E 2,840,951.6234
P.T. Station	10+66.76	N 1,163,167.2914	E 2,840,943.6425



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH  
DISTRICT KC  
STATE MO  
SHEET NO.

COUNTY  
CLAY

JOB NO.  
36201A


CONTRACT ID.

PROJECT NO.  
BR0-B024(27)

BRIDGE NO.  
10700091

DESCRIPTION	DATE



CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300



WSP  
WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

REFERENCE AND  
COORDINATES  
SHEET

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

DISTRICT  
KC

STATE  
MO

SHEET NO.  
36201A

CONTRACT ID.

PROJECT NO.  
BRO-B024(27)

BRIDGE NO.  
10700091

DESCRIPTION

DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300



WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

PLAN SHEET

SHEET 4 of 62















**PROPOSED  
FENCE SHEET**



- |   |   |   |
|---|---|---|
| ① SILT FENCE<br>STA./OFF. 100+80.00 / 10.00' LT | ⑩ SILT FENCE<br>STA./OFF. 100+80.00 / 10.00' RT |   |
| ② SILT FENCE<br>STA./OFF. 100+80.00 / 20.00' LT | ⑪ SILT FENCE<br>STA./OFF. 100+80.00 / 18.00' RT |   |
| ③ SILT FENCE<br>STA./OFF. 101+75.00 / 28.00' LT | ⑫ SILT FENCE<br>STA./OFF. 101+40.00 / 33.00' RT |   |
| ④ SILT FENCE<br>STA./OFF. 103+15.00 / 47.00' LT | ⑬ SILT FENCE<br>STA./OFF. 101+88.00 / 31.00' RT |   |
| ⑤ SILT FENCE<br>STA./OFF. 104+90.00 / 58.00' LT | ⑭ SILT FENCE<br>STA./OFF. 102+02.00 / 65.00' RT |   |
| ⑥ SILT FENCE<br>STA./OFF. 107+00.00 / 35.00' LT | ⑮ SILT FENCE<br>STA./OFF. 102+19.00 / 69.00' RT | ⑲ SILT FENCE<br>STA./OFF. 105+05.00 / 50.00' RT |
| ⑦ SILT FENCE<br>STA./OFF. 107+38.00 / 20.00' LT | ⑯ SILT FENCE<br>STA./OFF. 102+45.00 / 50.00' RT | ⑳ SILT FENCE<br>STA./OFF. 105+75.00 / 32.00' RT |
| ⑧ SILT FENCE<br>STA./OFF. 107+41.00 / 15.00' LT | ⑰ SILT FENCE<br>STA./OFF. 103+13.00 / 90.00' RT | ㉑ SILT FENCE<br>STA./OFF. 106+45.00 / 35.00' RT |
| ⑨ SILT FENCE<br>STA./OFF. 107+41.00 / 10.00' LT | ⑱ SILT FENCE<br>STA./OFF. 103+60.00 / 63.00' RT | ㉒ SILT FENCE<br>STA./OFF. 106+50.00 / 42.00' RT |

TEMPORARY DITCH CHECK	
SILT FENCE DURING DEMOLITION	
SILT FENCE DURING CONSTRUCTION	
TEMPORARY BERM	
ROCK LINED DITCH(*) ROCK BLANKET TYPE 2	

(\*) INSTALL PERMANENT ROCK DITCH LINING DURING CONSTRUCTION

STATE OF MISSOURI  
LAWRENCE D. DUENGO  
10-31-19  
NUMBER  
PE-2011034796  
PROFESSIONAL ENGINEER

DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

STATE  
MO

DISTRICT  
KC

SHEET NO.

COUNTY  
CLAY

JOB NO.  
36201A

CONTRACT ID.

PROJECT NO.  
BRO-B024(27)

BRIDGE NO.  
10700091

DESCRIPTION

DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943


TEMPORARY  
EROSION  
CONTROL SHEET

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.

SHEET 9 of 62



- ⑩ WATERLINE PI  
EXIST. STA. / OFF 103+25.47 / 83.23'
- ⑪ WATERLINE INTERSECTION WITH CREEKBED  
EXIST. STA. / OFF / ELEV. 104+34.58 / 54.24 / 757.49'
- ⑫ WATERLINE INTERSECTION WITH DITCH  
PROP. STA. / OFF / ELEV. 105+26.03 / 38.40 / 771.73'
- ⑬ WATERLINE PI  
EXIST. STA. / OFF 106+65.69 / 32.05'




STATE OF MISSOURI  
LAWRENCE D. OGDEN  
10-31-19  
NUMBER  
PE-2011034796  
PROFESSIONAL ENGINEER

DATE	
09/23/2019	
DATE PREPARED	
09/23/2019	
ROUTE	STATE
148TH	MO
DISTRICT	SHEET NO.
KC	
COUNTY	
CLAY	
JOB NO.	
36201A	
CONTRACT ID.	
PROJECT NO.	
BRO-BQ24(27)	
BRIDGE NO.	
10700091	


[illegible]

CLAY COUNTY, MISSOURI HIGHWAY DEPARTMENT	16616 NE 116TH STREET KEARNEY, MO 64060 PHONE: (816) 407-3300
---	---



**WSP**  
WSP USA Inc.  
100 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

# EXISTING UTILITY LOCATIONS SHEET



STATE OF MISSOURI

LAWRENCE D. DUDENKO

10-31-19

NUMBER

PE-2011034796

PROFESSIONAL ENGINEER

DATE

09/23/2019

DATE PREPARED

09/23/2019

ROUTE

148TH

STATE

MO

DISTRICT

KC

SHEET NO.

COUNTY

CLAY

JOB NO.

36201A

CONTRACT ID.

PROJECT NO.

BRO-B024(27)

BRIDGE NO.

10700091

DESCRIPTION	DATE
CLAY COUNTY, MISSOURI	
HIGHWAY DEPARTMENT	
16616 NE 116TH STREET	
KEARNEY, MO 64060	
PHONE: (816) 407-3300	

WSP

WSP USA Inc.

300 Wyandotte Street

Suite 200

Kansas City, MO 64105

913.310.9943


RIGHT OF WAY  
PLAN

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.


SHEET 12 of 62








PLAN VIEW



DRIVEWAY TYPICAL SECTION



IN FILLS

PROFILE VIEW

IN CUTS

DRIVEWAY SIDE SLOPES: \*

1 TO 1700 VEHICLES PER DAY ON STATE ROUTE USE 3:1 SLOPE (OR 6:1 SLOPE WHERE PRACTICABLE).

OVER 1700 VEHICLES PER DAY ON STATE ROUTE USE 6:1 SLOPE (OR FLATTER WHERE PRACTICABLE).

NOTE: RECOMMENDED WIDTH OF DRIVEWAY - 20'

\* IN ORDER TO MINIMIZE THE USE OF 6:1 SLOPED END PIPE SECTIONS ON NEW CONSTRUCTION AND WHERE POSSIBLE ON EXISTING ROUTES, THE LOCATION OF DRAINAGE PIPE SHOULD BE BEYOND THE CLEAR ZONE DISTANCE AS SHOWN IN TABLE 3.1 OF THE 1988 EDITION OF "ROADSIDE DESIGN GUIDE".

GENERAL NOTES:



NO PART OF THE DRIVEWAY EXCLUDING TAPERS SHALL BE CONSTRUCTED BEYOND THE PROPERTY FRONTAGE.

SURFACING SHALL BE AS SHOWN ON THE PLANS OR PERMIT.

LENGTH OF PIPE SHALL BE DETERMINED BY DEPTH AND LOCATION OF DITCH. (MINIMUM 32' LENGTH OF MINIMUM 15" DIAMETER PIPE), SEE PLANS.


THIS DRAWING ILLUSTRATES DRIVEWAY DETAILS FOR MINIMUM SITUATIONS. TRAFFIC VOLUMES, SAFETY CONSIDERATIONS, LOCAL REQUIREMENTS, ETC., MAY DICTATE MORE EXTENSIVE IMPROVEMENTS THAN ILLUSTRATED.

<p><b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b></p> <p>105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)</p>	
<p>KATHRYN PHILLIPS HARVEY NUMBER PE-23751 PROFESSIONAL ENGINEER</p> <p>THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY.</p>	<p><b>DRIVEWAY</b></p> <p><b>TYPE I</b></p>
<p>DATE EFFECTIVE: 07/01/2004</p> <p>DATE PREPARED: 8/21/2009</p>	<p><b>203.61A</b></p>
<p>SHEET NO. 1 OF 1</p>	



TYPICAL FENCE LOCATION

GATE OPENING	GATE POST SIZE	#/FT.
≤ 6'	2" DIA.	3.65
≤ 13'	2 1/2" DIA.	5.79
≤ 18'	3 1/2" DIA.	9.10
> 18'	6" DIA.	18.97
GATE FRAME	1 1/2" DIA.	2.72



- BRACES
- WIRE TIES
- 3.8" ADJUSTABLE TRUSS RODS.

#### GENERAL NOTES:

STEEL LINE POSTS SHALL BE OF AN APPROVED "U", "Y", "T" OR CHANNEL SECTION, NOTCHED OR STUDDED WITH AN ANCHOR PLATE. POST PUNCHED WITH HOLES OR SELF FASTENING LUGS WILL NOT BE PERMITTED.

STAPLES SHALL BE SCREW SHANK TYPE OR EQUIVALENT (1 1/4" MINIMUM LENGTH).

STRETCHED FABRIC AND BARBED WIRE ON OUTSIDE OF POST ON CORNERS AND CURVES.

ATTACHMENT OF FABRIC TO STEEL LINE POSTS IN ACCORDANCE WITH MANUFACTURE'S RECOMMENDATION.

GATES FOR WOVEN WIRE FENCE SHALL BE IN ACCORDANCE WITH SEC 607.20 AND 1043.3.6 OF THE STANDARD SPECIFICATIONS. EXCEPT THE FILLER SHALL BE WOVEN WIRE FABRIC OF THE SAME KIND AS USED FOR THE FENCE.

SINGLE LEAF GATES REQUIRE UP TO 12" OPENING. DOUBLE LEAF GATES REQUIRE OVER 12" OPENING. DIRECTION OF SWING OF GATES SHALL BE AS INDICATED ON THE PLANS OR AS DIRECTED BY THE ENGINEER.

**MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION**

105 WEST CAPITOL  
JEFFERSON CITY, MO 65102  
1-888-ASK-MODOT (1-888-275-6636)

**WOVEN WIRE FENCE**


THIS SHEET HAS BEEN SIGNED, SEALED AND DATED ELECTRONICALLY.

DATE EFFECTIVE: 07/01/2016


DATE PREPARED: 5/13/2016

607.20G

SHEET NO.  
1 OF 2





FLAT BOTTOM DITCH  
WITHOUT BEDDING MATERIAL




FLAT BOTTOM DITCH  
WITH BEDDING MATERIAL  
TYPICAL DITCH LINER DETAILS


TYPE	ROCK DITCH LINER MIN. THICKNESS	BEDDING MATERIAL MIN. THICKNESS
1	8"	--
2	12"	--
3	22"	8"
4	30"	12"

 <b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b> 105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)	
	<b>ROCK DITCH LINER</b>
DATE EFFECTIVE: 03/01/1993 DATE PREPARED: 8/21/2009	<b>609.60C</b>
SHEET NO. 1 OF 1	






IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



**MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION**

105 WEST CAPITOL  
JEFFERSON CITY, MO 65102  
1-888-ASK-MODOT (1-888-275-6636)




**CONCRETE SLOPE PROTECTION**

DATE EFFECTIVE: 07/01/2015  
DATE PREPARED: 5/29/2015

**611.60R**

SHEET NO.  
1 OF 1

ROCK DITCH CHECK



SECTION A-A


\* GEOTEXTILE LINING MAY BE INSTALLED AS REQUIRED BY THE ENGINEER.

NOTE:

ROCK DITCH CHECK IN THE CLEAR ZONE SHALL BE REMOVED OR LEVELED (IF ALLOWABLE) AFTER THE VEGETATION HAS SUFFICIENTLY MATURED TO PROTECT THE DITCH OR SWALE.


EXAMPLE  
DITCH CHECK SPACING  
FOR STANDARD HEIGHTS  
(FT.)

DITCH @ SLOPE %	SPACING FOR 9" EFF. HEIGHT	SPACING FOR 18" EFF. HEIGHT
0.5	150	300
1.0	75	150
1.5	50	100
2.0	37	75
2.5	30	60
3.0	25	50
3.5	21	43
4.0	19	38
4.5	16	33
5.0	15	30
5.5	13	27
6.0	12	25
6.5	11	23
7.0	10	21
7.5	10	20
8.0	9	19
8.5	9	18
9.0	8	17
9.5	8	16
10.0	7	15




MINIMUM DITCH CHECK SPACING


ALTERNATE DITCH CHECK




PLAN VIEW



SECTION B-B



TYPICAL SECTION  
VEE DITCH



TYPICAL SECTION  
TRAPEZOIDAL DITCH

NOTES:

USE MINIMUM 12 IN. DIAMETER LOG/SOCK.

USE 2 FT. WOODEN STAKES WITH A 2 IN. BY 2 IN. NOMINAL CROSS SECTION.

INSTALL LOG/SOCK TO A HEIGHT IN DITCH SO FLOW WILL NOT WASH AROUND LOG/SOCK AND SCOUR DITCH SLOPES OR AS DIRECTED BY ENGINEER.

INSTALL A MINIMUM OF 2 UPSLOPE STAKES AND 4 DOWNSLOPE STAKES AT AN ANGLE TO WEDGE LOG/SOCK TO BOTTOM OF DITCH.

EROSION CONTROL BLANKET SHALL BE ANCHORED ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.

GENERAL NOTES:

OTHER PROPRIETARY DITCH CHECKS MAY BE SUBSTITUTED IN ACCORDANCE WITH SEC 806 OR AS DIRECTED BY THE ENGINEER.

INSTALLATION OF PROPRIETARY DITCH CHECKS SHALL BE ACCORDING TO THE MANUFACTURER'S RECOMMENDATIONS.

MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION

105 WEST CAPITOL  
JEFFERSON CITY, MO 65102  
1-888-ASK-MODOT (1-888-275-6636)

STATE OF MISSOURI  
ERIC E. SCHROETER  
NUMBER PE-28411  
PROFESSIONAL ENGINEER

THIS SHEET HAS BEEN  
SIGNED, SEALED AND DATED  
ELECTRONICALLY.




TEMPORARY EROSION  
CONTROL MEASURES  
TEMPORARY DITCH CHECKS

DATE EFFECTIVE: 04/01/2015  
DATE PREPARED: 2/20/2015


806.10J

SHEET NO.  
1 OF 6





## TEMPORARY SLOPE DRAIN INLET TREATMENT



NOTE:


IN SOME CASES IT MAY BE NECESSARY TO EMBED METAL OR PLASTIC PIPE INTO THE FILL SLOPE TO SECURE PROPER ANCHORAGE.

## TEMPORARY BERM


(METAL, FLEXIBLE RUBBER OR PLASTIC PIPE)

NOTE:

MAXIMUM LENGTH BETWEEN SLOPE DRAINS SHALL BE APPROXIMATELY 500 FEET.




		<b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b> 105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)	
		<b>TEMPORARY EROSION CONTROL MEASURES</b> SLOPE DRAINS	
DATE EFFECTIVE: 04/01/2015 DATE PREPARED: 2/20/2015		<b>806.10J</b> SHEET NO. 4 OF 6	




DETAIL A


TYPICAL B-B




DETAIL A




PLAN VIEW



ELEVATION DETAIL  
FABRIC SILT FENCE



PERIMETER SILT FENCE  
FOR TRANSVERSE FLOW



PERIMETER SILT FENCE  
FOR ANGULAR FLOW

GENERAL NOTES:

USE SILT FENCE FOR FILL HEIGHTS GREATER OR EQUAL TO 10 FEET. ON ALL FILLS GREATER THAN 10 FEET HIGH, MID-SLOPE RUNS OF SILT FENCE SHOULD BE CONSIDERED.


FOR FABRIC SILT FENCE:

MINIMUM LONGITUDINAL SPLICE OVERLAP SHALL BE 2' WITH A POST AT EACH END.



SECURE FABRIC TO POSTS.


INSTEAD OF SILT FENCE ACROSS DRAINAGE DITCHES AND DRAINS, DITCH CHECKS SHALL BE USED AS SHOWN ON PLANS OR AS DIRECTED BY ENGINEER.

AT CULVERTS, PLACE SEDIMENT BARRIERS OVER THE TOP OF THE CULVERTS (NOT IN THE STREAM CHANNEL).




MINIMUM J-HOOK SPACING


 <b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b> 105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)	
	<b>TEMPORARY EROSION CONTROL MEASURES</b> <b>SILT FENCE</b>
DATE EFFECTIVE: 04/01/2015 DATE PREPARED: 2/20/2015	<b>806.10J</b>
SHEET NO. 5 OF 6	




ONE POST - SINGLE SIGN




ONE POST - SINGLE SIGN WITH SUPPLEMENTAL PLAQUE




TWO POST



CHEVRON SIGN



TYPE III OBJECT MARKER



ADJACENT TO CURB



GENERAL NOTES:

SIGN MOUNTING BOLTS SHALL BE INSTALLED WITH A NYLON WASHER AGAINST THE SIGN FACE WITH A STEEL WASHER BETWEEN THE NYLON WASHER AND BOLT HEAD.


A LOCKNUT SHALL BE USED TO FASTEN THE SIGN TO THE POST.

VERTICAL CLEARANCE FROM THE ROADWAY SHALL BE MET AND INCREASED ONLY TO MEET THE 5' MINIMUM VERTICAL CLEARANCE FROM THE GROUND.


HORIZONTAL OFFSET MAY BE ADJUSTED BASED ON FIELD CONDITIONS.

 <b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b> 105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)	
	<b>SIGN MOUNTING DETAILS</b> <b>MOUNTING HEIGHT &amp; OFFSET</b> <b>PIPE POSTS, PSST, WOOD</b> <b>&amp; U-CHANNEL POSTS</b>
DATE EFFECTIVE: 07/01/2017 DATE PREPARED: 5/1/2017	SHEET NO. <b>903.03BL</b> 10 OF 16


MOUNTING HEIGHT DETAILS




### LOCATION SURVEY RIGHT-OF-WAY MARKER



### WITNESS POST



IN EARTH



IN ROCK


### DRAIN MARKER


#### GENERAL NOTES:

WHEN STEEL AND LOCATION SURVEY R/W MARKERS ARE NOT SUITABLE DUE TO NATURAL GROUND FEATURES OR MAN-MADE STRUCTURES, ALTERNATIVE MONUMENTATION (IN COMPLIANCE WITH THE APPROVED MONUMENTATION, AS SPECIFIED BY THE MISSOURI MINIMUM STANDARDS FOR PROPERTY BOUNDARY SURVEYS) MAY BE SET.

<b>MISSOURI HIGHWAYS AND TRANSPORTATION COMMISSION</b> 105 WEST CAPITOL JEFFERSON CITY, MO 65102 1-888-ASK-MODOT (1-888-275-6636)	
	<b>RIGHT-OF-WAY AND DRAIN MARKERS</b>
DATE EFFECTIVE: 01/01/2003 DATE PREPARED: 8/21/2009	<b>602.00D</b>
SHEET NO. 1 OF 2	

Hydrologic Data
Drainage Area = 14.0 mi <sup>2</sup>
Design Flood Frequency = 25 years
Design Flood Discharge = 3,553 cfs
Design Flood (D.F.) Elevation = 781.11 ft
Base Flood (100-year)
Base Flood Elevation = 784.13 ft
Base Flood Discharge = 4,911 cfs
Estimated Backwater = -0.83 ft
Average Velocity thru Opening = 3.29 ft/s
Freeboard (50-year)
Freeboard = 0.2 ft
Roadway Overtopping
Overtopping Flood Discharge = 5,300 cfs
Overtopping Flood Frequency = > 100 years
Overtopping Flood Elevation = 784.94 ft




"" Indicates location of borings.

### Notice and Disclaimer Regarding Boring Log Data

The locations of all subsurface borings for this structure are shown on the plan sheet(s) for this structure. The boring data for all locations indicated, as well as any other boring logs or other factual records of subsurface data and investigations performed by the department for the design of the project, are shown on Sheet(s) No. 45-47 or will be available from the Project Contact upon written request. No greater significance or weight should be given to the boring data depicted on the plan sheets than is given to the subsurface data available from the district or elsewhere.

The Commission does not represent or warrant that any such boring data accurately depicts the conditions to be encountered in constructing this project. A contractor assumes all risks it may encounter in basing its bid prices, time or schedule of performance on the boring data depicted here or those available from the district, or on any other documentation not expressly warranted, which the contractor may obtain from the Commission.



B.M. #100 - Sta. 100+46.35, 6.98' RT.  
Elev. 790.22  
3/8" Rebar, No Cap

B.M. #101 - Sta. 100+86.39, 29.10' RT.  
Elev. 788.89  
1/2" Rebar & Cap "LS 174D M&M Land"

B.M. #102 - Sta. 100+81.91, 0.57' LT.  
Elev. 790.03  
1/2" Rebar Cap ILL.

BRIDGE: ROUTE 148TH OVER  
CARROLL CREEK  
STA. 103+33.12

STD. 609.00
STD. 617.10
STD. 706.35
STD.

Designed	Nov.	2018
Detailed	Nov.	2018
Checked	Feb.	2019

Note: This drawing is not to scale. Follow dimensions.

ESTIMATED QUANTITES				
Item		Substr.	Superstr.	Total
Class 1 Excavation	Cu. Yd.	308.0	-	308.0
Removal of Bridges	Lump Sum	-	-	1
Bridge Approach Slab (Minor Road)	Sq. Yd.	-	380	380
Galvanized Structural Steel Piles (12 in.)	Lin. Ft.	1,934	-	1,934
Dynamic Pile Testing	Each	4	-	4
Pile Point Reinforcement	Each	33	-	33
Class B Concrete (Substructure)	Cu. Yd.	204.3	-	204.3
Class B-2 Concrete (Haunched Slab)	Sq. Yd.	-	629	629
Reinforcing Steel (Bridges)	Lbs.	8,580	-	8,580
Reinforcing Steel (Epoxy Coated)	Lbs.	-	129,060	129,060
Vertical Drain at End Bents	Each	-	-	2
* Safety Barrier Curb	Lin. Ft.	-	330	330
** Safety Barrier Transition	Lin. Ft.	-	120	120

- \* Safety Barrier Curb on the bridge shall be Cast-in-Place option or Slip-Form option.  
\*\* Safety Barrier Transition on the approach slab shall be Cast-in-Place.

GENERAL NOTES:

DESIGN SPECIFICATIONS:  
2017-AASHTO LRFD Bridge Design Specifications (8th Ed.)  
Seismic Design Category A.

CONSTRUCTION SPECIFICATIONS:  
2019-Missouri Standard Specifications for Highway Construction

DESIGN LOADING:  
HL-93 (LRFD Superstructure, LRFD Substructure)  
35 lb/sf. Future Wearing Surface.  
Earth 120 lb/cf. Equivalent Fluid Pressure 45 lb/cf.  
Superstructure: Simply-supported, non-composite for dead loads.  
Continuous composite for live load.

DESIGN UNIT STRESSES:  
Class B Concrete (Substructure) f'c = 3,000 psi  
Class B-1 Concrete (Safety Barrier Curb) f'c = 4,000 psi  
Class B-2 Concrete (Superstructure) f'c = 4,000 psi  
Reinforcing Steel (Grade 60) fy = 60,000 psi  
Steel Pile (ASTM A709 Grade 50) fy = 50,000 psi

EMBANKMENT:  
Complete embankment as shown on the plans prior to driving the  
End Bent piling or commencing with the End Bent footing  
excavation.

DRIVEN PILES:  
This work shall consist of furnishing and driving steel load-bearing  
piles to the minimum nominal axial compressive resistance and  
penetration required per Sec 702, at the location shown on the plans.  
Dynamic Pile Testing shall be performed during pile installation to  
ensure pile integrity and capacity (See Special Provisions).

A minimum of one Dynamic Pile Test shall be done at each bent. No  
re-strike is required.

All piles shall be galvanized, in accordance with Sec. 702, the full  
length of pile or to the minimum galvanization penetration (elevation).  
Pile point reinforcing need not be galvanized. Shop drawings will not be  
required for pile point reinforcement.

FALSEWORK PLANS:  
A licensed Professional Engineer shall design the falsework details.  
Details shall bear the seal of a licensed Professional Engineer. Submit  
electronic plans with details in compliance with MoDOT Specifications Sec  
703 to the Field Engineer to review.

FALSEWORK PLANS AND SHOP DRAWINGS:  
Use the U.S. Customary system of units on falsework plans and  
shop drawing details.

FALSEWORK:  
Leave the falsework in place for the entire unit until 15 days after the  
last concrete pour for the unit or until the concrete has attained the  
required compressive strength as stated in Sec 703, whichever is longer  
as directed by the Engineer.

FORMWORK:  
Slab shall be cast-in-place with conventional forms. Precast prestressed  
panels and stay-in-place corrugated steel forms will not be permitted.

Method of forming the slab shall be as shown on the plans and in accordance  
with Sec 703. All hardware for forming the slab to be left in place as a  
permanent part of the structure shall be coated in accordance with ASTM  
A123 or ASTM B633 with a thickness Class SC4 and a finish Type 1, II or  
III.

JOINT FILLER:  
All joint filler shall be in accordance with Sec 1057 for preformed  
sponge rubber expansion and partition joint filler, except as noted.

FOUNDATION DATA						
Type	Design Data	Unit	Bent Number			
			1	2	3	4
Load Bearing Pile	Pile Type and Size		HP 12x53	HP 12x53	HP 12x53	HP 12x53
	Number	each	6	11	11	5
	Approximate Length Per Each	ft.	61	60	58	55
	Pile Point Reinforcement	each	All	All	All	All
	Min. Galvanized Penetration (Elev.)	ft.	Full Length	Full Length	Full Length	Full Length
	Est. Max Scour Depth 100 (Elev.)	ft.	-	751.62	751.62	-
	Min. Tip Penetration (Elev.)	ft.	Min. Embed	Min. Embed	Min. Embed	Min. Embed
	Criteria for Min Tip Penetration		Lateral Stability	Lateral Stability	Lateral Stability	Lateral Stability
	Pile Driving Verification Method		DT	DT	DT	DT
	Minimum Nominal Axial Compressive Resistance	kip	110	160	160	110

DT = Dynamic Testing  
Load Bearing Pile:  
Minimum Nominal Axial Compressive Resistance =  
Maximum Factored Loads / Resistance Factor  
Manufactured pile point reinforcement shall be used  
on all piles in this structure at all Bents.

ESTIMATED QUANTITIES:

ESTIMATED QUANTITIES FOR HAUNCHED SLAB		
Item	Unit	Total
Class B-2 Concrete (Haunched Slab)	Cu. Yd.	445

GENERAL NOTES CONT'D:

CONCRETE:  
Bevel all exposed edges of all concrete with 3/4 inch triangular  
molding, except as otherwise noted on the plans, per Sec 703.  
Construction joints are optional with the Contractor, but if used,  
place only at locations shown, or at locations approved by the Engineer.

SLAB ELEVATIONS:  
The Contractor shall record elevation readings on the "Slab Elevations"  
sheet in the table at locations designated by a "(2)". The Contractor  
shall submit the table on a half-sized sheet to the Engineer.

PIER BEAM CONSTRUCTION:  
Cure the Int. Bent walls as required by MoDOT before beginning the pier  
beam construction (placing resteel or formwork). Do not drill and grout  
bolts or other devices into the Int. Bent walls used for falsework  
support unless approved by the Engineer. Cure Int. Bent walls as required  
by the MoDOT Specs. before beginning to place superstructure concrete.


REINFORCING STEEL:  
Minimum clearance to reinforcing steel shall be 2", unless otherwise  
shown. Epoxy coat all reinforcing steel in the End Bents, deck slab,  
and barriers. Where non-coated bars come in contact with epoxy coated  
bars, they need not be coated.

Due to curvature requirements from ACI, some of the slab reinforcing  
steel will need to be prefabricated following ACI detailing guidelines.  
See Sh. #43 for details.

BARRIER:  
Build the bridge barrier after the falsework is struck.

TRAFFIC HANDLING:  
Route 148 to be closed during construction.


BACKFILL COMPACTION:  
Compact backfill at the End Bents.



GENERAL NOTES AND SUMMARY OF ESTIMATED QUANTITIES

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

STATE  
MO

DISTRICT  
KC

SHEET NO.

COUNTY  
CLAY

JOB NO.  
36201A


CONTRACT ID.

PROJECT NO.  
BRO-B024(27)

BRIDGE NO.  
10700091

DESCRIPTION	DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT




16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300


WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

GENERAL NOTES  
& SUMMARY OF  
QUANTITIES











Reinforcing Steel in Top of Pier Beam  
Reinforcing Steel in Bottom of Pier Beam  
PLAN  
(Looking Ahead Station)  
(Dimensions along  $\mathcal{C}$  Int. Bent No. 2)

NOTE: Field cut #8PB5 and #7PB4 bars at 6" chamfer (bott. pier beam only) (touch with epoxy after cutting)

Item	Unit	Total
Class 1 Excavation	Cu. Yd.	164.3
Galvanized Structural Steel Piles (12in)	Lin. Ft.	662
Dynamic Pile Testing	Each	1
Pile Point Reinforcement	Each	11
Class B Concrete (Substructure)	Cu. Yd.	107.9

These quantities are included in the Estimated Quantities table on Sheet No. 23.




STEEL PILE SPLICE  
(If required)

**\*\* Top of Pile Elevations**

Int. Bent No. 2	P7	P8	P9
Top of Pile EL	783.84	783.94	784.05
Pile Length (ft)	60.0	60.0	60.0
Int. Bent No. 2	P10	P11	P12
Top of Pile EL	784.15	784.26	784.37
Pile Length (ft)	60.0	60.0	60.0
Int. Bent No. 2	P13	P14	P15
Top of Pile EL	784.47	784.58	784.69
Pile Length (ft)	60.0	60.0	60.0
Int. Bent No. 2	P16	P17	
Top of Pile EL	784.80	784.91	
Pile Length (ft)	61.0	61.0	

See "As-built Pile Data" sheet for pile number designations



SECTION THRU BENT  
(Dimensions at  $\mathcal{C}$  Bent)

- LEGEND**
- EF = Each Face
  - FF = Far Face
  - NF = Near Face
  - \* Slope 4.0% Normal to  $\mathcal{C}$  Roadway
  - \*\* See this sheet for Top of Pile Elevations table
  - \*\*\* Galvanizing material shall be omitted or removed 1 inch clear of weld locations in accordance with Sec. 702.

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.

DATE  
09/23/2019  
DATE PREPARED  
09/23/2019  
ROUTE  
148TH  
STATE  
MO  
DISTRICT  
KC  
SHEET NO.  
COUNTY  
CLAY  
JOB NO.  
36201A  
CONTRACT ID.  
PROJECT NO.  
BR0-B024(27)  
BRIDGE NO.  
10700091

DESCRIPTION


DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT


16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

**WSP**  
WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943


**INTERMEDIATE  
BENT NO. 2**



PLAN  
(Looking Ahead Station)  
(Dimensions along & Int. Bent No. 3)



ELEVATION



NOTE: Field cut #8PB12 and #7PB11 bars at 6" chamfer (bott. pier beam only)(touch with epoxy after cutting)


**\*\*Top of Pile Elevations**

Int. Bent No. 3	P18	P19	P20
Top of Pile EL	783.54	783.65	783.76
Pile Length (ft)	57.0	57.0	58.0
Int. Bent No. 3	P21	P22	P23
Top of Pile EL	783.87	783.99	784.10
Pile Length (ft)	58.0	58.0	58.0
Int. Bent No. 3	P24	P25	P26
Top of Pile EL	784.21	784.32	784.44
Pile Length (ft)	58.0	58.0	58.0
Int. Bent No. 3	P28	P29	
Top of Pile EL	784.55	784.66	
Pile Length (ft)	58.0	58.0	

See "As-built Pile Data" sheet for pile number designations

Item	Unit	Total
Class 1 Excavation	Cu. Yd.	143.7
Galvanized Structural Steel Piles (12in)	Lin. Ft.	636
Dynamic Pile Testing	Each	1
Pile Point Reinforcement	Each	11
Class B Concrete (Substructure)	Cu. Yd.	96.4

These quantities are included in the Estimated Quantities table on Sheet No. 23.



SECTION THRU BENT  
(Dimensions at & Bent)

LEGEND

- EF = Each Face
- FF = Far Face
- NF = Near Face
- \* Slope 4.0% Normal to & Roadway
- \*\* See this sheet for Top of Pile Elevations table
- \*\*\* Galvanizing material shall be omitted or removed 1 inch clear of weld locations in accordance with Sec. 702.

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.

DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

DISTRICT  
KC

COUNTY  
CLAY

JOB NO.  
36201A

CONTRACT ID.

PROJECT NO.  
BR0-B024(27)

BRIDGE NO.  
10700091

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT


16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**INTERMEDIATE  
BENT NO. 3**


IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.






ELEVATION OF WING


ELEVATION OF END BENT



DETAIL A



PLAN OF END BENT




ELEVATION OF WING

PART PLAN

OPTIONAL TURNED DRAIN  
(Only if rock is encountered outside of wing)

VERTICAL DRAIN AT END BENTS  
(Squared end bent shown, skewed end bent similar)



PART SECTION A-A  
(Section thru wing similar)


General Notes:

All drain pipe shall be sloped 1 to 2 percent.

Drain pipe may be either 6-inch diameter corrugated metallic-coated steel pipe, underdrain, 4-inch diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4-inch diameter corrugated polyethylene (PE) drain pipe.

Drain pipe shall be placed at fill face of end bent and inside face of wings. The pipe shall slope to lowest grade of ground line, also missing the lower beam of end bent by a minimum of 1 1/2 inches.

Perforated pipe shall be placed at fill face side and inside face of wings at the bottom of end bent and plain pipe shall be used where the vertical drain ends to the exit at ground line.



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.

130	CLAY
-----	------

JOB NO.  
36201A

CONTRACT ID.	
--------------	--



PROJECT NO.  
BRO-B024(27)

BRIDGE NO.	10700091
------------	----------

[illegible]

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT


16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




## VERTICAL DRAIN



- (1) By the Design Engineer
- (2) By the Contractor
- (3) By Request
- (4) Based on dimensional requirements, assume 6 joints with  $\frac{1}{16}$ " crush (Take Up) per joint. Revise estimate if/when more accurate information becomes available. Ref: "Formwork for Concrete" Fifth Edition, by M.K. Hurd, Chapter 6
- (5) (col 7 - col 6)x12
- (6) Crush (Take Up) and camber must be included
- (7) (col 10 - col 9)x12
- (8) (col 10 - col 7)x12
- (9) (col 13 - col 12)
- (10) If transition falls on the bridge, then enter "Varies" for the % Slope
- (11) From "General Elevation and Plan" sheet
- (12) If bridge is not on the vertical curve, enter Abutment #1  $\frac{1}{2}$  bearing elevation from the "General Elevation and Plan" sheet. Represent a change in grade with G1 only.
- (13) Looking Up-Station
- (14) Out-to-Out
- (15) Ignore Fillet
- (16) Non-skewed bridges only require  $\frac{1}{2}$  stations.
- (17) Ignore theoretical camber at face of pier beams.





Note:  
See longitudinal section for  
transverse reinforcing steel.

The bottom longitudinal steel is shown along the short Edge of Deck. The top longitudinal steel is shown along the long Edge of Deck.

All longitudinal dimensions  
are along & Roadway = Profile  
Grade unless otherwise noted.

\* See "Geometric Layout" sheet for more information.

Note: 1.0 & 4.0 pts. are taken at  $\ell$  of abutments  
2.0 & 3.0 pts. are taken at  $\ell$  of piers  
1.0, 2.0, 3.0 & 4.0 are at theoretical bottom of slab (no account for depth of abutment or pier beam).

Top of Form Elevation at 10th Points, including camber and crush (ft.)															
1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0	2.1	2.2	2.3	2.4	2.5
785.04	785.06	785.06	785.05	785.02	784.93	784.79	784.59	784.33	784.03	783.67	784.09	784.40	784.63	784.76	784.79
2.6	2.7	2.8	2.9	3.0	3.1	3.2	3.3	3.4	3.5	3.6	3.7	3.8	3.9	4.0	
784.71	784.52	784.24	783.87	783.39	783.72	783.98	784.19	784.35	784.46	784.51	784.49	784.46	784.42	784.36	


Note: Elevations are taken at Crown Grade.

The change in elevation from Crown Grade to the Edge of Slab is -0.693' Lt. & 0.693' Rt.

### PLAN OF SLAB SHOWING REINFORCEMENT

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.



DEAD LOAD CAMBER DIAGRAM AT TENTH POINTS  
 Long Term Deflections = Initial Deflections x 3.5  
 (Initial Deflections Based on  $E_C = 3.644 \times 10^6$  p.s.i.)  
 (camber values in feet)  
 (Values shown are reduced for skew = 36%)

DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.

NO	COUNTY
	CLAY

JOB NO.  
36201A


CONTRACT ID.
--------------

PROJECT NO.  
BRO-B024(27

BRIDGE NO.	10700091
------------	----------

[illegible]

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT




**WSP**  
WSP USA Inc.  
1000 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943




**SUPERSTR.  
DETAILS I**








\*\*0 3/16" for Int. Bent No. 2  
 2 1/16" for Int. Bent No. 3  
 \*\*\*23 1/16" for Int. Bent No. 2  
 21 1/16" for Int. Bent No. 3  
 ΔΔ12 5/16" for Int. Bent No. 2  
 12 1/2" for Int. Bent No. 3



## SPACER FRAME INFORMATION




TYPICAL SECTION OF SLAB  
(Radial Section)

Note: This drawing is not to scale. Follow dimensions.

General Notes:  
For details and reinforcement Safety Barrier Curb, see Sh. No. 38 thru 40.

For Plan of Slab Showing Reinforcement, see Sh. No. 31 thru 32.

For Theoretical Slab Haunching Diagram and Theoretical Bottom of Slab Elevations, see Sh. No. 30.



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

STATE  
MO

DISTRICT  
KC

COUNTY  
CLAY

JOB NO.  
36201A

CONTRACT ID.

PROJECT NO.  
BR-BO24(27)

BRIDGE NO.  
10700091

DESCRIPTION

DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT




16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

SEAL OF CLAY COUNTY, MISSOURI




WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

SUPERSTR.  
DETAILS IV





With the approval of the engineer, the contractor may crown the bottom of the approach slab to match the crown of the roadway surface.



General Notes:

All concrete for the bridge approach slab and sleeper slab shall be in accordance with Sec 503 ( $f'_c = 4,000$  psi).

The reinforcing steel in the bridge approach slab and the sleeper slab shall be epoxy coated Grade 60 with  $f_y = 60,000$  psi.

Drain pipe may be either 6" diameter corrugated metallic-coated pipe underdrain, 4" diameter corrugated polyvinyl chloride (PVC) drain pipe, or 4" diameter corrugated polyethylene (PE) drain pipe.

Minimum clearance to reinforcing steel shall be  $1\frac{1}{2}"$ , unless otherwise shown.

The reinforcing steel in the bridge approach slab and the sleeper slab shall be continuous. The transverse reinforcing steel may be made continuous by lap splicing the #5 bars 29'.

All joint filler shall be in accordance with Sec 1057 for preformed fiber expansion joint filler except as noted.



The contractor shall pour and satisfactorily finish the bridge before pouring the bridge approach slab.

For Concrete Approach Pavement details, see roadway plans.

See Missouri Standard Plans Drawing 609.00 for details of Type A Curb.

Payment for furnishing all materials, labor and excavation necessary to construct the approach slab, including the timber header, sleeper slab, underdrain, Type 5 aggregate base, joint filler and all other appurtenances and incidental work as shown on this sheet, complete in place, will be considered completely covered by the contract unit price for Bridge Approach Slab (Major Road) per square yard.

\* Seal joint between vertical face of approach slab and wing with "Silicone Joint Sealant for Saw Cut and Formed Joints" in accordance with Sec 717.










Remove timber header when concrete pavement is placed.











## OPTIONAL SLIP-FORMED SAFETY BARRIER CURB

Use R bars and K bars similarly as shown for conventional-formed safety barrier curb.

General Notes:

Top of safety barrier curb shall be built parallel to grade with barrier curb joints (except at end bents) normal to grade.

All exposed edges of safety barrier curb shall have either a 1/2-inch radius or a 3/8-inch bevel, unless otherwise noted.

Payment for all concrete and reinforcement, complete in place, will be considered completely covered by the contract unit price for Safety Barrier Curb per linear foot.

Concrete in the safety barrier curb shall be Class B-1.


Measurement of safety barrier curb is to the nearest linear foot for each structure, measured along the outside top of slab from end of wing to end of wing.

Concrete traffic barrier delineators shall be placed on top of the safety barrier curb as shown on Missouri Standard Plans 617.10 and in accordance with Sec 617. Delineators on bridges with two-lane, two-way traffic shall have retroreflective sheeting on both sides. Concrete traffic barrier delineators will be considered completely covered by the contract unit price for Safety Barrier Curb.

Joint sealant and backer rods shall be in accordance with Sec 717 for silicone joint sealant for saw cut and formed joints.

Plastic waterstop shall not be used with saw cut joints.

For slip-formed option, all sides of the safety barrier curb shall have a vertically broomed finish and the curb top shall have a transversely broomed finish.



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE	STATE
148TH	MO

DISTRICT KC	SHEET NO.
----------------	-----------

COUNTY	
CLAY	

JOB NO.  
36201A

CONTRACT ID.	
--------------	--


PROJECT NO.  
BR0-B024(27)

BRIDGE NO.  
10700091

[illegible]

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




**WSP**  
WSP USA Inc.  
100 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
113.310.9943

## SAFETY BARRIER CURB DETAILS III

BILL OF REINFORCING STEEL																									
NO.	REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS							NOMINAL LENGTH	ACTUAL LENGTH	WEIGHT						
										B	C	D	E	F	H	K									
										FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.
			END BENT 1																						
4	8	A1	BOTT BEAM	E	20					60	5.000							60	5	645					
4	8	A2	TOP BEAM	E	20					60	5.000							60	5	645					
42	5	A3	APP SLAB	E	17					4	8.000							5	3	229					
10	5	A4	SIDE BEAM	E	20					60	5.000							60	5	630					
100	4	A5	STIRRUP	E	10	S						3	7.000	3	0.000			10	2	674					
42	4	A6	APP STEP	E	14					4	8.000	0	8.000	2	1.000		1	8.500	7	5	206				
14	4	A7	BEAM ENDS	E	10	S						2	0.000	2	2.000			6	2	57					
12	4	A13	STIRRUP	E	10	S						3	7.000	2	2.000			9	4	74					
4	4	A14	APP STEP	E	20					27	2.000							27	2	73					
			INT BENT 2																						
68	4	PB1	STIRRUP	E	10	S						2	7.000	3	5.000			8	7	386					
8	5	PB2	SIDE BEAM	E	20					45	6.000							45	6	380					
2	5	PB3	SIDE BEAM	E	20					44	2.000							44	2	92					
6	7	PB4	BOTT BEAM	E	20					44	2.000							44	2	542					
6	8	PB5	TOP BEAM	E	20					45	6.000							45	6	729					
4	4	PB6	STIRRUP	E	10	S						2	2.000	3	5.000			7	9	20					
10	4	PB7	BEAM ENDS	E	21					3	5.000	2	0.000	2	0.000		2	8.000	2	1.632	7	5	7	4	49
4	4	PB8	STIRRUP	E	10	S						2	7.000	3	3.000			8	5	8	4	22			
84	4	PW1	VERT WALL	20	X					34	6.000							34	6	34	6	1936			
64	4	PW2	HORIZ WALL	20	X					40	2.000							40	2	40	2	1717			
30	4	PW3	BOTT WALL	10	S	X						1	6.000	1	10.000			4	10	4	9	95			
2	6	PW4	HORIZ WALL	20	X					40	2.000							40	2	40	2	121			
65	4	PW5	WALL ENDS	7	X					2	4.500	1	6.500					5	8	5	7	241			
160	4	PW6	WALL TIES	18	X					1	9.000							2	9	2	8	283			
			INT BENT 3																						
8	5	PB9	SIDE BEAM	E	20					40	2.000							40	2	40	2	335			
2	5	PB10	SIDE BEAM	E	20					39	0.000							39	0	39	0	81			
6	7	PB11	BOTT BEAM	E	20					39	0.000							39	0	39	0	478			
6	8	PB12	TOP BEAM	E	20					40	2000							40	2	40	2	643			
68	4	PB13	STIRRUP	E	10	S						2	7.000	3	0.000			8	2	8	1	367			
4	4	PB14	STIRRUP	E	10	S						2	2.000	3	0.000			7	4	7	3	19			
10	4	PB15	BEAM ENDS	E	21					3	0.000	2	0.000	2	0.000		2	8.000	1	4.492	7	0	6	11	46
4	4	PB16	STIRRUP	E	10	S						2	7.000	2	9.000			7	11	7	10	21			
30	4	PW3	BOTT WALL	10	S	X						1	6.000	1	10.000			4	10	4	9	95			
65	4	PW5	WALL ENDS	7	X					2	4.500	1	6.500					5	8	5	7	241			
160	4	PW6	WALL TIES	18	X					1	9.000							2	9	2	8	283			
84	4	PW7	VERT WALL	20	X					34	6.000							34	6	34	6	1936			
64	4	PW8	HORIZ WALL	20	X					35	8.000							35	8	35	8	1525			
2	6	PW9	HORIZ WALL	20	X					35	8.000							35	8	35	8	107			
			END BENT 4																						
36	5	A3	APP SLAB	E	17					4	8.000							5	3	5	3	196			
14	4	A7	BEAM ENDS	E	10	S						2	0.000	2	2.000			6	2	6	1	57			
4	8	A8	BOTT BEAM	E	20					45	10.000							45	10	45	10	490			
4	8	A9	TOP BEAM	E	20					45	10.000							45	10	45	10	490			
10	5	A10	SIDE BEAM	E	20					45	10.000							45	10	45	10	478			
88	4	A11	STIRRUP	E	10	S						3	7.000	2	4.000			9	6	9	5	554			
36	4	A12	APP STEP	E	14					3	8.000	0	8.000	2	1.000		1	7.000	1	4.250	6	5	6	4	152
4	4	A13	STIRRUP	E	10	S						3	7.000	2	2.000			9	4	9	3	25			
2	4	A15	APP STEP	E	20					37	5.000							37	5	37	5	50			


BILL OF REINFORCING STEEL																										
NO.	REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS								NOMINAL LENGTH	ACTUAL LENGTH	WEIGHT						
										B	C	D	E	F	H	K	FT.				IN.	FT.	IN.	FT.	IN.	FT.
										FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.	FT.
			SLAB																							
30	8	S1*	SLAB	E	19					2	6.000	13	10.000					16	4	1302						
28	7	S2	SLAB	E	19					2	6.000	12	9.000					15	3	869						
26	7	S3	SLAB	E	19					2	6.000	11	2.000					13	8	722						
4	10	S4	SLAB	E	20					57	8.000							57	8	993						
2	4	S5	SLAB	E	20					15	8.000							15	8	21						
60	10	S6	SLAB	E	20					57	4.000							57	4	14802						
56	11	S7	SLAB	E	20					55	11.000							55	11	16637						
52	10	S8	SLAB	E	20					60	0.000							60	0	13425						
24	10	S9	SLAB	E	20					53	5.000							53	5	5516						
20	10	S10	SLAB	E	20					42	4.000							42	4	3643						
20	9	S11	SLAB	E	20					39	8.000							39	8	2697						
40	9	S12*	SLAB	E	20					33	3.000							33	3	4522						
40	4	S13	SLAB	E	20					12	8.000							12	8	338						
44	9	S14*	SLAB	E	20					7	3.000							7	3	1085						
24	10	S15	SLAB	E	20					59	10.000							59	10	6179						
20	9	S16	SLAB	E	20					43	9.000							43	9	2975						
20	9	S17	SLAB	E	20					38	0.000							38	0	2584						
20	10	S18*	SLAB	E	20					26	4.000							26	4	2266						
40	4	S19	SLAB	E	20					13	11.000							13	11	372						
4	4	S20	SLAB	E	20					10	1.000							10	1	27						
30	8	S21*	SLAB	E	19					2	6.000	12	10.000					15	4	1222						
28	7	S22	SLAB	E	19					2	6.000	11	9.000					14	3	811						
26	7	S23	SLAB	E	19					2	6.000	10	2.000					12	8	669						
24	10	S24	SLAB	E	20					50	9.000							50	9	5241						
20	10	S25	SLAB	E	20					40	3.000							40	3	3464						
20	9	S26	SLAB	E	20					37	7.000							37	7	2556						
66	6	T1	SLAB	E	20					27	5.000							27	5	2718						
90	5	T2	SLAB	E	20					23	11.000							23	11	2245						
228	4	T3	SLAB	E	20					26	11.000							26	11	4100						
		T4-T52	SPACER FRAME	E				V												6623						
66	6	T53	SLAB	E	20					21	10.000							21	10	2164						
			BARRIER																							
344	5	R1	BARRIER CURB	E	26					2	6.000	0	4.250	2	6.125		2	6.000	0	1861						
344	5	R3	BARRIER CURB	E	19	S				1	5.000	0	6.000					1	11	669						
344	5	R4	BARRIER CURB	E	27	S						0	6.000	0	11.250	0	7.000	1	0.000	1028						
56	5	R5	BARRIER CURB	E	20					9	7.000							9	7	560						
7	5	R6	BARRIER CURB	E	20					43	3.000							43	3	316						
7	5	R7	BARRIER CURB	E	20					44	11.000							44	11	328						
7	5	R8	BARRIER CURB	E	20					39	4.000							39	4	287						
7	5	R9	BARRIER CURB	E	20					37	9.000							37	9	276						
7	5	R10	BARRIER CURB	E	20					42	5.000							42	5	310						
7	5	R11	BARRIER CURB	E	20					39	1.000							39	1	285						
			SLIP FORM																							
40	5	C1	SLIP FORM	E	20					10	0.000							10	0	417						

BILL OF REINFORCING STEEL																	
NO.	REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS							
										B	C	D	E	F	H	K	NOMINAL LENGTH
										FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.
			TOTALS														
4																	8352
4					E												8642
5					E												11003
6																	228
6					E												10573
7					E												4092
8					E												6165
9					E												16419
10					E												55530
11					E												16637
			TOTAL														8580
			TOTAL		E												129060
			END BENTS														
4					E												1920
5					E												1533
8					E												2270
			TOTAL														5723
			INT BENTS														
4					E												932
5					E												888
7					E												1020
8					E												1372
			TOTAL														4212
			SLAB														
4					E												5790
5					E												2245
6					E												10573
7					E												3072
8					E												2523
9					E												16419
10					E												55530
11					E												16637
			TOTAL														112789
			Reinforcing Steel (Bridges)														
4																	8352
6																	228
			TOTAL														8580
			Safety Barrier Curb														
5					E												5919
			TOTAL														5919



STIRRUP HOOK DIMENSIONS				
GRADES 40 - 50 - 60 KSI				
BAR SIZE	D (IN.)	90° HOOK A OR G	135° HOOK A OR G	APPROX. H
#4	2"	4 1/2"	4 1/2"	3"
#5	2 1/2"	6"	5 1/2"	3 3/4"
#6	4 1/2"	12"	8"	4 1/2"

NOTE: UNLESS OTHERWISE NOTED, DIAMETER "D" IS THE SAME FOR ALL BENDS AND HOOKS ON A BAR.




END HOOK DIMENSIONS				
ALL GRADES				
BAR SIZE	D (IN.)	180° HOOKS A OR G	90° HOOKS J	A OR G
#3	2 1/4"	5"	3"	6"
#4	3"	6"	4"	8"
#5	3 3/4"	7"	5"	10"
#6	4 1/2"	8"	6"	12"
#8	6"	11"	8"	16"
#9	9 1/2"	15"	11 3/4"	19"
#10	10 3/4"	17"	13 1/4"	22"
#11	12"	19"	14 3/4"	2'-0"
#14	18 1/4"	2'-3"	21 3/4"	2'-7"

NOTE: ALL STANDARD HOOKS AND BENDS OTHER THAN 180 DEGREE ARE TO BE BENT WITH SAME PROCEDURE AS FOR 90 DEGREE STANDARD HOOKS. HOOKS AND BENDS SHALL BE IN ACCORDANCE WITH THE PROCEDURES AS SHOWN ON THIS SHEET. E = EPOXY COATED REINFORCEMENT. S = STIRRUP. X = BAR IS INCLUDED IN SUBSTRUCTURE QUANTITIES. V = BAR DIMENSIONS VARY IN EQUAL INCREMENTS BETWEEN DIMENSIONS SHOWN ON THIS LINE AND THE FOLLOWING LINE. NO. EA. = NUMBER OF BARS OF EACH LENGTH. NOMINAL LENGTHS ARE BASED ON OUT TO OUT DIMENSIONS SHOWN IN BENDING DIAGRAMS AND ARE LISTED FOR FABRICATORS USE. (NEAREST INCH) ACTUAL LENGTHS ARE MEASURED ALONG CENTERLINE BAR TO THE NEAREST INCH. PAYWEIGHTS ARE BASED ON ACTUAL LENGTHS. FOUR ANGLE OR CHANNEL SPACERS ARE REQUIRED FOR EACH COLUMN SPIRAL. SPACERS ARE TO BE PLACED ON INSIDE OF SPIRALS. LENGTH AND WEIGHT OF COLUMN SPIRALS DO NOT INCLUDE REINFORCING STEEL (GRADE 60) FY = 60,000 PSI.

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.

BILL OF REINFORCING STEEL																	
NO.	REQ'D.	MARK NO.	LOCATION	EPOXY (E)	SHAPE NO.	STIRRUP (S)	SUBSTR. (X)	VARIES (V)	NO. EACH	DIMENSIONS							
										B	C	D	E	F	H	K	NOMINAL LENGTH
										FT.	IN.	FT.	IN.	FT.	IN.	FT.	IN.
			Slip Form Option														
5			TOTAL		E												417
																	417



STATE OF MISSOURI  
WITNESS MY HAND  
12-18-19  
NUMBER  
PE-2018037127  
PROFESSIONAL ENGINEER

DATE  
09/23/2019  
DATE PREPARED  
09/23/2019  
ROUTE  
148TH  
DISTRICT  
KC  
STATE  
MO  
SHEET NO.  
COUNTY  
CLAY  
JOB NO.  
36201A  
CONTRACT ID.  
PROJECT NO.  
BR0-B024(27)  
BRIDGE NO.  
10700091

DESCRIPTION

DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

SEAL OF CLAY COUNTY, MISSOURI

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

BAR LIST & BENDING DIAGRAMS II

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.

BOREHOLE INFORMATION

Page 1 of 3

STATION 104+00

OFFSET C.L.

NORTHING

EASTING

DRILLING COMPANY GeoSource, LLC

METHOD 4-inch Flight Augers

HAMMER Auto

LOG OF BORING NO. B-1

PROJECT NAME NE 148th Street over Carroll Creek

SITE LOCATION SE ¼, NW ¼ of Section 31, T53N, R30W  
Kearney, Clay County, Missouri

OWNER / ENGINEER MDOT / WSP USA

SAMPLE NO.

SAMPLE TYPE

RECOVERY

STANDARD PENETRATION BLOWS/FT.

UNCONFINED STRENGTH PSF

DRY DENSITY PCF

MOISTURE CONTENT, %

UNIFIED SOIL SYMBOL

GRAPHIC LOG

DEPTH, Feet.

Boring offset to existing road, due to overhead power line

MATERIAL DESCRIPTION

Approx. Surface Elevation: 93.0

0.8 Asphaltic Concrete 92.3

FILL, clayey silt, medium stiff, brown and gray brown mixed, trace sand

5

6.0 87.0

SILTY LEAN CLAY, stiff, dark gray brown to gray brown, trace fine sand

10

15

18.0 75.0

LEAN CLAY, very soft, brown, trace fine sand

20

\*\* compressive strength in psi

\* Calibrated Penetrometer

The stratification lines represent the approximate boundary lines between soil and rock types. In-situ the transition may be more gradational in nature.

WATER LEVEL OBSERVATIONS

▽ 20.0 feet W.D.

▽ 22.0 feet A.B.

Backfilled @ Completion

GeoSource

Your Source for Geotechnical and Materials Engineering

BORING STARTED 12-4-18

BORING COMPLETED 12-4-18

RIG CME-55

DRILLER LS

APPROVED JJZ

JOB # LM17G2012

BOREHOLE INFORMATION

Page 2 of 3

STATION 104+00

OFFSET C.L.

NORTHING

EASTING

DRILLING COMPANY GeoSource, LLC

METHOD 4-inch Flight Augers

HAMMER Auto

LOG OF BORING NO. B-1

PROJECT NAME NE 148th Street over Carroll Creek

SITE LOCATION SE ¼, NW ¼ of Section 31, T53N, R30W  
Kearney, Clay County, Missouri

OWNER / ENGINEER MDOT / WSP USA

SAMPLE NO.

SAMPLE TYPE

RECOVERY

STANDARD PENETRATION BLOWS/FT.

UNCONFINED STRENGTH PSF

DRY DENSITY PCF

MOISTURE CONTENT, %

UNIFIED SOIL SYMBOL

GRAPHIC LOG

DEPTH, Feet.

LEAN CLAY, very soft, brown, trace fine sand

23.0 70.0

SILTY LEAN CLAY, very soft, saturated, light gray brown, trace fine sand

25

28.0 65.0

CLAYEY SILT, very soft, gray, trace fine sand

30

33.0 60.0

SANDY SILT, very loose, fine grained, saturated, gray, with interbedded sand seams

35

38.5 54.5

SAND, very loose, fine to medium grained, poorly graded, gray, with some silt

40

\*\* compressive strength in psi

\* Calibrated Penetrometer

The stratification lines represent the approximate boundary lines between soil and rock types. In-situ the transition may be more gradational in nature.

WATER LEVEL OBSERVATIONS

▽ 20.0 feet W.D.

▽ 22.0 feet A.B.

Backfilled @ Completion

GeoSource

Your Source for Geotechnical and Materials Engineering

BORING STARTED 12-4-18

BORING COMPLETED 12-4-18

RIG CME-55

DRILLER LS

APPROVED JJZ

JOB # LM17G2012

Detailed Nov. 2018  
Checked Feb. 2019

Note: This drawing is not to scale. Follow dimensions.

BORING DATA  
Note: For locations of borings, see "General Elevation and Plan"

SHEET 45 of 62

DATE 09/23/2019

DATE PREPARED 09/23/2019

ROUTE 148TH

DISTRICT KC

STATE MO

SHEET NO.

COUNTY CLAY

JOB NO. 36201A

CONTRACT ID.

PROJECT NO. BR0-B024(27)

BRIDGE NO. 10700091

DESCRIPTION	DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300

**WSP**  
WSP USA, Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

BORING LOG  
DETAILS I


IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.












WEST ABUTMENT ALIGNMENT		
STATION	NORTHING	EASTING
20+00.00	1163193.02	2841073.96
20+70.00	1163131.26	2841106.91
20+90.00	1163121.30	2841089.57
21+20.00	1163094.81	2841103.65



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.

COUNTY  
CLAY

JOB NO.  
36201A



CONTRACT ID.

PROJECT NO.  
BRO-B024(27  
201065 NO

[illegible]


DATE	DESCRIPTION

CLAY COUNTY, MISSOURI HIGHWAY DEPARTMENT	16616 NE 116TH STREET KEARNEY, MO 64060 PHONE (816) 421-4023 FAX (816) 421-3200
---	---




**ABUTMENT  
SECTION  
KEY MAP**

[illegible]




WEST ABUTMENT STA. 20+00.0000 TO STA. 20+50.0000



DATE	
DATE PREPARED	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	

DESCRIPTION	DATE



CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300



**WSP**  
WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**WEST ABUTMENT  
CROSS SECTION  
SHEET**

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.




DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	

DESCRIPTION	DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300









**WSP**


WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

WEST ABUTMENT  
CROSS SECTION  
SHEET

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.




EAST ABUTMENT STA. 20+00.0000 TO STA. 20+50.0000



DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	




DATE	DESCRIPTION

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




**wsp**  
WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**EAST ABUTMENT  
CROSS SECTION  
SHEET**



EAST ABUTMENT STA. 20+60.0000 TO STA. 21+20.0000




DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	

DATE	DESCRIPTION

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300





**WSP**

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

EAST ABUTMENT  
CROSS SECTION  
SHEET


IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



WEST SIDE STA. 100+80.0000 R1 TO STA. 101+00.0000 R1

TOTAL CUT: 771.19 CY / 1.4 VMF = 550.85 CY  
TOTAL FILL: 995.64 CY X 1.4 VMF = 1393.90 CY  
BALANCE: -843.05 CY

WEST SIDE EARTHWORK



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE  
148TH

STATE  
MO

DISTRICT  
KC

SHEET NO.

COUNTY  
CLAY

JOB NO.  
36201A

CONTRACT ID.


PROJECT NO.  
BR0-B024(27)

BRIDGE NO.  
10700091

DATE	DESCRIPTION

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT



16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




**WSP**

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**CROSS SECTIONS**



STA. 102+00.0000 R1 TO STA. 102+50.0000 R1




DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	

DESCRIPTION	DATE

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT




16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




**wsp**

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**CROSS SECTIONS**



WEST SIDE STA. 101+75.0000 R1 TO STA. 102+25.0000 R1



DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	
PROJECT NO. BR0-B024(27)	
BRIDGE NO. 10700091	

DATE	DESCRIPTION



CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT  
16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300



**WSP**  
WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**CROSS SECTIONS**





WEST SIDE STA. 102+50.0000 R1 TO STA. 102+75.0000 R1



DATE	09/23/2019
------	------------

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.

NO	COUNTY CLAY
----	----------------

JOB NO.  
36201A

CONTRACT ID.
--------------


PROJECT NO.	BRO-B024(27)
-------------	--------------

BRIDGE NO.	10700091
------------	----------

[illegible]



CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




## CROSS SECTIONS

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



WEST SIDE STA. 103+00.0000 R1 TO STA. 103+12.5782 R1



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.


RC	COUNTY
	CLAY
	JOB NO.
	36201A
	CONTRACT ID.

PROJECT NO.	BRO-B024(27
BRIDGE NO.	10700091

[illegible]

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT



16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




WSP USA Inc.  
3300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913 310 0042

## CROSS SECTIONS

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED:



		EAST SIDE EARTHWORK	
TOTAL CUT:	248.36 CY /	1.4 VMF =	177.40 CY
TOTAL FILL:	786.95 CY X	1.4 VMF =	1101.73 CY
		BALANCE:	-924.33 CY



DATE	09/23/2019
------	------------

DATE PREPARED  
09/23/2019

ROUTE	STATE
148TH	MO

DISTRICT KC	SHEET NO.
----------------	-----------

COUNTY
CLAY

JOB NO.  
36201A



CONTRACT ID.	PROJECT

PROJECT NO.	FH33
BRO-B024(27)	



BRIDGE NO.					
10700091					

[illegible]


CLAY COUNTY, MISSOURI HIGHWAY DEPARTMENT	16616 NE 116TH STREET KEARNEY, MO 64060 PHONE: (816) 407-3300
---	---



## CROSS SECTIONS



EAST SIDE STA. 105+25.0000 R1 TO STA. 105+75.0000 R1



DATE	09/23/2019
------	------------

DATE PREPARED  
09/23/2019

ROUTE	STATE
148TH	MO

DISTRICT KC	SHEET NO.
----------------	-----------

COUNTY CLAY	SE BE SV
----------------	----------

JOB NO.  
36201A


CONTRACT ID.	133H
8801503 HQ	

PROJECT NO.	13 31
BRO-B024(27)	
221005 NO	

BRIDGE NO.					
10700091					

[illegible][illegible]

CLAY COUNTY, MISSOURI HIGHWAY DEPARTMENT	16616 NE 116TH STREET KEARNEY, MO 64060 PHONE: (816) 407-3300
---	---





**WSP**

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

## CROSS SECTIONS

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



EAST SIDE STA. 106+00.0000 R1 TO STA. 106+25.0000 R1




DATE 09/23/2019	
DATE PREPARED 09/23/2019	
ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.
COUNTY CLAY	
JOB NO. 36201A	
CONTRACT ID.	

PROJECT NO. BR0-B024(27)
BRIDGE NO. 10700091

DATE	DESCRIPTION

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT

16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300






**wsp**


WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**CROSS SECTIONS**

IF A SEAL IS PRESENT ON THIS SHEET IT HAS BEEN ELECTRONICALLY SEALED AND DATED.



EAST SIDE STA. 106+50.0000 R1 TO STA. 107+00.0000 R1




DATE	
09/23/2019	
DATE PREPARED	
09/23/2019	
ROUTE	STATE
148TH	MO
DISTRICT	SHEET NO.
KC	
COUNTY	
CLAY	
JOB NO.	
36201A	
CONTRACT ID.	
PROJECT NO.	
BR0-B024(27)	
BRIDGE NO.	
10700091	

DATE	DESCRIPTION

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT




16616 NE 116TH STREET  
KEARNEY, MO 64060  
PHONE: (816) 407-3300




**WSP**

WSP USA Inc.  
300 Wyandotte Street  
Suite 200  
Kansas City, MO 64105  
913.310.9943

**CROSS SECTIONS**



EAST SIDE STA. 107+25.0000 R1 TO STA. 107+60.0000 R1



DATE  
09/23/2019

DATE PREPARED  
09/23/2019

ROUTE 148TH	STATE MO
DISTRICT KC	SHEET NO.

RC	
COUNTY	
CLAY	

JOB NO.  
36201A


CONTRACT ID.
--------------

PROJECT NO.
BRO-B024(27)

BRIDGE NO.
10700091

[illegible]

CLAY COUNTY, MISSOURI  
HIGHWAY DEPARTMENT



## CROSS SECTIONS

# **Invitation for Bid No. 19-20**

## **CLAY COUNTY BRIDGE REPLACEMENT BRO-B024(27)**

Bids for the Proposal for the construction of Clay County Bridge No. 10700091 are due on the 26<sup>th</sup> day of March, 2020 at 2:00 P.M. (prevailing Local Time). Bids can be submitted by either: 1) delivery of sealed hard-copy bid to Clay County Highway Department, 16616 NE 116<sup>th</sup> Street, Kearney, MO 64060; OR 2) electronic upload of the bid in pdf form through Public Purchase website ([www.publicpurchase.com](http://www.publicpurchase.com)).

After the time noted above, the bids will be opened and read.

The proposed work includes: Demolition of the existing NE 148<sup>th</sup> Street Bridge spanning Carroll Creek and the construction of a new three-span solid superstructure slab bridge, approach roadway work, and incidental work in accordance with the plans and specifications.

A digital copy of the plans and specifications, as well as bid package, may be downloaded through the Clay County Purchasing web site's link to Public Purchase ([publicpurchase.com](http://publicpurchase.com)). Specific questions on the documents can be directed to the Engineer of Record, Lawrence Oquendo PE at WSP USA Inc., 816-702-4241.

All labor used in the construction of this public improvement shall be paid a wage no less than the prevailing hourly rate of wages of work of a similar character in this locality as established by the United States Department of Labor (Federal Wage Rate), or by the Missouri Department of Labor and Industrial Relations (State Wage Rate), whichever is higher.

The Clay County Commission hereby notifies all bidders that it will affirmatively ensure that in any contract entered into pursuant to this advertisement, businesses owned and controlled by socially and economically disadvantaged individuals will be afforded full opportunity to submit bids in response to this invitation and will not be discriminated against on the grounds of race, color, religion, creed, sex, age, ancestry, or national origin in consideration for an award.

All bidders must be on MoDOT's Qualified Contractor List per Section 102.2 of the Missouri Standard Specifications for Highway Construction, 2019 Edition including all revisions. The contractor questionnaire must be on file seven (7) days prior to bid opening.

Contractors and sub-contractors who sign a contract to work on public works projects shall provide a 10-Hour OSHA construction safety program, or similar program approved by the Department of Labor and Industrial Relations, to be completed by their on-site employees within sixty (60) days of beginning work on the construction project.

The DBE Goal for this project is 8%.

No second tier subcontracting will be allowed on this project.

A certified cashier's check or a bid bond in the amount of 5% shall be submitted with each proposal.

The Clay County Purchasing reserves the right to reject any or all bids.

The project will be awarded to the lowest, responsive, responsible bidder.

**Clay County Purchasing**