

**SE0037**

Madison County  
Existing Bridge: T0093  
Route M over Big Creek

**Legend**

- CL Channel
- T0093
- Valley Section

T0093

Zone A

East Fork Big Creek

The section and/or profile lines shown are intended to show location only.

Terminal points of these lines should be based on the information provided by the Bridge Survey Location Request and not on the ends of the lines shown here.





12/19

Job No. SE0037

Replaces Bridge No. T0093

**Missouri Department of Transportation**  
**Bridge Survey Location Request**

Page 1 to be completed by District staff.

Bridge over: Big Creek Route: M  
 County: Madison Section: 16 Township: 31 North Range: 7 East  
 Latitude: 37°21'40.45"N Longitude: 90°16'31"W  
 District Contact: Garrett Galyean (573-472-5221) Date: 5/4/2023

### HIGH WATER ELEVATIONS AT PROPOSED BRIDGE SITE

Recorded high water elevations or elevation of high water marks

Extreme High Water (EHW) (Give date(s) of occurrence)		
Elevations and date(s) of same	Location	Source of information
6.4" Below (2008)	Below North End of Bridge Deck	HW Marks 2008

Existing Bridge Overtopped <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Unknown	Existing Roadway Overtopped <input type="checkbox"/> Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> Unknown
	Approx. Overtopping Location(s):

### LOCATION OF NEW BRIDGE

Replace in Existing Location	<input checked="" type="checkbox"/>	Provide details of any proposed changes to profile grade below or as an attachment.
Relocation (near existing Structure)	<input type="checkbox"/>	Provide details of proposed location and grade of the roadway across the floodplain, any proposed/potential channel changes or modifications, etc. below or as an attachment.
New Route	<input type="checkbox"/>	
Other:	<input type="checkbox"/>	

Additional Information:

Note: Proposed elevations, distances, etc. are based on the best available data at the time the form was completed. Actual field conditions or recently acquired data may require deviation from the proposed values. Please contact the Bridge Division with concerns regarding the proposed values or if large deviations from these values are required.

Note: The information below supplements the survey requirements noted in the EPG, please consult EPG 238 for additional surveying requirements.

Bridge Contact: Xinguo Cai, (573) 522-1947, xinguo.cai@modot.mo.gov

Survey Type: **1D Survey**

Stream Crossing Survey Location Details (1D)						
Item		Requirement	Standard Guidance		Specific Guidance	
Profiles* (EPG 238.3.36.1.3)	C/L Profile	Terminal Point	Limit of Longest offset Profile		Use Standard Guidance	
	Upstream Offset Profile	Terminal Point	Same as Valley Sections		Elevation =	630
		Offset Distance	On Natural Ground		Estimated Distance =	30
	Downstream Offset Profile	Terminal Point	Same as Valley Sections		Elevation =	630
		Offset Distance	On Natural Ground		Estimated Distance =	30
	Special	N/A				
Streambed Profiles** (EPG 238.3.36.3.6)		Length	Natural Stream	Section limits (Min. of 1000' each side of crossing.)	Use Natural Stream Guidance	
			Drainage Ditch	500' Each Side of Crossing		
		Elevation Intervals	Within 1000' of Crossing	Nat. Stream 25'	Use Natural Stream Guidance (see EPG 238.3.36.3.6 if a significant slope change is encountered)	
				Drain. Ditch 50'		
			Beyond 1000' from Crossing	At Vertical and Horizontal Break Points (200' max.)		
		Valley Sections (EPG 238.3.36.3.8), (EPG 750.3.1.1)		Terminal Point	Natural Stream	5' above EHW
Drainage Ditch	25' Beyond Bankside Toe of Levee				Distance =	N/A

Item	Requirement	Standard Guidance		Specific Guidance
Water Surface Profile (EPG 238.3.36.3.7)	Water Surface Profile Data Needed? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No			
	Locations with flowing water	Drainage Ditch	100' and 200' each side of Crossing	Use Water Surface Profile Standard Guidance

Item	Requirement	Standard Guidance	Specific Guidance
Typical Channel Sections (EPG 238.3.36.3.9)	Typical Channel Section Data Needed? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
	Within 300' each side of Centerline	Provide when Needed (i.e., Culvert on Perennial and	

		Intermittent Stream)	
--	--	----------------------	--

Item	Requirement	Standard Guidance	Specific Guidance
Existing Bridge Data	Existing Bridge Data Needed? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
	Description	Provide General Description	N/A

Item	Requirement	Standard Guidance	Specific Guidance
Other Bridges (EPG 238.3.36.3.10)	Other Bridge Data Needed? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
	Description	Provide General Description	N/A
	Profile Location	C/L Structure	N/A
	Profile Terminal Point	5' above EHW	Elevation = N/A

\* additional profiles may be needed for relocated routes

\*\* at confluent streams provide proposed data for both streams as appropriate.

#### Additional Information:

#### Additional Documents Provided:

Image & kmz file showing Valley Section Locations.

#### Roadway Design Notes for Bridge Survey:

The Bridge Survey should include all the pertinent items listed in [EPG 747](#) and the [Bridge Survey Checklist](#).

#### Bridge Design Notes:

TMS has indicated road closure multiple times in last 20 years due to roadway overtopping.  
FEMA Zone A.


LM

# BILL OF REINFORCING STEEL FOR SUPERSTRUCTURE

No.	Size	Length	Location
16	2"φ	26'-0"	C1
158	2"φ	24'-0"	C2
16	2"φ	25'-6"	C3
244	2"φ	24'-0"	S1
52	2"φ	26'-0"	S2
90	2"φ	22'-3"	S3
12	2"φ	22'-3"	S4
52	2"φ	25'-3"	S5

GENERAL NOTES:

*Bridge excavation will be allowed for all bents within horizontal limits shown and noted on these design plans, sheet #2. This excavation will be computed from existing ground line to bottom end of 6"x6" backing supports for end bents and to bottom of sway bracing for interior bents.*



BRIDGE OVER EAST FORK OF BIG CREEK

MADISON COUNTY


Drawn Aug. 1933 By R.J.G.  
Traced Aug. 1933 By R.J.G.  
Checked Aug. 1935 By N.M.R.

Sheet No. 1 of 3.


# MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
5	MO.	Ref # 6(SB)-S2	19		


Note: Space dowel bars "C2" at approximately 12" cts. in curbs between outlets and at ends.



PLAN OF SLAB SHOWING REINFORCING




DETAIL OF BEVEL FOR RUBBER COMPOUND JOINTS



METALLIC EDGE Moulding


Span	STANDARD I-BEAMS		BETHLEHEM BEAMS	
	Inside	Outside	Inside	Outside
36'-0"	13'-0" x 37"	13'-0" x 47"	13'-0" x 47"	13'-0" x 47"
49'-0"	24'-0" x 115"	24'-0" x 105"	24'-0" x 91"	24'-0" x 91"

Note: Top of curbs under end posts shall be finished to a smooth surface parallel to grade. Not less than one nor more than four soft lead plates of 1/8" thickness shall be used under angles of each end rail post for aligning rail to correct elevation. Plates shall be 8 1/2" x 6" and shall be punched 1/4" on same gauge as the angles. No grouting permitted. Cost of lead plates to be included in price bid for other items.




Note: Floor slab to be brought to grade and dead load deflection taken care of by increasing slab thickness. Depth of slab at outside face of curb to be kept uniform and bottom surface of slab warped between curb and outside beam to obtain required thickness at beam. Payment will be allowed for additional concrete required for thickening slab. This additional concrete is included in "Estimated Quantities".


DEFLECTION DIAGRAM




PLAN OF STRUCTURAL STEEL



HALF SECTION THRU SPAN




RAIL EXPANSION JOINT




SECTION A-A

DETAIL OF PILING SHOE

DETAIL OF RAIL BRACKETS AT ENDS OF SPAN



LOCATION OF POSTS AT END BENTS



TYPICAL PART ELEVATION SHOWING CURB DETAILS  
BRIDGE OVER EAST FORK OF BIG CREEK

STATE ROAD FROM MARQUAND TO BUCKHORN  
ABOUT 8.5 MILES S.W. OF MARQUAND  
PROJECT NO. REF # 6(SB)-S2 STA. 422 + 65

MADISON COUNTY

Drawn Aug. 1933 By R.J.G.  
Traced Aug. 1933 By R.J.G. Assembled Feb. 1934 By H.A.A.-J.H.M.  
Checked Aug. 1933 By N.M.R. Checked Feb. 1934 By L.H.S.


Note: This drawing is not to scale. Follow dimensions.

Sheet No. 2 of 3.




# MISSOURI STATE HIGHWAY DEPARTMENT

FED. ROAD DIST. NO.	STATE	FED. AID PROJ. NO.	FISCAL YEAR	SHEET NO.	TOTAL SHEETS
1	MO.	22-630	19		



ELEVATION OF END BENT




PLAN OF END BENT

Note: Any irregularity in alignment of piling in end bents to be corrected by facing one surface of the 6"x6" backing support so as to place the surface of the backing in a true plane and eliminate any strain on the backing plank. Splice in backing plank to be made at center of 6"x6" backing support and to be alternated on the intermediate supports.

## NAILING SCHEDULE:


Backing plank to supports; 3-60d at each support and at splices, 3-60d each side of splice. Pieces at ends of backwall to backing plank; 4-60d to each backing plank.




EXPANSION

FIXED

TYPICAL JOINTS OVER INT. BENTS




DETAILS OF BEARING ON PILE CAP




SECTION A-A



END BENT CAP PLATE




PLAN OF BEARING PLATES



Note: Cast iron clamps used on bearing plates to have 1/2" clearance at flange of beam to allow for expansion. All clamps to have 3/4" cored holes. Use two clamps only on each I-Beam at pile caps on end bents.

DETAILS OF FLANGE CLAMPS



DETAIL OF INTERIOR BENT

Note: Omit sway bracing when distance from bottom of pile cap to ground is less than 5'-0". Carry sway bracing down to approximately Elev. 614.30. Excavation will be allowed for interior bents within the maximum horizontal limits of 4'-9" in width and 21'-7 1/2" in length.

PIECE	NO.	SIZE	LENGTH	REMARKS	SHAPING & BORING SKETCHES
Backing Plank	2	3"x12"	18'-8"	Cut to length.	
"	2	3"x12"	25'-11 1/2"	"	
"	2	3"x12"	23'-5 1/2"	"	
"	2	3"x12"	17'-11 1/2"	"	
"	2	3"x12"	15'-5 1/2"	"	
"	2	3"x12"	22'-9 1/2"	"	
"	2	3"x12"	20'-8 1/2"	"	
"	2	3"x12"	14'-9 1/2"	"	
"	2	3"x12"	12'-9 1/2"	"	
"	2	3"x12"	19'-7"	"	
Edge Support	4	3"x12"	10'-11"	Cut to length & shape.	
Shoulder Plank	2	3"x8"	2'-7 1/2"	"	
"	2	3"x8"	2'-6 1/2"	"	
Backing Support	8	6"x6"	6'-0"	"	
"	4	6"x6"	4'-0"	"	
Back. Support Cap	2	6"x6"	23'-10 1/2"	Cut to length.	
Pile Cap	4	12"x12"	21'-7 1/2"	"	
Sway Bracing	4	3"x8"	4'-0"	"	

\* S2S to exactly 11 1/2" depth.  
Note: Pile caps to be classified as "Beams and Stringers".  
All other timber to be classified as "Joists and Plank".

## BRIDGE OVER EAST FORK OF BIG CREEK

STATE ROAD FROM MARQUAND TO BUCKHORN

ABOUT 8.5 MILES S.W. OF MARQUAND

PROJECT NO. REF. 6(SB)-52 STA. 422 + 65

MADISON COUNTY

Drawn Aug. 1933 By R.J.G. Assembled Feb. 1934 By H.B.A. - J.M.T.  
Traced Aug. 1933 By R.J.G. Checked Feb. 1934 By L.K.S.  
Checked Aug. 1933 By N.M.R.

Note: This drawing is not to scale. Follow dimensions.

Sheet No. 3 of 3.

T-93

ELI TRIPP ET UX

SE 1/4, J.W. 1/4  
Sec. 15

J.W. 1/4, J.W. 1/4  
Sec. 15  
T. 31 N. - R. 7 E.

10 MASON 1-2

Field

Field

Field

Excavate Top of Bluff  
Sta. 420+15 to 422+30, 1.15 mi.  
(See X-Sections)

SE 1/4, J.W. 1/4  
Sec. 16

Field

GENERAL NOTES - (Sec. 3)

All buildings within limits of R/W to be removed by property owners previous to construction.  
Contractor shall take care of all live traffic over project during construction.

Clearing & Grubbing Unit are 50 ft. Sec. 3, from

S. R. & E. APPROACHES				
STATION	Side	15' 24'	Exc.	FILL
421+50	Left	20	35	55
422+15	Left	20	35	55
422+30	Left	20	35	55
422+45	Left	20	35	55
422+60	Left	20	35	55


DRAINAGE STRUCTURES				
STATION	Side	15' 24'	Exc.	FILL
422+15	Left	20	35	55
422+30	Left	20	35	55
422+45	Left	20	35	55
422+60	Left	20	35	55

Exc. 15' 03" Bl.  
D. 4"  
L. 1.793  
P. 14321


Sta 422+65 Build  
2-25' x 1-49' I-Beam Span  
on Cret. P. & Bents  
20' Span E. R.  
Fill Exc. 97.48'±  
Rev. Exc. 97.48'±  
(See Br. Dwg. #E93)

End Ref. 6  
Sec. 1

Dep. Ref. 6  
Sec. 2 - W. R. HOVIS







STATION SPWD SEE NEW ENCL

STATION	SPWD	SEE	NEW ENCL
422-107	0244	4124	50' 26" 25'
422-108	114	10	32' 21"
422-109	0244	4124	30' 31' 25"

STATION SPWD SEE NEW ENCL

STATION	SPWD	SEE	NEW ENCL
422-107	0244	4124	50' 26" 25'
422-108	114	10	32' 21"
422-109	0244	4124	30' 31' 25"

