

February 5, 2025

**Pemiscot County Port Authority
John Ferguson II
2353 N. State Hwy D
Hayti, MO 63851**

BIDDING ADDENDUM 4

**For work titled:
Office Space Build-Out**

Project Number / Client Number: 24-7022

TO ALL BIDDERS

GENERAL NOTES

This addendum is issued for the purpose of clarifying the intent of the contract documents or for making necessary corrections, deletions, and/or additions to the documents on all items of discrepancy raised up to the time of the issuance of this addendum.

Each bidder is hereby instructed and authorized to incorporate into his proposal the instructions contained in this addendum. This addendum forms a part of the bidding and contract documents and modifies the original bidding documents, dated January 2025. Acknowledge receipt of this addendum in space provided on Bid Form. **FAILURE TO DO SO MAY SUBJECT BIDDER TO DISQUALIFICATION.**

This addendum consists of one (1) – 8-1/2" x 11" pages AND eleven (11) – 24"x36" pages.

PLANS

Replace Plan Sheets with revised plan sheets noted as Addenda #4 in the "Revisions History" title block (all Architectural Plan Sheets) note that not all changes/revisions are highlighted in red:

INDEX OF ARCHITECTURAL DRAWINGS

G100	Cover
G101	Architectural Specifications
G102	Architectural Specifications
G103	Architectural Specifications
G201	Accessibilty Notes & Details
G202	Accessibilty Notes & Details
G203	Ceiling Details
A101	Floor Plan
A102	Wall, Door & Window Schedule, Interior Elevations
A501	Building Sections
A801	Reflective Ceiling Plan

All other terms and conditions of the Project Manual and Drawings shall remain unchanged.

END OF ADDENDUM 4











Symbols Key

- Rough Lumber
- Finish Lumber
- Structural Steel
- Brick
- Concrete Masonry Unit
- Poured-In-Place Concrete
- Gravel
- Window Glazing
- Batt Insulation
- Rigid Insulation
- Plywood
- Sand/Mortar/Plaster
- Earth
- New Construction
- Existing Construction
- Varies Insulation Type - Refer Wall Details

Dimension X'-X"

Elevation Datum + 8'-0"

Revision Indicates Sheet Revision



INDEX OF ARCHITECTURAL DRAWINGS

- G100

Cover
- G101

Architectural Specifications
- G102

Architectural Specifications
- G103

Architectural Specifications
- G201

Accessibilty Notes & Details
- G202

Accessibilty Notes & Details
- G203

Ceiling Details
- A101

Floor Plan
- A102

Wall, Door & Window Schedule, Interior Elevations
- A501

Building Sections
- A801

Reflective Ceiling Plan

Building Codes:

- Local Adopted County Codes:
- International Building Codes (IBC); 2003 Ed.
 - International Plumbing Code (IPC); 2006 Ed.
 - International Fire Code (IFC); 2006 Ed.
 - International Mechanical Code (IMC); 2006 Ed.
 - National Electrical Code (NEC); 2005 Ed.
- Federal Codes:
- 2010 ADA

Building Code Information

Use & Occupancy Classification [Sec. 304, Sec. 311]:	Mixed Use: Business 'B'; Storage 'S1'
Type of Construction [Table 601]:	Type 2B
Allowable Height & Area [Tables 503]:	Business (B): 4S; 23,000 SF Storage (S1): 3S; 17,500SF
Actual Height & Area (Gross):	Business (B) 1S; 3,000 SF Storage (S1) 1S; 6,000 SF
Automatic Sprinkler System [Sec. 903]:	No
Occupancy Load [Sec. 1004]	53
Min. Egress Exits [Sec. 1014] (Per Occupancy 1-500)	2 Required
Exit & Egress Access Doorway Separation [1014.2.1]	56'-5" (Min. 1/2 Overall Diagonal Dim.)
Max. Common Path of Egress Travel (CPET) [Table 1013.3]	75'
Max. Exit Access Travel Distance (EATD) [Table 1015]	200' (NS; 'B'); 200' (NS; 'S-1')
Egress Exits Provided	3 Provided

General Notes:

- A.

Contractors shall familiarize themselves with the project site and plans prior bidding and shall notify the Design Builder (618-687-3900) of any discrepancies in a formal Request for Information (RFI).
- B.

The general contractor shall be responsible to coordinate with all subcontractors. This does not relieve the subcontractors from coordinating with the General Contractor.
- C.

The general contractor and subcontractors shall both be responsible to cross-reference and coordinate work between all trades and drawing sheets.
- D.

All work shall comply with local, state, and federal codes & laws.
- E.

At the completion of the project the contractor shall turn in one full size set of "As-Built" drawings. "As-Built" shall record all field changes.
- F.

At the completion of the project the contractor shall turn in all Warranties & O&M's.
- G.

All materials/equipment shall be new and free of all hazardous materials.
- H.

Contractors shall submit shop drawings/product data and physical colors samples as requested.
- I.

The owner shall be responsible for all utilities during construction.
- J.

Owner has first salvage rights to all removed materials.



KLINGNER

ASSOCIATES, P.C.

Engineers • Architects • Surveyors

www.klingner.com

Quincy, IL, Hannibal, MO

Burlington, IL, Kansas City, MO


Columbia, MO, Davenport, IA

© 2004 KLINGNER & ASSOCIATES P.C.
This document shall not be used for any purpose or project for which it is not intended. Klingner & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims, damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this document. In addition, unauthorized reproduction of this document, in part or as a whole, is prohibited.

REVISION HISTORY			
NO.	DESCRIPTION	DATE	APPR.

1	Addendum #4	02/05/25	
---	-------------	----------	--

ISSUED FOR
Bidding



PEMISCOT COUNTY PORT AUTHORITY

OFFICE BUILDING BUILT OUT

PEMISCOT COUNTY PORT AUTHORITY

111 EAST 3RD STREET

CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"	
Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.	
DESIGNED Designer	DRAWN Author
FIELD	FIELD BOOK
CHECKED Checker	CHECK DATE

SHEET TITLE	
Cover	
PROJECT NO. 24-7022	
DRAWING ISSUED DATE: 12-05-24	
SHEET G100	

C. Shop Drawings: Indicate system dimensions, framed opening requirements and tolerances, affected related work, expansion and contraction joint location and details, and field welding required.

D. Hardware Schedule: Complete itemization of each item of hardware to be provided for each door, cross-referenced to door identification numbers in Contract Documents.

PART 2 PRODUCTS

2.01 BASIS OF DESIGN -- FRAMING FOR INSULATING GLAZING

A. Center-Set Style, Thermally-Broken:

1. Vertical Mullion Dimensions: 2 inches wide by 4-1/2 inches deep (51 mm wide by 114 mm deep).

B. Center-Set Style, Not Thermally-Broken:

1. Vertical Mullion Dimensions: 1-3/4 inches wide by 4-1/2 inches deep (45 mm wide by 114 mm deep).

2.02 BASIS OF DESIGN -- SWINGING DOORS

A. Narrow Stile, Insulating Glazing, Thermally-Broken:

B. Narrow Stile, Insulating Glazing, Not Thermally-Broken:

1. Thickness: 1-3/4 inches (43 mm).

2.03 ALUMINUM-FRAMED STOREFRONT

A. Aluminum-Framed Storefront: Factory fabricated, factory finished aluminum framing members with infill, and related flashings, anchorage and attachment devices.

1. Fabrication: Joints and corners flush, hairline, and weatherproof, accurately fitted and secured, prepared to receive anchors and hardware, fasteners and attachments concealed from view; reinforced as required for imposed loads.
2. Construction: Eliminate noises caused by wind and thermal movement, prevent vibration harmonics, and prevent "stack effect" in internal spaces.
3. System Internal Drainage: Drain to the exterior by means of a weep drainage network any water entering joints, condensation occurring in glazing channel, and migrating moisture occurring within system.
4. Expansion/Contraction: Provide for expansion and contraction within system components caused by cycling temperature range of 170 degrees F (95 degrees C) over a 12 hour period without causing detrimental effect to system components, anchorages, and other building elements.
5. Movement: Allow for movement between storefront and adjacent construction, without damage to components or deterioration of seals.
6. Perimeter Clearance: Minimize space between framing members and adjacent construction while allowing expected movement.

B. Performance Requirements

1. Wind Loads: Design size and shape components to withstand the specified load requirements without damage or permanent set, when tested in accordance with ASTM E330/E330M, using loads 1.5 times the design wind loads and 10 second duration of maximum load.
 - a. Member Deflection: Limit member deflection to flexure limit of glass in any direction, with full recovery of glazing materials.
2. Air Leakage: 0.06 cfm/sq ft (0.3 L/sec sq m) maximum leakage of storefront wall area when tested in accordance with ASTM E283/E283M at 1.57 psf (75 Pa) pressure difference.

2.04 COMPONENTS

A. Aluminum Framing Members: Tubular aluminum sections, thermally broken with interior section insulated from exterior, drainage holes and internal weep drainage system.

1. Glazing Stops: Flush.

B. Glazing: See Section 08 00 00.

C. Swing Doors: Glazed aluminum.

1. Finish: Same as storefront.

2.05 MATERIALS

A. Extruded Aluminum: ASTM B221 (ASTM B221M).

B. Fasteners: Stainless steel.

C. Glazing Gaskets: Type to suit application to achieve weather, moisture, and air infiltration requirements.

2.06 HARDWARE

A. For each door, include weatherstripping, sill sweep strip, and threshold.

B. Other Door Hardware: Storefront manufacturer's standard type to suit application.

1. Finish on Hand-Constructed Items: Polished chrome.

C. For each door, include but hinges, pivots, push handle, pull handle, exit device, narrow stile handle latch, and closer.

PART 3 EXECUTION

3.01 INSTALLATION

A. Install wall system in accordance with manufacturer's instructions.

B. Attach to structure to permit sufficient adjustment to accommodate construction tolerances and other irregularities.

C. Provide alignment attachments and shims to permanently fasten system to building structure.

D. Align assembly plumb and level, free of warp or twist. Maintain assembly dimensional tolerances, aligning with adjacent work.

E. Provide thermal isolation where components penetrate or disrupt building insulation.

F. Install sill flashings. Turn up ends and edges; seal to adjacent work to form water tight dam.

G. Where fasteners penetrate sill flashings, make watertight by seating and sealing fastener heads to sill flashing.

H. Pack fibrous insulation in shim spaces at perimeter of assembly to maintain continuity of thermal barrier.

I. Set thresholds in bed of sealant and secure.

J. Install hardware using templates provided.

K. Touch-up minor damage to factory applied finish; replace components that cannot be satisfactorily repaired.

3.02 ADJUSTING

A. Adjust operating hardware and sash for smooth operation.

3.03 CLEANING

A. Remove protective material from pre-finished aluminum surfaces.

END OF SECTION
SECTION 08 71 00
DOOR HARDWARE

PART 1 GENERAL

1.01 ADMINISTRATIVE REQUIREMENTS

A. Coordinate the manufacture, fabrication, and installation of products that door hardware is installed on.

B. Keying Requirements Meeting:

1. Schedule meeting at project site prior to Contractor occupancy.
2. Attendance Required:
 - a. Contractor.
 - b. Owner.
 - c. Installer's Architectural Hardware Consultant (AHC).
3. Agenda:
 - a. Establish keying requirements.
 - b. Verify locksets and locking hardware are functionally correct for project requirements.
 - c. Verify that keying and programming complies with project requirements.
4. Incorporate "Keying Requirements Meeting" decisions into keying submittal upon review of door hardware keying system including, but not limited to, the following:

5. Record minutes and distribute copies within two days after meeting to participants, with two copies to Architect, Owner, participants, and those affected by decisions made.

6. Deliver established keying requirements to manufacturers.

1.02 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements for submittal procedures.

B. Product Data: Manufacturer's catalog literature for each type of hardware, marked to clearly show products to be furnished for this project, and includes construction details, material descriptions, finishes, and dimensions and profiles of individual components.

C. Shop Drawings - Door Hardware Schedule: Submit detailed listing that includes each item of hardware to be installed on each door. Use door numbering scheme as included in Contract Documents.

1. Prepared by or under supervision of Architectural Hardware Consultant (AHC).

2. Provide complete description for each door listed.

PART 2 PRODUCTS

2.01 DESIGN AND PERFORMANCE CRITERIA

A. Provide specified door hardware as required to make doors fully functional, compliant with applicable codes, and secure to extent indicated.

B. Provide individual items of single type, of same model, and by same manufacturer.

C. Provide door hardware products that comply with the following requirements:

1. Applicable provisions of federal, state, and local codes.

2. Accessibility: ADA Standards and ICC A117.1.

2.02 FINISHES

A. Finishes: Identified in Section 08 0671 - Door Hardware Schedule.

PART 3 EXECUTION

3.01 INSTALLATION

A. Install hardware in accordance with manufacturer's instructions and applicable codes.

B. Use templates provided by hardware item manufacturer.

C. Door Hardware Mounting Heights: Distance from finished floor to center line of hardware item. As indicated in following list; unless noted otherwise in Door Hardware Schedule or on drawings.

D. Set exterior door thresholds with full-width bead of elastomeric sealant at each point of contact with floor providing a continuous weather seal; anchor thresholds with stainless steel countersunk screws.

3.02 ADJUSTING

A. Adjust work under provisions of Section 01 70 00 - Execution and Closeout Requirements.

B. Adjust hardware for smooth operation.

C. Adjust gasketing for complete, continuous seal; replace if unable to make complete seal.

END OF SECTION
SECTION 09 21 16
GYPSUM BOARD ASSEMBLIES - USG

PART 1 GENERAL

1.01 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements for submittal procedures.

B. Product Data: Include data on metal framing, gypsum board, glass mat faced gypsum board, sheathing, accessories, and joint finishing system.

PART 2 PRODUCTS

2.01 WALL ASSEMBLY TYPES

A. See drawings for graphic representations of assemblies.

2.02 GYPSUM BOARD ASSEMBLIES

A. Provide completed assemblies complying with ASTM C840 and GA-216.

B. Interior Partitions, Indicated as Acoustic: Provide completed assemblies with the following characteristics:

1. Sound Transmission Loss Values: STC as indicated, calculated in accordance with ASTM E413, based on tests conducted in accordance with ASTM E90.

2.03 BOARD MATERIALS

A. Manufacturers - Gypsum-Based Board:

1. USG Corporation: www.usg.com

B. Gypsum Board: Paper-faced gypsum panels as defined in ASTM C1396/C1396M; sizes to minimize joints in place; ends square cut.

1. Application: Use for vertical surfaces and ceilings, unless otherwise indicated.

2. Thickness:

a. Vertical Surfaces: As indicated on drawings.

3. Moisture- and Mold-Resistant Paper-Faced Board Products:

2.04 GYPSUM WALLBOARD ACCESSORIES

A. Beads, Joint Accessories, and Other Trim: ASTM C1047, rigid plastic, galvanized steel, or rolled zinc, unless otherwise indicated.

1. Corner Beads: Low profile, for 90 degree outside corners.

2. L-Trim with Tear-Away Strip: Sized to fit gypsum wallboard.

3. Expansion Joints:

a. Type: V-shaped PVC with tear away fins.

B. Joint Materials: ASTM C475/C475M and as recommended by gypsum board manufacturer for project conditions.

C. Fasteners and Adhesives: Products recommended by gypsum board manufacturer.

PART 3 EXECUTION

3.01 FRAMING INSTALLATION

A. Metal Framing: Install in accordance with ASTM C754 and manufacturer's instructions.

B. Studs: Space studs at 16 inches on center (at 406 mm on center).

1. Extend partition framing to structure where indicated and to ceiling in other locations.

2. Partitions Terminating at Ceiling: Attach ceiling runner securely to ceiling track in accordance with manufacturer's instructions.

C. Openings: Reinforce openings as required for weight of doors or operable panels, using not less than double studs at jams.

D. Blocking: Install wood blocking for support of items outline on drawing and/or as requested by using agency.

3.02 ACOUSTIC ACCESSORIES INSTALLATION

A. Acoustic Insulation: Place tightly within spaces, around cut openings, behind and around electrical and mechanical items within partitions, and tight to items passing through partitions.

B. Acoustic Sealant: Install in accordance with manufacturer's instructions.

3.03 BOARD INSTALLATION

A. Comply with ASTM C840, GA-216, and manufacturer's instructions. Install to minimize butt end joints, especially in highly visible locations.

3.04 JOINT TREATMENT

A. Finish gypsum board in accordance with levels defined in ASTM C840, as follows:

1. Level 5: Walls and ceilings to receive semi-gloss or gloss paint finish and other areas specifically indicated.

2. Level 4: Walls and ceilings to receive paint finish or wall coverings, unless otherwise indicated.

3. Level 2: In utility areas, behind cabinetry, and on backing board to receive tile finish.

4. Level 1: Fire-resistance-rated wall areas above finished ceilings, whether or not accessible in the completed construction.

B. Tape, fill, and sand exposed joints, edges, and corners to produce smooth surface ready to receive finishes.

1. Feather coats of joint compound so that camber is maximum 1/32 inch (0.8 mm).

C. Where Level 5 finish is indicated, spray apply high build drywall surfacer over entire surface after joints have been properly treated; achieve a flat and tool mark-free finish.

END OF SECTION
SECTION 09 22 16
NON-STRUCTURAL METAL FRAMING

PART 1 GENERAL

1.01 SECTION INCLUDES

A. Metal partition, ceiling, and soffit framing.

B. Framing accessories.

1.02 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements for submittal procedures.

B. Shop Drawings:

1. Indicate prefabricated work, component details, stud layout, framed openings, anchorage to structure, acoustic details, type and location of fasteners, accessories, and items of other related work.

2. Describe method for securing studs to tracks, splicing, and for blocking and reinforcement of framing connections.

C. Product Data: Provide data describing framing member materials and finish, product criteria, load charts, and limitations.

D. Product Data: Provide manufacturer's data on partition head to structure connectors, showing compliance with requirements.

PART 2 PRODUCTS

2.01 MANUFACTURERS

A. Metal Framing, Connectors, and Accessories:

1. ClarkDietrich: www.clarkdietrich.com/#sle.

2. Jaimes Industries: www.jaimesind.com/#sle.

3. Steel Construction Systems: www.steelconsystems.com/#sle.

4. Approved Equal.

2.02 FRAMING MATERIALS

A. Fire-Resistance-Rated Assemblies: Comply with applicable code and as follows:

1. Fire-Resistance-Rated Partitions: Listed assembly by UL, No. U419; 1 hour rating.

B. Loadbearing Studs: As specified in Section 05 40 00.

C. Non-Loadbearing Framing System Components: AISI S220; sheet steel, of size and properties necessary for the spacing indicated, with maximum deflection of wall framing of L/240 at 5 psf (L/240 at 240 Pa).

1. Studs: C-shaped.

2. Runners: U-shaped, sized to match studs.

3. Furring: Hat-shaped sections, minimum depth of 7/8 inch (22 mm).

D. Partition Head to Structure Connections: Provide track fastened to structure with legs of sufficient length to accommodate deflection, for friction fit of studs cut short and braced with continuous bridging on both sides.

E. Non-Loadbearing Framing Accessories:

1. Ceiling Hangers: Type and size as specified in ASTM C754 for spacing required.

2. Bracing and Bridging: ASTM A653/A653M G90 galvanized steel; for lateral bracing of wall studs with slots for engaging on-module studs.

3. Framing Connectors: ASTM A653/A653M steel clips; secures cold rolled channel to wall studs for lateral bracing.

PART 3 EXECUTION

3.01 INSTALLATION OF STUD FRAMING

A. Comply with requirements of ASTM C1007.

B. Install structural members and connections complying with ASTM C1007.

C. Extend partition framing to structure where indicated and to ceiling in other locations.

D. Partitions Terminating at Ceiling: Attach ceiling runner securely to ceiling track in accordance with manufacturer's instructions.

E. Align and secure top and bottom runners at 24 inches (600 mm) on center.

F. Fit runners under and above openings; secure intermediate studs to same spacing as wall studs.

G. Install studs vertically at 16 inches (400 mm) on center.

H. Align stud web openings horizontally.

I. Secure studs to tracks using crimping method. Do not weld.

J. Fabricate corners using a minimum of three studs.

K. Install double studs at wall openings, door and window jambs, not more than 2 inches (50 mm) from each side of openings.

L. Coordinate installation of bucks, anchors, and blocking with electrical, mechanical, and other work to be placed within or behind stud framing.

M. Furring: Install at spacing and locations shown on drawings. Lap splices a minimum of 6 inches (150 mm).

3.02 CEILING AND SOFFIT FRAMING

A. Install furring after work above ceiling or soffit is complete. Coordinate the location of hangers with other work.

B. Install furring independent of walls, columns, and above-ceiling work.

C. Securely anchor hangers to structural members or embed them in structural slab. Space hangers as required to limit deflection to criteria indicated. Use rigid hangers at exterior soffits.

D. Space main carrying channels at maximum 72 inches (1 800 mm) on center, and not more than 6 inches (150 mm) from wall surfaces. Lap splice securely.

E. Securely fix carrying channels to hangers to prevent turning or twisting and to transmit full load to hangers.

F. Place furring channels perpendicular to carrying channels, not more than 2 inches (50 mm) from perimeter walls, and rigidly secure. Lap splices securely.

END OF SECTION
SECTION 09 51 00
ACOUSTICAL CEILINGS - USG

PART 1 GENERAL

1.01 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements for submittal procedures.

B. Shop Drawings: Indicate grid layout and related dimensioning.

C. Product Data: Provide data on suspension system components and acoustical units.

PART 2 PRODUCTS

2.01 CEILING ASSEMBLIES

A. Refer to Room Finish Schedule and Reflected Ceiling Plans on drawings for additional ceiling assembly information.

B. Acoustical Ceiling Assembly Type ACT-1:

1. Acoustical Units: Armstrong - Ultima Lay-in Square - Item No. 1900

a. Panel Size: 24 inches by 24 inches (2 by 2) panel (609.6 mm by 609.6 mm).

b. Panel Edge: SQ edge.

c. Color: Flat White.

2. Suspension Grid: Armstrong 15/16 Prelude XL (No. 1356)

2.02 CEILING COMPONENT PRODUCTS

A. Suspension Systems:

1. Metal Suspension Systems - General: Complying with ASTM C635/C635M, die cut and interlocking components, with wall angles and moldings, curtain pockets, and splices as required.

B. Moldings and Trim:

1. Edge Molding, Expansion Joints, and Splices - General: Same material, thickness, and finish as metal pan panels, unless otherwise indicated.
2. Perimeter Wall Moldings: Same metal and finish as grid.
 - a. Size: As required for installation conditions.
 - b. Acoustical Sealant For Perimeter Moldings: Nonhardening, nonskinning, for use in conjunction with suspended ceiling system.
3. Trim Accessories: Manufacturer's standard clips, cleats splice plates, extension plates, closure plates, corner pieces, and similar accessories required for a complete installation.

2.03 ACCESSORIES

A. Support Channels, Carriers, and Hangers: Galvanized steel; size and type to suit application and ceiling system fitness requirement specified.

B. Suspension Wire: Size and type as required for application, seismic requirements, and ceiling system fitness requirement specified.

1. Concealed Suspension:
 - a. Suspension Wire: Steel, annealed, galvanized finish, 12 gauge, 0.0808 (2.05 mm) diameter, complying with ASTM A641/A641M.

C. Touch-Up Paint for Exposed Surfaces: Type and color to match acoustical units and suspension system grid and trim elements.

D. Touch-Up Paint For Concealed Items: Zinc rich type, as recommended by ceiling system manufacturer.

2.04 FABRICATION

A. Shop fabricate ceiling components to the greatest extent possible.

PART 3 EXECUTION

3.01 PREPARATION

A. Coordinate the location of hangers with other work.

B. Install ceiling system after major above-ceiling work is complete.

C. Acclimate wood ceiling materials by removing from packaging in installation area a minimum of 72 hours prior to installation.

3.02 INSTALLATION - SUSPENSION SYSTEM

A. Install suspension system in accordance with ASTM C636/C636M and manufacturer's instructions and as supplemented in this section.

B. Install hangers and inserts coordinated with overhead work. Provide additional hangers and supports as required.

C. Rigidly secure system, including integral mechanical and electrical components, for maximum deflection of 1/360.

D. Seismic Suspension System, Seismic Design Category C: Hang suspension system independent of walls, columns, ducts, pipes and conduit. Maintain a 3/8 inch (9 mm) clearance between grid ends and wall.

E. Where ducts, facility services, or equipment prevent the regular spacing of hangers, reinforce the nearest affected hangers and related carrying channels to span the extra distance.

F. Do not support components on main runners or cross runners if weight causes total dead load to exceed deflection capability.

G. Support fixture loads using supplementary hangers located within 6 inches (152 mm) of each corner, or support components independently.

H. Do not eccentrically load system or induce rotation of runners.

I. Edge Moldings: Install at intersection of ceiling and vertical surfaces and penetrations, using components of maximum length; set level. Provide edge moldings at junction with other ceiling finishes. Miter corners. Provide preformed edge closures to match bulkheaded cornered partitions.

1. Use longest practical lengths.

3.03 INSTALLATION - ACOUSTICAL UNITS

A. Install acoustical units in accordance with manufacturer's instructions.

B. Fit acoustical units in place, free from damaged edges or other defects detrimental to appearance and function.

C. Fit edge trim neatly against abutting surfaces.

D. Install acoustical units level, in uniform plane, and free from twist, warp, and dents.

E. Cutting Acoustical Units:

1. Make field cut edges of same profile as factory edges.

F. Where round obstructions occur, provide preformed closures to match perimeter molding.

END OF SECTION
SECTION 09 91 13
EXTERIOR PAINTING

PART 1 GENERAL

1.01 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.

B. Product Data: Provide complete list of products to be used, with the following information for each:

1. Manufacturer's name, product name and/or catalog number, and general product category (e.g. "alkyd enamel").
2. Cross-reference to specified paint system(s) product is to be used in; include description of each system.

C. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches (216 by 279 mm) in size, illustrating range of colors available for each finishing product specified.

1. Where sheen is specified, submit samples in only that sheen.

PART 2 PRODUCTS

2.01 MANUFACTURERS

A. Provide paints and finishes used in any individual system from the same manufacturer; no exceptions.

B. Paints:

1. Sherwin-Williams Company: www.sherwin-williams.com

C. Primer Sealers: Same as manufactured as top coats.

2.02 PAINTS AND FINISHES - GENERAL

A. Paints and Finishes: Ready-mixed, unless required to be a field-catalyzed paint.

1. Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating, with good flow and brushing properties, and capable of drying or curing free of streaks or sags.
2. Supply each paint material in quantity required to complete entire project's work from a single production run.
3. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is described explicitly in manufacturer's product instructions.

2.03 PAINT SYSTEMS - EXTERIOR

A. Exterior Surfaces to be Painted, Unless Otherwise Indicated: Including concrete, concrete masonry units, brick, fiber cement siding, primed wood, primed metal, and metal doors/frames.

1. Two top coats and one coat primer.
2. Top Coat(s): Color Indicated on Drawings.

2.04 PRIMERS

A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top coats.

PART 3 EXECUTION

.01 PREPARATION

A. Clean surfaces thoroughly and correct defects prior to application.

B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

C. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces for finishing.

D. Seal surfaces that might cause bleed through or staining of topcoat.

E. Remove mildew from impervious surfaces by scrubbing with solution of tetra-sodium phosphate and bleach. Rinse with clean water and allow surface to dry.

F. Concrete:

G. Masonry:

H. Fiber Cement Siding: Remove dirt, dust and other foreign matter with a stiff fiber brush. Do not coat surfaces if moisture content or alkalinity of surfaces to be coated exceeds that permitted in manufacturer's written instructions.

I. Exterior Wood Surfaces to Receive Opaque Finish: Remove dust, grit, and foreign matter. Seal knots, pitch cracks, and sappy sections. Fill nail holes with tinted exterior caulking compound after prime coat has been applied. Back prime concealed surfaces before installation.

J. Metal Doors to be Painted: Prime metal door top and bottom edge surfaces.

.02 APPLICATION

A. Exterior Wood to Receive Opaque Finish: If final painting must be delayed more than 2 weeks after installation of woodwork, apply primer within 2 weeks and final coating within 4 weeks.

B. Apply products in accordance with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual".

C. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.

D. Apply each coat to uniform appearance.

E. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.

F. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

END OF SECTION
SECTION 09 91 23
INTERIOR PAINTING

PART 1 GENERAL

.01 SUBMITTALS

A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.

B. Product Data: Provide complete list of products to be used, with the following information for each:

1. Manufacturer's name, product name and/or catalog number, and general product category (e.g., "alkyd enamel").

2. Cross-reference to specified paint system products to be used in project; include description of each system.

C. Samples: Submit three paper "draw down" samples, 8-1/2 by 11 inches (216 by 279 mm) in size, illustrating range of colors available for each finishing product specified.

1. Where sheen is specified, submit samples in only that sheen.

PART 2 PRODUCTS

.01 MANUFACTURERS

A. Provide paints and finishes used in any individual system from the same manufacturer; no exceptions.

B. Paints:

1. Sherwin-Williams Company: www.sherwin-williams.com/#/sie.

C. Primer Sealers: Same manufacturer as top coats.

.02 PAINTS AND FINISHES - GENERAL

A. Paints and Finishes: Ready-mixed, unless intended to be a field-catalyzed paint.

1. Provide paints and finishes of a soft paste consistency, capable of being readily and uniformly dispersed to a homogeneous coating, with good flow and brushing properties, and capable of drying or curing free of streaks or sags.

2. Supply each paint material in quantity required to complete entire project's work from a single production run.

3. Do not reduce, thin, or dilute paint or finishes or add materials unless such procedure is specifically described in manufacturer's product instructions.

B. Colors: To be selected from manufacturer's full range of available colors.

1. Selection to be made by Architect after award of contract.

.03 PAINT SYSTEMS - INTERIOR

A. Interior Surfaces to be Painted. Unless Otherwise Indicated: Including gypsum board, concrete, concrete masonry units, brick, wood, plaster, uncoated steel, shop primed steel, galvanized steel, aluminum, and acoustical ceilings.

1. Two top coats and one coat primer.

2. **PT-1:** Interior Latex Enamel: Sherwin-Williams ProMar 400 VOC Interior Latex

a. Sheen: Satin

b. Color: To be selected by owner

c. Locations: All walls

3. **PT-2:** Interior Latex Enamel: Sherwin-Williams ProClassic Alkyd Interior Enamel

a. Sheen: Semi Gloss

b. Color: to be selected by owner

c. Locations: doors, frames and casing

1) Doors & Frames

4. Primer: As recommended by top coat manufacturer for specific substrate.

.04 PRIMERS

A. Primers: Provide the following unless other primer is required or recommended by manufacturer of top coats.

PART 3 EXECUTION

.01 PREPARATION

A. Clean surfaces thoroughly and correct defects prior to application.

B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

C. Remove or mask surface appurtenances, including electrical plates, hardware, light fixture trim, escutcheons, and fittings, prior to preparing surfaces or finishing.

D. Seal surfaces that might cause bleed through or staining of topcoat.

E. Concrete:

F. Masonry:

G. Gypsum Board: Fill minor defects with filler compound. Spot prime defects after repair.

H. Plaster: Fill hairline cracks, small holes, and imperfections with latex patching plaster. Make smooth and flush with adjacent surfaces. Wash and neutralize high-alkali surfaces.

I. Aluminum: Remove surface contamination and oils and wash with solvent according to SSPC-SP 1.

J. Galvanized Surfaces:

K. Ferrous Metal:

1. Solvent clean according to SSPC-SP 1.

<div>KLINGINGER & ASSOCIATES P.C. Engineers • Architects • Surveyors www.klinginger.com</div> <div>Quincy, IL, Hannibal, MO Burlington, VA, Columbia, MD, Davenport, IA Carbondale, Illinois 2160 West Main St. 518.331.4455</div>					
<small>© 2024 KLINGINGER & ASSOCIATES P.C. This document shall not be used for any purpose or project for which it is not intended. Klinginger & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims. Damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this documents, in addition, unauthorized reproduction of this document, in part or as a whole, is prohibited.</small>					
REVISION HISTORY					
NO.	DESCRIPTION	DATE	APPR.		
Δ	Addendum #4	02/05/25			
ISSUED FOR Bidding					
PEMISCOT COUNTY PORT AUTHORITY OFFICE BUILDING BUILT OUT					
PEMISCOT COUNTY PORT AUTHORITY 111 EAST 3RD STREET CARUTHERSVILLE, MO 63830					
Non-Reduced Sheet Size: 24" x 36" Full scale plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.					
DESIGNED Designer	DRAWN Author				
FIELD Field Book	FIELD BOOK				
CHECKED Checker	CHECK DATE				
SHEET TITLE Architectural Specifications					

2. Shop-Primed Surfaces: Sand and scrape to remove loose primer and rust. Feather edges to make touch-up patches inconspicuous. Clean surfaces with solvent. Prime bare steel surfaces. Re-prime entire shop-primed item.
3. Remove rust, loose mill scale, and other foreign substances using methods recommended in writing by paint manufacturer and blast cleaning according to SSPC-SP 6 Commercial Blast Cleaning. Protect from corrosion until coated.
- L. Wood Surfaces to Receive Opaque Finish: Wipe off dust and grit prior to priming. Seal knots, pitch streaks, and sappy sections with sealer. Fill nail holes and cracks after primer has dried; sand between coats. Back prime concealed surfaces before installation.

3.02 APPLICATION

- A. Apply products in accordance with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual".
- B. Do not apply finishes to surfaces that are not dry. Allow applied coats to dry before next coat is applied.
- C. Apply each coat to uniform appearance in thicknesses specified by manufacturer.
- D. Sand wood and metal surfaces lightly between coats to achieve required finish.
- E. Vacuum clean surfaces of loose particles. Use tack cloth to remove dust and particles just prior to applying next coat.
- F. Reinstall electrical cover plates, hardware, light fixture trim, escutcheons, and fittings removed prior to finishing.

END OF SECTION

SECTION 10 28 00

TOILET, BATH, AND LAUNDRY ACCESSORIES

PART 1 GENERAL

1.01 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Submit data on accessories describing size, finish, details of function, and attachment methods.

PART 2 PRODUCTS

2.01 COMMERCIAL TOILET ACCESSORIES

- A. Toilet Paper Dispenser: Double roll, surface mounted, for coreless type rolls.
- B. Mirrors: Stainless steel framed, 1/4 inch (6 mm) thick annealed float glass; ASTM C1036.
- C. Grab Bars: Stainless steel, smooth surface.
1. Standard Duty Grab Bars:
- a. Push/Pull Point Load: 250 pound-force (1112 N), minimum.
- b. Dimensions: 1-1/4 inch (32 mm) outside diameter, minimum 0.05 inch (1.3 mm) wall thickness, exposed flange mounting, 1-1/2 inch (38 mm) clearance between wall and inside of grab bar.
- c. Length and Configuration: As indicated on drawings.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install accessories in accordance with manufacturers' instructions in locations indicated on drawings.
- B. Install plumb and level, securely and rigidly anchored to substrate.
- C. Mounting Heights: As required by accessibility regulations, unless otherwise indicated.

END OF SECTION




KLINGNER & ASSOCIATES, P.C.
Engineers • Architects • Surveyors

www.klingner.com
Quincy, IL, Hannibal, MO
Burlington, IA, Columbia, MO
Carbondale, Illinois
2150 West Main St.
618.331.4050

© 2024 KLINGNER & ASSOCIATES P.C.
This document shall not be used for any purpose or project for which it is not intended. Klingner & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims, damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this document. In addition, unauthorized reproduction of this document, in part or as a whole, is prohibited.

REVISION HISTORY			
NO.	DESCRIPTION	DATE	APPR.
1	Addendum #4	02/05/25	

ISSUED FOR
Bidding



PEMISCOT COUNTY PORT AUTHORITY
OFFICE BUILDING BUILT OUT

PEMISCOT COUNTY PORT AUTHORITY
111 EAST 3RD STREET
CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"
Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.



DESIGNED Designer	DRAWN Author
FIELD	FIELD BOOK
CHECKED Checker	CHECK DATE

SHEET TITLE
Architectural
Specifications

PROJECT NO.
24-7022
DRAWING ISSUED DATE:
12-05-24

SHEET
G103

Note:
Changes In Level Grater Than 1/2" Shall Be By Means Of A Ramp.



Change in Level

1 SCALE: NOT TO SCALE




Figure 305.3
Clear Floor or Ground Space




Figure 305.5
Position of Clear Floor or Ground Space




Figure 305.7.1
Maneuvering Clearance in an Alcove, Forward Approach




Figure 305.7.2
Maneuvering Clearance in an Alcove, Parallel Approach

Clearance or Ground Space

5 SCALE: NOT TO SCALE




Figure 306.2
Toe Clearance








Figure 306.3
Knee Clearance

Toe and Knee Clearance

9 SCALE: NOT TO SCALE



Objects Mounted On Post Or Pylons



Walking Perpendicular To A Wall

Figure 307.2

Limits of Protruding Objects

13 SCALE: NOT TO SCALE




Figure 307.3

Post-Mounted Objects

2 SCALE: NOT TO SCALE




Figure 307.4

Vertical Clearance

6 SCALE: NOT TO SCALE




Figure 308.2.1
Unobstructed Forward Reach




Figure 308.2.2
Obstructed High Forward Reach

Forward Reach

10 SCALE: NOT TO SCALE




Figure 308.3.1
Unobstructed Side Reach




Figure 308.3.2
Obstructed High Side Reach

Side Reach

11 SCALE: NOT TO SCALE






Figure 403.5.1
Clear Width of an Accessible Route



(a) 180 degree turn



(b) 180 degree turn (Exception)

Figure 403.5.2

Clear Width

14 SCALE: NOT TO SCALE






Figure 404.2.3

Clear Width of Doorways


3 SCALE: NOT TO SCALE




(a) front approach



(b) side approach



(c) pocket or hinge approach




(d) stop or latch approach


Figure 404.2.4.2

Maneuvering Doorways without Doors


7 SCALE: NOT TO SCALE




(a) front approach, pull side




(b) front approach, push side




(c) front approach, push side, door provided with both closer and latch




(d) hinge approach, pull side




(e) hinge approach, pull side




(f) hinge approach, push side




(g) hinge approach, push side, door provided with both closer and latch




(h) latch approach, pull side



(i) latch approach, pull side, door provided with closer



(j) latch approach, push side




(k) latch approach, push side, door provided with closer


Provide This Space If Door Is Equipped With Both A Latch And A Closer

Maneuvering Doorways at Doors and Gates


12 SCALE: NOT TO SCALE




60" Diameter Space



T-Shaped Space For 180 Turns







Minimum Clear Width For Single Wheelchair



Minimum Clear Width For Two Wheelchairs

Figure 404.2.4.1


Installation Height and Location:
Signs shall be located 48" minimum above finish floor or ground surfaces, measured from the baseline of lowest tactile character and 60" maximum above the finish floor or ground surface, measured from the baseline of the highest tactile character.




1/8" Radius, Typ.

703.6.1 Pictogram Field:
Character and Braille shall not be located in the pictogram field.


703.6.2 Finish and Contrast:
Pictograms shall have a non-glare finish and shall contrast with either a light or dark field.



Proportions
International Symbol Of
Accessibility
Figure 703.7.2.1



International
TDD Symbol
Figure 703.7.2.2



International Symbol Of
Access For Hearing Loss
Figure 703.7.2.4




Figure 703.4.2
Location of Tactile Sign at Doors




Figure 703.4.1
Height of Tactile Characters Above Finish Floor or Ground

Permanent Signs

1 SCALE: NOT TO SCALE




Figure 604.5.1
Side Wall Grab Bar at Water Closet




Figure 604.7
Dispenser Outlet Location




Figure 604.5.2
Rear Wall Grab Bar at Water Closets

Figure 604.51.1
Side-Wall Grab Bar For Water Closet (ICC A117.1; 2017 Ed.)




Figure 608.2.1
Transfer Type Shower




Figure 608.3.1
Grab Bars for Transfer Type Showers




Figure 608.5.1
Transfer Type Shower

Note: inside finished dimensions measured at the center points of opposing sides

Grab Bar & Dispenser Location

4 SCALE: NOT TO SCALE




Figure 604.3.1
Size of Clearance at Water Closet




Figure 604.2
Water Closet Location




Figure 604.8.1.1
Size of Wheelchair Accessible Toilet Compartment

Transfer Type Showers

5 SCALE: NOT TO SCALE




Figure 608.2.2
Standard Roll-In Type Shower




Figure 608.2.3
Alternate Roll-In Type Shower

Note: Dimensions measured from centerline of opposing sides' material finish

Height & Depth Of Urinals

6 SCALE: NOT TO SCALE





Figure 704.2.1.2

Size of Water Closet

8 SCALE: NOT TO SCALE






Figure 604.8.1.4

Handrail Extensions at Roll-In Shower

9 SCALE: NOT TO SCALE




Figure 607.2
Clearance for Bathtubs




Figure 607.2
Clearance for Bathtubs




Figure 607.4.1
Grab Bars for Bathtubs with Permanent Seats




Figure 607.4.2
Grab Bars for Bathtubs with Removable In-Tub Seats




Figure 607.5
Bathtub Control Location

Note: Controls shall be located between the bathtub rim, grab bar, and the centerline of the width of the bathtub.

Forward Approach Clearance

10 SCALE: NOT TO SCALE




Figure 607.4.1
Grab Bars for Bathtubs with Permanent Seats

Figure 607.4.2
Grab Bars for Bathtubs with Removable In-Tub Seats

Figure 607.5
Bathtub Control Location

Note: Controls shall be located between the bathtub rim, grab bar, and the centerline of the width of the bathtub.

Handrail Extensions

7 SCALE: NOT TO SCALE




Figure 505.10.1
Top and Bottom Handrail Extension at Ramps




Figure 505.10.2
Top Handrail Extension at Stairs




Figure 505.10.3
Bottom Handrail Extension at Stairs

Note: X = Tread Depth

Handrails & Grab Bar Spacing

11 SCALE: NOT TO SCALE




Figure 608.5.2
Standard Roll-In Type Shower Compartment Control Location





Figure 608.5.3
Alternate Roll-In Type Shower Compartment Control Location


Toe Clearance At Water Closet

12 SCALE: NOT TO SCALE




Clearance & Heights for Bathtubs

13 SCALE: NOT TO SCALE



Section 602.1 & 602.7
Clearance for Drinking Fountain



Mounting Heights

16 SCALE: NOT TO SCALE

Sink Protrusion & Clearance


15 SCALE: NOT TO SCALE

Mounting Heights

15 SCALE: NOT TO SCALE

Control Location at Roll-In Shower

14 SCALE: NOT TO SCALE



Mounting Heights


16 SCALE: NOT TO SCALE

Sink Protrusion & Clearance

15 SCALE: NOT TO SCALE

Mounting Heights


15 SCALE: NOT TO SCALE



Screw Through Gypsum Board into Molding at all Main & Cross Tee's (complete perimeter)

Gypsum Board Ceiling Panel

Fire Expansion Notch _____




1. Perimeter Vertical Hanger Support Wire, 8" Max. from Wall.
2. Horizontal Restraint (Splay Wires or Rigid Bracing) Within 2" of Intersection and Splayed 90° Apart at 45° Angles.
3. Compression Posts (Struts) 12ft. OC in Both Directions, Starting 6 ft. from Walls.
4. Supplementary Light Fixture Attachment.
5. Seismic Separation Joint.

1 SCALE: Not to Scale


Attach Cross-Tee of Suspension System to 2" Wall Molding (on Two Adjacent Walls) with Pop Rivets or Screws

At Opposite End, Cross-Tee Shall Have 3/4" Clearance From the Wall to the End of the Tee, Rest Upon the 2" Angle Wall Molding and be Free to Slide.



Light Fixtures Must be Positively Attached to the Ceiling Grid With an Attachment Capable of Carrying 100% of the Weight of the Light Fixtures. Light Fixture Weight up to 56 Pounds Shall Require Two Vertical Support Wires; These Wires be Slack.

Air Terminals Weighing Less than 20 Pounds Shall be Positively Attached to the Ceiling Grid. Air Terminals Weighing 20 Pounds but not More than 56 Pounds, Shall be Secured to the Building Structure (Above the Ceiling), in Addition to Being Attached to the Ceiling Grid. These Wires may be Slack. Air Terminal Weighing More than 56 pounds Shall Require Independent Support from the Building Structure, (Above the Ceiling).



3 SCALE: Not to Scale

4 SCALE: Not to Scale



© 2024 KLINGNER & ASSOCIATES P.C.
This document shall not be used for any purpose or project for which it is not intended. Klingner & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims, damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this document. In addition, unauthorized reproduction of this document, in part or as a whole, is

REVISION HISTORY			
MARK	DESCRIPTION	DATE	APP
1	Addendum #4	02/05/25	-

ISSUED FOR
Bidding



PEMISCOT COUNTY PORT AUTHORITY
OFFICE BUILDING BUILT OUT

PEMISCOT COUNTY PORT AUTHORITY
111 EAST 3RD STREET
CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"
Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.

DESIGNED Designer	DRAWN Author
FIELD	FIELD BOOK

CHECKED Checker	CHECK DATE
--------------------	------------


SHEET TITLE

Ceiling Details

PROJECT NO.	24-7022
-------------	---------

DRAWING ISSUED DATE:
12-05-24
SHEET

G203



Floor Plan

SCALE: 3/16" = 1'-0"

Floor Plan Keyed Notes:

Applies To Floor Plan

- Demo wall as required for new window opening (3'x4' - see window sch'd). Provide new Mtl. Stud Framing, Flashing/Mtl. Trim, and Gyp. Board returns (interior side). Coordinate Rough-opening size with window manufacture.
- Demo existing door and wall as required for new double door. Provide new Mtl. Stud Framing, Flashing/Mtl. Trim, and Gyp. Board returns (interior side). Coordinate Rough-opening size with door manufacture.
- Ower shall patch concrete slab As Required.
- Semi-Recessed Fire Extinguisher Cabinet by Uline Mode No. H-5800 (11" x 6" x 24")
- Base [VB-1]: By Owner
- Floor: Owner shall patch, grind, clean, and prep and install new flooring.
- Ceiling: Lay-In Ceiling Tile By Armstrong: Series: FINE FISSURED; Item #: 1728 With HUMIGUARD Plus and BIOBLOCK; Style: 24"x24" Square Edge; Grid: 15/16" Wide; Color: White (WH).
- Wall Paint [PT-1]: Paint By Benjamin Moore; Collection: Off White Collection; Finish: Flat; Color: Submit Samples for Owners Approval
- Wall Paint [PT-2]: Paint By Benjamin Moore; Collection: Off White Collection; Finish: Semi-Gloss; Color: Submit Samples for Owners Approval
- Existing door to remain.
- Install new Aluminum Window by Kawneer (Model: 451T TriFab VersaGlaze with Sill Receiver; Glazing: 1" Insulated Center Glazing (Low-E) & 1/4" Interior).

- Existing X-Bracing.
- Water Heater - Re: MEP Sheets
- Utility Sink - Re: MEP Sheets

- Restroom Partition: Floor-Mounted With Headrail Brace By Hadrian Or Approved Equal, Material: Phenolic Core. Owner Shall Select And Approve Color From Manufacturer Standard Colors. Manufacturer Shall Provide All Installation Hardware And Door Hardware.

- Urinal Screen: Wall Mounted By Hadrian Or Approved Equal (1" Thick x 18" Deep x 48" High) Material: Phenolic, Install 12" AFF. Owner Shall Select And Approve Color From Manufacturer Standard Colors. Manufacturer Shall Provide All Installation Hardware.

Floor Plan General Notes:


Applies To Floor Plan

- All dimensions are to wall finish unless noted otherwise.
- All walls to be primed and painted unless noted otherwise. Paint floor to ceiling and corner to corner. One (1) coat of primer and two (2) coats of paint. Owner will select one field color and three accent colors for the walls.
- All hollow metal doors and frames to be painted - two coats. Prior to painting spot prime any factory scratches.
- Extend Gypsum Board 6" Above Lay-In Ceiling.
- Provide 5/8" gypsum board on walls, mud/tape (level 4), prime & paint.
- Provide moisture resistant gypsum board at locations that my be exposed to moisture, including but not limited to MEP rooms, behind break room cabinets, and restrooms.
- Provide concrete pad for all ground mounted equipment (ie. Main Switch, transformer, condensing unit, generators, etc.) Coordinate w/ MEP & Structural Sheets.
- Coordinate all equipment (electrical panels, air compressors, main switch, transformer, etc) and locations with MEP sheets.
- Coordinate all work with MEP, Structural, and Civil drawings.
- Floor: Owner shall grind, Clean, Patch and Prep all concrete floors (excluding Shop 114) for a smooth and level finish and stained with a concrete stain.
- All electrical panel locations shall be coordinated with MEP Drawings. Provide 3/4" Fire-treated Plywood or Unistrut as required for new electrical panels & equipment.
- All existing underslab rough-in have been completed prior to the project and new wall must be coordinated with existing plumbing. Minor adjustment may be required and the contractor shall verify any adjustments meet ADA guidelines.

© 2024 KLINGNER & ASSOCIATES P.C.
This document shall not be used for any purpose or project for which it is not intended. Klingner & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims, damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this document. In addition, unauthorized reproduction of this document, in part or as a whole, is prohibited.

NO.	DESCRIPTION	DATE	APPR.
1	Addendum #4	02/05/25	

ISSUED FOR	Bidding
------------	---------



PEMISCOT COUNTY PORT AUTHORITY
OFFICE BUILDING BUILT OUT
PEMISCOT COUNTY PORT AUTHORITY
111 EAST 3RD STREET
CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"

Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.

DESIGNED	DRAWN
Klingner	CLH
FIELD	FIELD BOOK

CHECKED	CHECK DATE
---	---

SHEET TITLE
Floor Plan


PROJECT NO.
24-7022

DRAWING ISSUED DATE:
12-05-24

SHEET


A101





Door Schedule General Notes

- A. All Hollow Metal (HM) Doors And Frames Shall Be Welded At Frame Seams, Galvalume, Factory Primed, And Factory Prepped To Receive Specified Hardware.
B. Contractor To Verify All Wall Thicknesses Prior To Ordering Frames
C. Doors Shall Be A Min. 18 Gauge And Frames Shall Be A Min. 16 Gauge.
D. All Hollow Metal Doors - Spot Prime Scratches Prior To Painting.
E. Refer To Specs For All Door Hardware




Alum. Door Schedule

1 SCALE: 1/2" = 1'-0"

Hollow Metal Door Schedule

2 SCALE: 1/2" = 1'-0"




WINDOW GENERAL NOTE:

- Aluminum Windows Shall be Kawneer 451 (w/Sill Receiver) or Approved Equal
- All aluminum windows shall have center glazing.

Aluminum Window Legend

3 SCALE: 1/2" = 1'-0"



Microwave Cabinet


8 SCALE: 1" = 1'-0"

Base & Wall Cabinets

7 SCALE: 1" = 1'-0"

Kitchenette

6 SCALE: 1/2" = 1'-0"




Kitchen/Breakroom 102

Restroom Hardware

- T.P.H. Toilet Paper Holder
W.M. Wall Mounted Mirror
G.B. Grab Bar With Size Noted Elevations

NOTE:

- Provide Wall Blocking For All Accessories.
- Owner To Provide And Install TPH, Paper Towel Holder, and Soap Dispenser



Restroom

5 SCALE: 1/2" = 1'-0"


Restroom

4 SCALE: 1/2" = 1'-0"

WALL SCHEDULE


TYPE	SECTION	DESCRIPTION
1		A. Metal Stud: 3 5/8" Non-Structural Metal Studs (Re: Section 09 22 16) Spaced At 16" O.C. From Top Of Slab To 6" Above Finish Ceiling. Support To Structure As Required. B. Gypsum Board * : 5/8" Gypsum Wall Board, Extend Each Side Of Gypsum Board To 6" Min. Above Ceiling. C. Ceiling Height - Re: Reflective Ceiling Plan D. Insulation: Sound Attenuating Insulation Between Studs At Restrooms And Offices. <div>* Indicated Gypsum Board One Side Only</div>
2		A. Metal Stud: 6" Non-Structural Metal Studs (Re: Section 09 22 16) Spaced At 16" O.C. From Top Of Slab To 6" Above Finish Ceiling. Support To Structure As Required. B. Gypsum Board * : 5/8" Gypsum Wall Board, Extend Each Side Of Gypsum Board To 6" Min. Above Ceiling. C. Ceiling Height - Re: Reflective Ceiling Plan D. Insulation: Sound Attenuating Insulation Between Studs At Restrooms And Offices. <div>* Indicated Gypsum Board One Side Only</div>
3		A. Metal Stud: 3 5/8" Structural Metal Studs (Re: Section 05 40 00) Spaced At 16" O.C. From Top Of Slab To Mezzanine. B. Gypsum Board * : 5/8" Gypsum Wall Board, Extend Each Side Of Gypsum Board To 6" Min. Above Ceiling. C. Ceiling Height - Re: Reflective Ceiling Plan D. Insulation: Sound Attenuating Insulation Between Studs At Restrooms And Offices. <div>* Indicated Gypsum Board One Side Only</div>
4		A. Metal Stud: 3 5/8" Structural Metal Studs (Re: Section 05 40 00) Spaced At 16" O.C. From Top Of Slab To Mezzanine. B. Gypsum Board * : (3) Layer of 5/8" Gypsum Wall Board - Each Side. C. Ceiling Height - Re: Reflective Ceiling Plan D. Insulation: Sound Attenuating Insulation Between Studs At Restrooms And Offices. <div>3 Hour Rating UL # U419</div>

Typical



ISSUED FOR

Bidding



PEMISCOT COUNTY PORT AUTHORITY
OFFICE BUILDING BUILT OUT

PEMISCOT COUNTY PORT AUTHORITY
111 EAST 3RD STREET
CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"

Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.

DESIGNED: Designer
DRAWN: Author

CHECKED: Checker
FIELD BOOK

SHEET TITLE

Wall, Door & Window
Schedule, Interior
Elevations

PROJECT NO.


24-7022

DRAWING ISSUED DATE:

12-05-24


SHEET

A102




Building Section

1 SCALE: 1/4" = 1'-0"



Wall Section


3 SCALE: 1/2" = 1'-0"




Wall Section

2 SCALE: 1/2" = 1'-0"

Finish Symbols



Key




Note: See MEP Sheets For Notes, Details, & Schedules

General Notes:

Applies To Reflective Ceiling Plan

- A. Heights are from top of floor to underside of the finished ceiling.
- B. Coordinate Architectural and MEP sheets for appropriate fixture arrangements & ductwork sizing.
- C. Mechanical Equipment - Re: MEP Sheets
- D. Ceiling Finish - Re: Room Finish Schedule



Reflective Ceiling Plan

1 SCALE: 3/16" = 1'-0"

© 2024 KLINGNER & ASSOCIATES P.C.
This document shall not be used for any purpose or project for which it is not intended. Klingner & Associates P.C. and their Divisions shall be indemnified by the client and held harmless from all claims, damages, liabilities, losses and expenses, including attorneys fees and costs arising out of such misuse or reuse of this document. In addition, unauthorized reproduction of this document, in part or as a whole, is prohibited.

REVISION HISTORY			
NO.	DESCRIPTION	DATE	APPR.
1	Addendum #4	02/05/25	

ISSUED FOR
Bidding



PEMISCOT COUNTY PORT AUTHORITY
OFFICE BUILDING BUILT OUT

PEMISCOT COUNTY PORT AUTHORITY
111 EAST 3RD STREET
CARUTHERSVILLE, MO 63830

Non-Reduced Sheet Size: 24" x 36"
Full sized plans have been prepared using standard scales. Reduced size plans may not conform to standard scales.

DESIGNED Klingner	DRAWN CLH, MG
FIELD	FIELD BOOK

CHECKED ---	CHECK DATE ---
----------------	-------------------

SHEET TITLE
Reflective Ceiling Plan

PROJECT NO.
24-7022
DRAWING ISSUED DATE:
12-05-24

SHEET
A801



KLINGNER & ASSOCIATES, P.C.
Engineers • Architects • Surveyors
www.klingner.com
Carbondale, Illinois
2150 West Main St.
Burlington, IL 61810
618.331.4050

Quincy, IL, Hannibal, MO
St. Louis, MO
Columbia, MO, Davenport, IA