

GRAFFITI REMOVER MGS 05-01

1.0 DESCRIPTION. This specification covers a commercial grade liquid graffiti remover for use on porous concrete or smooth metal surfaces.

2.0 GENERAL.

2.1 The liquid graffiti remover shall be a non-drip formula that will cling to vertical surfaces without runs or drips.

2.2 The liquid graffiti remover shall be applied by brush, roller, or sprayer (High Velocity Low Pressure).

2.3 The liquid graffiti remover shall be nonflammable, noncombustible, and of a minimal fire hazard formulary.

2.4 The required set time shall not be longer than one hour and the graffiti remover shall be removable with water, with an applied pressure less than 3,000 psi.

2.5 The liquid graffiti remover shall not damage glass, metal, masonry, wood, or resinous materials.

2.6 The shelf life of the liquid graffiti remover shall be at least one year.

2.7 The liquid graffiti remover shall be effective in temperatures as low as 40° F.

2.8 The liquid graffiti remover shall not require dilution for use.

2.9 There shall be no shadowing after the graffiti has been removed.

3.0 LABELING.

3.1 The containers for the graffiti remover shall have affixed a label indicating the company and product name and any pertinent handling instructions.

4.0 RESTRICTION FROM FUTURE PURCHASE. If, through the course of field use, it is determined that the product does not perform satisfactorily, or does not comply with any part of this specification, no subsequent purchase of the product will be allowed. A listing of products Restricted From Future Purchase will be maintained in the [Materials Manual FS2090 Table1](#).