Effective: Mar. 2021 Supersedes: Aug. STANDARD DRAWING GUIDANCE (SDG) (do not show on plans)

2020

RHB04_quidance



PART PLAN OF SLAB SHOWING SPECIAL REPAIR ZONES

before requesting PDFs for sign and seal.



Note: This drawing is not to scale. Follow dimensions.

*	TWP	*	F	RGE	*							
]						ć
Match												4
exist.	barr	ier	٦									i v
		~										>
_							DAT	E PR	EPAR	RED		_
Removal Existin	of g		Å.				9/	8/	20	21	TF	- LOOL
(Before	hydr hydr	0					*	- T	61	M	<u>)</u>	
	XXX	<u></u>	· · · · · · · · · · · · · · · · · · ·				BR		31	1	NU	
/			<	Clea & Ep	ning oxy			*	4 I I			۵ ۱
hic	< >	<' - X "		toat (F	ing D			JOB *	ND.			H L
	K−−L a	imits nd Ep	s of Cl	lean batir	ing		CON	ITRA	СТ	ID.		F L
Ŭ							PR	OJEC	T N	10.		, U
							BF R	RTDGI RHB	е N 04	о. а		1
ies												
216-1	0.00	sq.	, yard	Тс	x x	z						
216-1	0.01	sq.	yard		X	IPT10						-
505-0	0.04	cu.	yard		X	SCRI						L U
505-20 704-0	0.00 1.01	sq. sq.	, yard , foot		X	B						Ļ
704-0	1.02	sq.	foot		X X							
704-0	1.04	sq.	foot		X							
704-0	1.06	inear	- foot		XX	ATE						
704-0	1.13	sq.	foot		X	â						
						NOI				I TOL	5102	1900
						RAT				САР	40 02 12	9-67
ic deck re	epair	will	be pa	id f	or	SPOF				WEST		7-00
						RAN				105		
							NU I ON				ERSO	
						AN S		⊢			JEFFI	
		Year				WAY 900		0		Ν		0 4 - 0
em Axle ()					I GH		Ď			, ,	201
f'c = 4	,000	psi				H I Z		₫	1	Į.	5	
						SOUF		Σ				
ch new bri	dge v	vearin	ng sur	face		MIS	arepsilon	_		-	J	
c 704, unl	ess c	other	wise n	oted	•							
ed lines.	Heavy	/ line	es ind	icat	е							
ore orderi	ng ne	ew ma	terial	•								
of wearing	, surf	ace	as sho	wn o	ņ							
nishing ar ed in the	nd ins contr	sur te stall fact i	ing th	e rice	·							
ent for vo	riati	ons	in thi	ckne	SS							
						1						
to be mai and Sheet	ntair No.	ned or for	nd rstag	urin ed	g							
ROUTE >	₭											
(Match Ex	istin	ig)										

IRO4 CIE



es:							ATED.
ск [©] ".							D DN
identify sound and unsound							LED A
- ir zones, complete the							/ SEA
sting deck repair							ALLY
ir th void tube replacement		DAT	E PR	EPAR	ED		DNIC.
air	R		<u>ہ</u>	20.	Z I STATE		CTR
arr zones, remove existing	DIS		т	SH	MU eet n	0.	ELE
ace hydro demolition, removing nd concrete inside special repair "minimum of sound concrete d concrete outside special repair		3R		NTY (NO.	2		T HAS BEEN
eeded complete incidental		CON	ITRA	сті	D.		ETI
air zones, complete the		PR	OJEC	CT N	0.		SHE
th void tube replacement		BF R		е NC 041). C		THIS
urface including additional							TON
of monolithic deck repair.							ESEN
the areas designated as	z						S PRI
all be completed before hydro ical sequence beginning with same letter designation may be	RIPTIO						EAL IS
ime. Hydro demolition shall not repairs in all special repair d properly cured.	DESCI						IF A S
as not designated as a special ompleted after hydro demolition.							
r shall be completed in one d concrete shall have attained a f 3200 psi before work can be ecial repair zone.	DATE						
rea does not exceed 4 square otal repair area within a es not exceed 12 square feet, e may be repaired at the same ne.	RTATION				T CAPITOL MO 65102	275-6636)	
o the void tube as a result of tions shall be patched or y the engineer at the	ID TRANSPO				105 WES	DDT (1-888-:	
deck shall be patched as er in a manner that shall completely free of concrete. bosed void will be considered the contract unit price for e special repair zones and outside special repair zones.	HIGHWAYS AN				JEFF	1 - 888 - ASK - MOI	
rtion of the void tube is beyond as determined by the engineer, eriorated void tube shall be a shall be maintained completely ing of the longitudinal not be permitted. The fiber e voids shall have an outside thickness the same as the	MISSOURI		Σ				
of replacing the void tube will ly covered by the contract unit with Void Tube Replacement. rizontal projection of the area							
epair is not required.							



	SEC/SUR	*	TWP	*	RGE	E *			
SPANS							1		
	Mat	tch exis	t. barr	ier	ı				
Removal of <u>Concre</u>	te	Removo Existi	il of na					date pref 9/8/2	021
and Total Surface Hydro Demolition-	-	Deck F (Befor	Repair ™e hydr	0	1				state MO
<u></u>	<u> </u>	demoli <u>-/-/-/-</u> /-	tion)-	7		r	וס ר	ISTRICT BR	SHEET NO. 1
					<c∣< td=""><td>eaning</td><td></td><td>COUNT *</td><td>Y</td></c∣<>	eaning		COUNT *	Y
JII Depth	lonolithi	•		′ –X ″		ating		JOB N	0.
epair l	еск кера	ir —	È-Li	imi†s	of Clea	pning		CONTRACT	ID.
. REPAIR ZONES LITION REPAIRS)			ar	nd Epc	ху Соа-	ting —	J	PROJECT	NO.
								BRIDGE	NO.
Ectimated 0		inc							40
Item	uunnn	162				Total			
molition		216-	10.01	sq.	yard foot	X			
ck Repair		216-	15.02	sq.	foot	X	NO I		
Surface Material		505-	00.04	cu.	yard	X	RIPT		
ormed)		704-	01.01	sq.	foot	X	ESCI		
nformed) (Unformed)		704-704-	01.02 01.03	sq. sa.	foot foot	X X			
		704-	01.04	sq.	foot	X			
ges)		704-704-	01.06 01.07	sq. inear	+00+ foot	X			
ting		704-	01.13	sq.	foot	Х	ATE		
							à		
							NO I		I TOL 5102 536)
surface material for	monolithi	'c deck r	repair	will	be paid	for	RAT		CAP 40 6: 75-6
e in accordance with	Sec 109.						SPOF		ИЕ S T T Y • I B B - 2
							RAN		105 V V CI (1-8)
							D		ERSO
Ed.) Standard Specifi	cations						AN		JEFF <-MO(
-Year			ر <u> </u>	'ear			VΑΥS		-ASP
) and Military 24,000	lb Tande	em Axle ()				I CHV	Ň	-888
If-Solo and Eull Dont	b Popair'	f'o -	- 1 000				н	7	1
	ц керан ,		- 4,000	psi			OUR	Σ(
cent to bridge ends s	hall matc	ch new br	idge w	earin	g surfa	се	AI SS		
nall be in accordance	with Sec	: 704, ur	nless o	therw	ise not	ed.	2	-	
rk is indicated by li	ght dashe	ed lines.	Heavy	line	s indic	ate			
all dimensions in f	ield befo	re order	ing ne	w mat	erial				
rade and a minimum th	ickness c	of wear in	ng ne	ace a	s shown	on			
ary to use additional ne structure. The cos	quantiti t of furr	es of we	aring and ins	surfa talli	ce at v na the	arious			
e considered complete al labor, materials c	ly covere r equipme	ed in the ent for N	e contr variati	act ui ons ii	nit pri n thick	ce, ness			
during construction.	Iraffic	to be ma	<u>intain</u>	ed on	dur	ing			
way piùna for fruttic	CONTROL_	<u>unu snee</u>	5 I INU.	ror_	_sruged	_			
REPAIRS TO BR	[DGE: F	ROUTE	*						
OVER *									
ROUTE * FROM * TO *									
BEGINNING STATION	±	(Match E	xistin	g)					



Note: This drawing is not to scale. Follow dimensions. Sheet No.

Checked





*	ΤWΡ	*	F	€GE	*						
		_									
Removal d	barr of	er	\mathbf{r}				DATE	PREPA	ARED		
Existing Deck Repo	ir		N			R		5/20	JZI STA	TE	-
demolitic	nyaro on) –	7 .	/			015 T		s	IVI HEET	NO.	
			· · · · · · · · · · · · · · · · · · ·	Clear	ning		<u>с</u>	OUNTI	(-
	// <u>, , /</u>	· · · · · · · · · · · · · · · · · · ·];	& Epi Coat	oxy ing	-	J	* DB NO			-
Sole	< _ ∟	imits	لح of CI	(H ean i) ina		CONT	RACT	ID.		-
	' ai	nd Epo	сху Сс	batir	ng		PRO	JECT	N0.		-
							BRI	DGE N	10.		-
							T T	IB04	1e		-
ies				To							
216-10	0.00	sq.	yard		Х						
216-10	0.01 5.03	sq. sq.	yard foot		X	TION					
505-00	0.04	cu.	yard		X	CRIP					
704-01	.01	sq.	foot		X	DES					
704-01	· 02	sq. sq.	+00+ foot		X						
704-01	• 04	sq.	foot		X						
704-01	.071	inear	foot		X			-		+	-
704-01	1.12 1.13	sq. sq.	+00+ foot		X X	DATE					
						z			Ы	53	
						ATI			APITI	651	-663-
ic deck re	Dair	will	be pa	id f	or	ORT			STC	OM .	G / Z -
						ANSF			5 WE	CITY	888-
						T R			10	SON	
						AND		_		FFER	nuum
	<u> </u>	rear				Y S MMI				۳.	- ASK -
em Axle (CHW/		2))		- 888-
and						Ξ H			₩	ב'	÷
icement)	f′c	= 4,0	00 ps	i		JUR I		<u>,</u>			
ch new bri	dge w	vearin	g sur	face		ISSC		- \	<u> </u>	J	
204 404		thory	teo p	otod		Σ					_
ed lines.	ess c Heavy	line 'line	s ind	icat	• e						
ore orderi	ng ne	w mat		•	~						
ies of wea ishina an	sur⊤ ring d ins	surfa surfa	ce at	wn o var e	ious						
ed in the ent for va	contr riati	act u ons i	nit pi n thi	rice ckne	, ss						
to be mai	ntair	ied on	d	urin	g						
<u>unu sheet</u>	<u>INU.</u>	TUP	_ பழ	24							
ROUTE ¥	÷										
(Match Ex	istin	g)				1					

RHB04_CIP_VS_or_SS_Slab.dgn



Checked

tes:					ATFD.
eck D ".					ND D
identify sound and unsound					FD A
 jir zones, complete the					Y SFA
sting deck repair					ALL.
th void tube replacement		DATE 9/8	PREPAR	ed 21	SON I C
pair zones, remove existing	RO	UTE	5	state MO	FCT
ace bydro demolition, removing		RICT	SHE	2 ET NO.	LL Z LL
Ind concrete inside special repair minimum of sound concrete ad concrete outside special repair (E)		J 06	UNTY * 3 NO.		T HAS BF
needed complete incidental		CONTR	ACT I	D.	
pair zones, complete the		PROJI	ECT NO).	SHF
air <u>th void tube replacement</u> pair		BRID RHI	GE NC BO4-	f	DN THI
urface including additional of monolithic deck repair.					RESENT
n the greas designated as	I ON				LS L
shall be completed before hydro	RIPT				E AI
 same letter designation may be ime. Hydro demolition shall not e repairs in all special repair nd properly cured. 	DESC				IF A
eas not designated as a special completed after hydro demolition.					
r shall be completed in one nd concrete shall have attained a 5 3200 psi before work can be pecial repair zone.	DATE				
area does not exceed 4 square otal repair area within a pes not exceed 12 square feet, e may be repaired at the same one.	SPORTATION			WEST CAPITOL TY. MO 65102	0000-017-00
to the void tube as a result of tions shall be patched or by the engineer at the	AND TRAN SSION		_	105 FFERSON CI	
e deck shall be patched as per in a manner that shall a completely free of concrete. posed void will be considered the contract unit price for	H I GHWAYS COMM I				
prtion of the void tube is beyond as determined by the engineer, eriorated void tube shall be a shall be maintained completely ing of the longitudinal not be permitted. The fiber he voids shall have an outside thickness the same as the chored at not more than the of replacing the void tube will ely covered by the contract unit with Void Tube Replacement. or izontal projection of the area an.	MISSOUR	Σ			
epair is not required.					



*	twp *	F	RGE 米					
		→						
tch exi	st. barrier							
Remov	val of					DATE PI	REPARED	
Deck (Befo	Repair pre hydro				RO	UTE	sta M	ITE O
demol		 21 - Fi			DIS E	RICT	SHEET 1	NO.
		· · · · · · · · · · · · · · · · · · ·	Cleaning & Epoxy	Ĵ		cou Ə	NTY (
-Sole	X'->	<"	Coating			J0B →	ND. €	
	← Limi and	ts of CI Epoxy Co	leaning pating —]		CONTRA	CT ID.	
						PROJE	CT NO.	
						RHE	04g	
ies								
216	5-10.01 s	sq. yard	Total X					
216	5-15.02 s	q. foot	X		NO I			
505	-00.04 c	sy. 1001 su. yard	X		RIPT			
704	-20.00 s	sq. yara sq. foot	X		DESC			
704 704	-01.02 ड -01.03 ड	sq. foot sq. foot	X X					
704 704	-01.04 s	sq. foot sq. foot	X X	_				
704	-01.07 line	ar foot	X		μ			
704	-01.13 s	sq. foot	X		DAT			
					I ON		TOL	102
					RAT		CAPI	AD 65 75-66
ic deck	repair wi	II be pa	id for		SPOF		WEST	ТҮ. N 88-27
					IRAN V		105	N CI (1-8
					ND S I ON			-ERSC DDDT
	— Yea	r			YS A MMIS	F		JEFF SK-M
em Axle					HWA' COI	Q		388-A
and					НIG	Ď	₩	۲ <u>۳</u>
acement) $f' c = 4$	1,000 ps	i		UR I	5	K	Γ
ch new l	oridge wear	ing sur	face		ISSC		~	J
- 704 · I	inless othe	erwise n	oted.		Σ			
ed line:	s. Heavy l'	ines ind	icate					
ore orde	erina new r	material						
of wear	ing surface	e as sho	wn on					
ies of v nishing ed in th	wearing sur and insta	face at lling th	various e rice.	5				
ent for	variations	s in thi	ckness					
to b -	maintaint d		uring					
and She	eet No.	for stag	ed_					
RUITE	· ¥							
NUUTE	· •							
(Match	Existing)							

RHB04_CIP_VS_or_SS_Slab.dgn





Detailed Checked

Sheet No. 1 of

ABOUT * MILES * UF * BEGINNING STATION _____±

HR04 CIE

*	TWP *	R	GE 米						
						DATE P	REPAR	ED	
Mata	ch st. barrier					9/8/	20	21	
					RU A	₭		MO	-
- K - T - J				1	DIS'	RICT BR	SH	_{ЕЕТ 1}	10.
<u>.</u>			Epoxy Contina			COL ;	inty K		
	< X'-X"	``	H			JOB	NO.		
	-Limits and Epo	of Cl xy Cc	eaning ating —			CONTR	ACT :	۱D.	
	· · · ·	<u> </u>	5			PROJE	CT N	0.	
						BRID	GE NO).	
						RHE	304	i	_
· i a c									
163			Total	_	z				
21	6-10.00 sq.	yard	X		ΡTIC				
50 70	<u>4-01.01</u> sq.	yara foot	× ×	_	CRI				
70	4-01.02 sq.	foot	Х		DES				
70	$\frac{4-01.03}{4-01.04}$ sq.	foot	X X	_					
70	4-01.06 sq.	foot	X						
70	4-01.07 linear	foot	Х						
70	<u>4-01.12 sq.</u> 4-01.13 sq.	+00+ foot	× ×	_	Ш				
		1001	~		DAT				
					z				1
					TIC			0 T T C	6636
					RTA			CAF	75-(
					RANSPO			05 WEST	1-888-2
					AND T ISSION	L			-MODOT
em Axle	Year				GHWAYS COMM	Q			-888-ASK
_and acement	f'c = 4.00)0 ps	ī		IH INU	20			ר'
ch new	bridge wearing	j sur-	face		MISSO			•	
c 704, ed line	unless otherwi es. Heavy lines	ise no s ind	oted. icate						
ore ord	tering new mate	erial							
of wear	rina surface as	s show	wn on						
ies of nishing ed in t ent for	wearing surfact and installing the contract un variations in	ce at ng the nit pr n thio	various e fice, ckness	6					
to be and Sh	maintained on heet No. for	dı dı	uring_ ed_						
ROUTE	E *								
(Match	Existing)								





+ ~ ~ •	
ptes: deck	DATE PREPARED 9/8/2021 ROUTE STATE # MO DISTRICT SHEET NO. BR 2 COUNTY * JOB NO. * CONTRACT ID. PROJECT NO. BRIDGE NO.
tir shall be completed in one and concrete shall have attained a of 3200 psi before work can be special repair zone. area does not exceed 4 square total repair area within a loes not exceed 12 square feet, one may be repaired at the same cone.	RHB04 j
by the engineer at the ne deck shall be patched as her in a manner that shall be completely free of concrete. exposed void will be considered of the contract unit price for portion of the void tube is beyond g as determined by the engineer. theriorated void tube shall be rea shall be maintained completely ting of the longitudinal I not be permitted. The fiber ne voids shall have an outside I thickness the same as the chored at not more than the set of replacing the void tube will rely covered by the contract unit with Void Tube Replacement. norizontal projection of the area an.	MISSOURI HIGHWAYS AND TRANSPORTATION DATE COMMISSION Intervention COMMISSION COMMISSION COMMISSION Intervention COMMISSION COMUNICATION COMUNI
BAWS, epoxy polymer, or MMA polymer (1) and renumber others ne inal depth dimension to bottom of thickness for thin wearing ete crack filler: (1) and (3) and renumber others ne & the wearing surface inal depth dimension to the ce" with "Concrete Crack der note to point to the	



Detailed Checked

Sheet No. 1 of

*	TWP *	R	GE 米					
	>							
Matc	h t. barrier					date pr 9/8/	epared 2021	
0,10					ROL	JTE €	stat MC))
- <u></u>	<u>, , , , , , , , , , , , , , , , , , , </u>	· [(leanin		DIST B	RICT	SHEET 1	NO.
	· · · · · · · · · · · · · · · · · · ·		Epoxy Coating	g		ر ۲	NTY (
	X -X	 مf CI	(H)			јов *	ND.	
	and Epo	xy Co	ating -			CONTRA	CT ID.	
						PROJEC	CT NO.	
						BRIDG RHB	е NO. 04k	
ies								
100			Total		NO			
216 505	5-15.02 sq. 5-20.00 sq.	foot yard	X X	_	IPTI			
704	4-01.01 sq.	foot	X		ESCR			
704	4-01.03 sq.	foot	X		ā			
704	4-01.04 sq.	foot	X X	_				
704	4-01.07 linear	foot	X					
704	4-01.12 sq.	foot	X		ш			
10-	4 01 13 34	1001	~		DAT			
				_	z		ц. ц.	02 6)
					ATI(AP I TO	651(-663(
					ORT		L C	MD -275-
					NSP		WES	IТҮ. 888-
					TRA N		105	0N C
					ND S I O			-ERS
					S A MIS	⊢		JEFF SK-MO
em Axle	Year				НИАУ СОМ	0	\mathbf{i}	88-AS
					НІСІ	Q	₩	1-8.
_and icement) $f'c = 4,00$)0 psi	i		JUR I	5		L
ch new	bridge wearing) surt	face		MISSI			
704,	unless otherwi	se no	oted.					
ed line	s. Heavy lines	indi	icate					
ore ord	ering new mate	erial.						
of wear ies of nishing ed in t ent for	ing surface as wearing surfac and installir he contract ur variations ir	s show ce at ng the nit pr n thic	vn on variou Fice, Skness	S				
to be and Sh	maintained on eet No. for	dı stage	uring_ ed_					
ROUTE	E *							
(Match	Existing)							

HB04 CIP



- Delete existing lin
 Adjust top of the o to bottom of new we
- Adjust depth for the

DECK REPAIR DETAILS

Note: This drawing is not to scale. Follow dimensions. Sheet No. of

tes:	
aring surface[plus of]	
tify areas in need of repair. pair zones, complete the	
air ith void tube replacement pair	DATE PREPARED
air zones, complete the	9/8/2021 ROUTE STATE
air ith void tube replacement	TRICT SHEET NO. BR 2
surface.	
	JOB NO. *
eas not designated as a special completed prior to work in Zone A.	CONTRACT ID.
in the areas designated as shall be completed in beginning with Zone A. Zones designation may be repaired at	BRIDGE NO. RHBO4L
ir shall be completed in one nd concrete shall have attained a of 3200 psi before work can be pecial repair zone.	z
area does not exceed 4 square total repair area within a oes not exceed 12 square feet, ne may be repaired at the same one,	DESCRIPTIO
to the void tube as a result of ations shall be patched or by the engineer at the	
e deck shall be patched as eer in a manner that shall a completely free of concrete. xposed void will be considered the contract unit price for	ATION DATE APITOL 65102
ortion of the void tube is beyond as determined by the engineer. teriorated void tube shall be ea shall be maintained completely ting of the longitudinal I not be permitted. The fiber he voids shall have an outside I thickness the same as the chored at not more than the t of replacing the void tube will ely covered by the contract unit with Void Tube Replacement. orizontal projection of the area an.	IIGHWAYS AND TRANSPORT COMMISSION I COMMISSION I COMMISSION
repair is not required.	MISSOURI
t, UBAWS, epoxy polymer wearing surfaces: re inside wearing surface riginal depth dimension paring surface in wearing surfaces	

8/2021