



- NOTES:**
1. ALL SIGNS TO BE MOUNTED ON PERFORATED SQUARE STEEL TUBE POST - STANDARD DRAWING 903.03.
 2. SIGN HEIGHT TO BE 7' FROM BOTTOM OF SIGN TO EDGE OF PAVEMENT ELEVATION.
 3. FLEXIBLE DELINEATORS TO BE LOCATED AT RADIUS POINTS.
 4. REFLECTIVE MARKERS TO BE LOCATED ONE AT THE CENTER OF ISLAND NOSE. THEN 2' SPACING ON EITHER SIDE.
 5. DRAWING NOT TO SCALE. FOLLOW DIMENSIONS.

STANDARD DETAILS
 RIGHT IN/RIGHT OUT
 ISLAND
 (with a right turn lane)

<p>①</p> <p>R1-2 YIELD 48" x 48"</p>	<p>②</p> <p>R3-2 NO LEFT TURN 24" x 24"</p>	<p>③</p> <p>W12-1 DOUBLE ARROW 24" x 24"</p>
<p>④</p> <p>R4-7 KEEP RIGHT 24" x 30"</p>	<p>⑤</p> <p>18" FLEXIBLE DELINEATOR</p>	<p>⑥</p> <p>REFLECTIVE RAISED PAVEMENT MARKER (STIMSONITE MODEL 88)</p>