



## Chip Spreaders

### CSV816 Variable Width Chip Spreader



#### PERFORMANCE FEATURES INCLUDE:

- Variable Width Spread Hopper - 8' to 16' (2.44-4.88 m)
- No Permit Load - 8'6" (2.59 m) Maximum Transport Width
- 275 hp (205 kw) Cummins T4 Final Diesel Engine
- Hydrostatic Front Wheel Drive Propel System
- Reversible Cooling Fan for Cooling System Maintenance
- Application Rate Control
- 12" (30.48 cm) Abrasion Resistant Augers



Designed with the Paving Professional in Mind.®



# Features

## Operation

**Automatic Control:** The CSV816 computer maintains accurate application rate of aggregate regardless of changes in ground speed and allows the gates to vary infinitely. Operator has access to change the rate at any time, even while chipping. Gates automatically close when machine is stopped.



**Smooth Operation:** Hydrostatic drive ensures smooth starts and stops. Application rate computer monitors speed and varies the gate openings to maintain the set application rate.

**Operator Controls:** One full console on left side with right-hand remote operator control on right side of machine.



## Material Management

**Hopper Wings:** New contoured folding wings provide excellent clean-out ability. Improved clearance for truck when loading the receiving hopper. Large, 3.5 cubic yard receiving hopper.

**Complete Clean Out:** Wheel wells do not protrude into the hopper area. Material capacity and flow is optimized.

**Clean Operation:** Rubber side skirting runs the complete length of conveyor belts to prevent spillage of the aggregate.



## Reliability



**Reduced Maintenance:** Conveyor drive motors are on floating mounts for dependable, low maintenance performance.

## Options

- All-wheel Drive System
- Consult Dealer/Factory for Engine Options
- Dual Operator Consoles with Slides
- Pressure Transducers to Display (Hydraulic Pressures)
- Chip Spreader Telemetric System
- Remote Camera for Hitch
- Hopper Vibrators
- Tool & Storage Box
- Umbrella (qty 2)
- Extended Warranty Program

LeeBoy makes continuous improvements to all its products and reserves the right to change specifications without notice. Photos and illustrations may contain standard and optional equipment.

CSV816 Chip Spreader, IZ

# LeeBoy

VT LeeBoy, Inc.  
500 Lincoln County Pkwy. Ext.  
Lincolnton, NC 28092  
704.966.3300

www.**LeeBoy**.com



## Other Members of the LeeBoy Group of Products...



Maximizer 3 Distributor



Tru-Pac 915 Roller



Challenger 7 Broom

**Contact your LeeBoy dealer:**

"LeeBoy is dedicated to providing top quality parts and service support on every unit sold."



ST. LOUIS DIVISION HEADQUARTERS  
4670 CROSSROADS INDUSTRIAL DRIVE  
BRIDGETON, MO 63044  
314-291-1330/800-274-7230  
FAX 314-291-8050

September 21, 2016

Missouri Department of Transportation  
General Services Division  
830 MoDOT Drive  
Jefferson City, Missouri 65109

RE: Request Number 3-160922TV

Gentlemen:

We are pleased to submit the following quotation for your consideration in response to the above referenced request:

**ONE NEW ROSCO MODEL CSV816 VARIABLE WIDTH CHIP SPREADER** equipped as follows:

All hydrostatic chip spreaders are front wheel drive and equipped with Tier 4 Final engine; proportional hydraulic fan drive – new system to save horsepower, reduce noise and reverses for radiator cleanout; temperature controlled hydraulic oil cooler; infinitely variable speed hydrostatic drive system, 385/65R Duplex radial tires, 12" wide receiving hopper with folding wings at 4 cubic yard truck capacity, rubber skirting and feed control gates adjustable from deck, variable width spread hopper with individual gate control, automatic cut-offs for conveyor and augers when they are full, hydraulic driven spread roll and augers, hydraulically released and hydraulically adjustable height truck hitch, full left hand sliding driver's station with operator's control console that includes ignition switch, automatic conveyor control and application rate control, Plus 1 CAB-Bus control and onboard diagnostic system with DP 710TM Color Graphic Display – gauges include engine water temperature, engine oil pressure, tachometer, fuel gauge, voltmeter, hydraulic temperature, hour meter, speed and direction controls, engine throttle, spread hopper/conveyor controls, hitch release hitch height, conveyor on/off and horn; right hand remote operator control panel; handrail mounted LED light package (work lights, tail lights, stop and turn signals and safety strobe light); 8'6" legal hauling width without permits.

With the following additional features in lieu of standard where applicable:

All-wheel drive

Tool and storage box

**CASH SALE PRICE**

**\$254,730.00**

**ABOVE PRICING GOOD FOR 30 DAYS UNLESS OTHERWISE NOTED.**



Options

1. Vibrators for variable hoppers (1 for each side).	
<b>ADD-----</b>	<b>\$ 2,344.00</b>
5. Dual side operator station (power shift console seat assembly).	
<b>ADD-----</b>	<b>\$13,560.00</b>
9. Strobe lights (at all four corners of unit).	
<b>ADD-----</b>	<b>\$ 1,705.00</b>
10. Full length flashing.	
<b>ADD-----</b>	<b>\$ 4,260.00</b>
12. Umbrella (2).	
<b>ADD-----</b>	<b>\$ 426.00</b>
16. Telematics System.	
<b>ADD-----</b>	<b>\$ 4,900.00</b>
17. Pressure transducer to display hydraulic pressures.	
<b>ADD-----</b>	<b>\$ 1,610.00</b>

Exception to Specification

Fuel Tank – 50 gallons in lieu of 60 gallons.

Terms

To be arranged.

Delivery


From factory approximately 120 days after receipt of order, subject to prior sale.

State/Local Taxes not included and must be added if applicable.

Thank you for the opportunity to quote the Missouri Department of Transportation. If we may be of further assistance, please don't hesitate to call.

Yours very truly,

ROLAND MACHINERY COMPANY  
ST. LOUIS DIVISION

  
James M. Jesuit  
Vice President/General Manager

JMJ/kf

cc: Mr. Dan Christensen, Roland/Cape Girardeau