

BID FORM

**MAILING ADDRESS:**  
**MISSOURI DEPARTMENT OF TRANSPORTATION**  
**GENERAL SERVICES, P.O. BOX 270**  
**JEFFERSON CITY, MO 65102**

REQUEST NO.	3-170105TV
DATE	December 15, 2016

SEALED BIDS, SUBJECT TO THE ATTACHED CONDITIONS WILL  
BE RECEIVED AT THIS OFFICE UNTIL

**1:00 pm., Local Time, January 5, 2017**

AND THEN PUBLICLY OPENED AND READ FOR FURNISHING  
THE FOLLOWING EQUIPMENT.

**BIDS TO BE BASED F.O.B. MISSOURI DEPARTMENT OF  
TRANSPORTATION**

Submit net bid as cash discount stipulations will not be considered

**Various End User Delivery Locations**

DEFINITE DELIVERY DATE SHOULD BE SHOWN. THE BIDDER MUST SIGN AND RETURN BEFORE DATE AND TIME SET  
FOR OPENING.

**BUYER:** Tom Veasman  
**BUYER EMAIL:**  
tom.veasman@modot.mo.gov

**BUYER TELEPHONE:** 573-522-4404

**MEDIUM DUTY VEHICLES**

This Request For Bid seeks bids from qualified organizations to provide vehicles in accordance with the following pages. MoDOT will receive bids at the following mailing address: P.O. Box 270, Jefferson City, MO 65102-0270, or hand-delivered in a sealed envelope to the following **physical address: General Services Procurement at 830 MoDOT Drive, Jefferson City, MO 65109** until 1:00 p.m., January 5, 2017. Bid forms and information may be obtained by contacting Tom Veasman at 573-522-4404, [tom.veasman@modot.mo.gov](mailto:tom.veasman@modot.mo.gov), or electronically download them at:

<http://www.modot.org/business/surplus/Fleet%20Buyers%20Web%20Page/LightDutyTrucks.htm>

**Components of Agreement:** The Agreement between MHTC and the successful Bidder(s) shall consist of: the RFB and any written amendments thereto, the "Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions" that are attached to this RFB and the bid submitted by the Bidder in response to the RFB. However, MHTC reserves the right to clarify any relationship in writing and such written clarification shall govern in case of conflict with the applicable requirements stated in the RFB or the Bidder's bid. The Bidder is cautioned that its bid shall be subject to acceptance by MHTC without further clarification.

**Return sealed bids to the address shown at the top of this page to the attention of the buyer. Submission of bids to the above mailing address must go through MoDOT's mail room and will require additional time to arrive at 830 MoDOT Drive.**

(SEE ATTACHED FOR TERMS, CONDITIONS, AND INSTRUCTIONS)

*In compliance with the above Request For Bid, and subject to all conditions thereof, the undersigned bidder agrees to furnish and deliver any or all the items on which prices were bid within the timeframe specified herein, after receipt of formal purchase order.*

**Date:** \_\_\_\_\_  
**Telephone No.:** \_\_\_\_\_  
**Fax No.:** \_\_\_\_\_  
**Federal I.D. No.** \_\_\_\_\_  
**Email Address:** \_\_\_\_\_

**Firm Name:** \_\_\_\_\_  
**Address:** \_\_\_\_\_  
**By (Signature):** \_\_\_\_\_  
**Type/Print Name** \_\_\_\_\_

**Is your firm MBE certified?** ☐ Yes ☐ No

**Title:** \_\_\_\_\_  
**Is your firm WBE certified?** ☐ Yes ☐ No

## 1. INTRODUCTION AND GENERAL INFORMATION

### 1.1 Introduction:

- 1.1.1 This Request for Bid (RFB) seeks bids from qualified organizations to provide **Medium Duty Vehicles** to the Missouri Highways and Transportation Commission (MHTC), acting by and through its operating arm, the Missouri Department of Transportation (MoDOT). Each bid must be in a sealed envelope, be mailed or delivered by courier to the RFB Coordinator at the below listed address, on or before the date and time listed herein for receipt of bids/proposals. All questions regarding the RFB shall be submitted to the RFB Coordinator. **Bids must be returned to the office of the RFB Coordinator no later than 1:00 p.m. Local Time, January 5, 2017.**

#### **RFB COORDINATOR:**

**Tom Veasman, Senior General Services Specialist**

#### **MAILING ADDRESS:**

**Missouri Department of Transportation  
P. O. Box 270  
Jefferson City, MO 65102  
Attn: Tom Veasman**

#### **PHYSICAL ADDRESS:**

**Missouri Department of Transportation  
General Services Division  
830 MoDOT Drive  
Jefferson City, MO 65109**

Note that submission of bids to the above **mailing address** must go through MoDOT's mail room and will require additional time to arrive at 830 MoDOT Drive.

**PHONE: 573-522-4404**

**FAX: 573-526-6948**

### 1.2 General Information:

- 1.2.1 This document constitutes an invitation for competitive, sealed bids for the procurement of **Medium Duty Vehicles** as set forth herein.
- 1.2.2 Organization: This RFB is divided into the following parts:
- 1) Introduction and General Information
  - 2) Scope of Work
  - 3) Bid Submission
  - 4) Pricing Pages
  - 5) Vendor Information and Preference Certification Form
  - 6) Notice Of Cooperative Purchasing
  - 7) Terms and Conditions
  - 8) Pricing Entry Sheets (EXCEL Spreadsheet – Separate attachment)

## 2. SCOPE OF WORK

### 2.1 General Requirements:

- 2.1.1 The bidder shall provide **Medium Duty Vehicles** on an as needed, if needed basis for MoDOT, in accordance with the provisions and requirements stated herein.
- 2.1.2 The bidder shall provide all deliverables to the sole satisfaction of MoDOT.
- 2.1.3 MoDOT does not guarantee that any unit(s) will be ordered.
- 2.1.4 Unless otherwise specified herein, the bidder shall furnish all material, labor, facilities, equipment, and supplies necessary to provide the deliverables required herein.
- 2.1.5 MoDOT reserves the right to reject any or all bids, and to accept or reject any items thereon, and to waive technicalities. In case of error in the extension of prices in the bid, unit prices will govern.

**2.2 Required Specifications:** All vehicle bids must comply with the attached MoDOT Specifications, and any other provisions outlined in the solicitation documents. Any deviation from these specifications must be indicated for review, or else bid may be considered non-responsive.

### 2.3 Delivery Requirements:

- 2.3.1 The following delivery requirements shall apply:
  - a. Unless otherwise specified on the solicitation documents or purchase order, suppliers shall give at least 24 hours advance notice of each delivery. Delivery will only be received between the hours of 8:00 a.m. to 3:00 p.m., Monday through Friday. No vehicles will be received on Saturday, Sunday or state holidays.
  - b. The prices bid herein include the delivery cost of the unit. The bidder agrees to pay all transportation charges on the material as FOB - Destination. Freight costs must be included in the unit price bid and not listed as a separate line item.
  - c. Any demurrage is to be paid by the Contractor direct to the railroad or carrier.
- 2.3.2 The contractor shall deliver the products specified herein to the following MoDOT locations:
  - a. St. Joseph, Missouri 64502
  - b. Macon, Missouri 63552
  - c. Hannibal, Missouri 63401
  - d. Lee's Summit, Missouri 64064-8002
  - e. Jefferson City, Missouri 65102
  - f. Chesterfield, Missouri 63017-5712
  - g. Joplin, Missouri 64802
  - h. Springfield, Missouri 65801
  - i. Willow Springs, Missouri 65793
  - j. Sikeston, Missouri 63801
  - k. Other district locations as may be required

## **2.4 Invoicing and Payment Requirements:**

- 2.4.1 Contractor – A successful Bidder to whom a contract is awarded.
- 2.4.2 The contractor shall submit an itemized invoice to the applicable requesting address for the completion of deliverables, as specified herein.
- 2.4.3 Each invoice should be itemized in accordance with items listed on the purchase order. The statewide financial management system has been designed to capture certain receipt and payment information. Therefore, each invoice submitted must reference the purchase order number and must be itemized in accordance with items listed on the purchase order. Failure to comply with this requirement may delay processing of invoices for payment.
- 2.4.4 The contractor shall be paid in accordance with the prices stated on the pricing pages of this document after completion of deliverables specified herein and acceptance by MoDOT.
- 2.4.5 Other than the payment specified above, no other payments or reimbursements shall be made to the contractor for any reason whatsoever.
- 2.4.6 Unless otherwise provided for in the solicitation documents, payment for all equipment, supplies, and/or services required herein shall be made in arrears. MoDOT shall not make any advance deposits.
- 2.4.7 MoDOT assumes no obligation for equipment, supplies, and/or services shipped or provided in excess of the quantity ordered. Any unauthorized quantity is subject to MoDOT's rejection and shall be returned at the contractor's expense.
- 2.4.8 MoDOT reserves the right to purchase goods and services using the state-purchasing card.

## **2.5 Other Award Requirements:**

- 2.5.1 Date of Award – The date for which the Bid Tabulation is posted to the MoDOT public website.
- 2.5.2 Original Contract Period – The contract period shall commence from the date of award until the end of the 2017 model year.
- 2.5.3 Renewal Periods – MoDOT has the right, at its sole option and in its sole discretion, to extend the contract period for up to two (2) additional one-year periods, or any portion therein. If the option for renewal is exercised by MoDOT, the bidder shall agree to all terms and conditions of the RFB and all subsequent amendments.
- 2.5.4 Escalation Clause - In the event the contractor requests a price increase during the original contract period or any contract renewal period, the contractor must provide a written request and documentation justifying the need for a price increase, and the amount of such price increase. MoDOT will review the contractor's written request and documentation, and decide if a price increase is to be granted at that particular time. The contractor shall understand and agree that MoDOT's decision shall be final and without recourse.
  - a. No price increase shall be granted during the first 3 months of the original contract period, or if applicable, the first 3 months of a contract renewal period.
  - b. In the event a price increase is granted due to an approved escalation, the renewal percentage shall be based upon the current award value.
- 2.5.5 Inspection and Acceptance: MoDOT reserves the right to inspect the unit at the point of manufacture, intermediate storage point, or at a destination which shall be at the discretion of MoDOT.

- a. No equipment, supplies, and/or services received by MoDOT pursuant to an award shall be deemed accepted until MoDOT has had reasonable opportunity to inspect said equipment, supplies, and/or services.
- b. All equipment, supplies, and/or services which do not comply with the specifications and/or requirements or which are otherwise unacceptable or defective may be rejected. In addition, all equipment, supplies, and/or services which are discovered to be defective or which do not conform to any warranty of the contractor upon inspection (or at any later time if the defects contained were not reasonably ascertainable upon the initial inspection) may be rejected.
- c. MoDOT reserves the right to return any such rejected shipment at the contractor's expense for full credit or replacement and to specify a reasonable date by which replacements must be received.
- d. MoDOT's right to reject any unacceptable equipment, supplies, and/or services shall not exclude any other legal or equitable remedies that MoDOT may have.

2.5.6 Net Delivered Price - the unit(s) shall be delivered complete and ready for use to the delivery destinations.

**2.6 Diesel Fuel Requirements:** In accordance with RSMo 414.365, MoDOT must use fuel with at least the biodiesel content of B-20. (<http://www.moga.mo.gov/statutes/C400-499/4140000365.htm>) By submitting a response to this bid, you agree to comply with all the terms of your company's standard equipment warranties, except to the extent the equipment problems are determined to be attributed to MoDOT's use of B-20 fuel.

### 3. BID SUBMISSION

#### 3.1 Bid Submission Information:

- 3.1.1 All bids must be received in a sealed envelope/package clearly marked **“3-170105TV Medium Duty Vehicles”**. All bids must be received at the office of the RFB Coordinator as outlined in Section 1. **“INTRODUCTION AND GENERAL INFORMATION”**.
- 3.1.2 **In addition to a hard copy of the Pricing Sheets, bid pricing should be submitted electronically on a flash drive or CD using the EXCEL spreadsheet (Pricing Entry Sheets) provided on the website for this bid. A copy of the Pricing Entry Sheets will suffice as a hardcopy.**
- 3.1.3 The bidder may withdraw, modify or correct his/her bid after it has been deposited with MoDOT provided such request is submitted in writing and received at the location designated for the bid opening prior to the date and time specified for opening bids. Such a request received as specified will be attached to the bid and the bid will be considered to have been modified accordingly. No bid may be modified after the date and time specified for the opening of bids.
- 3.1.4 Open Competition / Request For Bid Document:
  - a. It shall be the bidder's responsibility to ask questions, request changes or clarification, or otherwise advise MoDOT if any language, specifications or requirements of an RFB appear to be ambiguous, contradictory, and/or arbitrary, or appears to inadvertently restrict or limit the requirements stated in the RFB to a single source. Any and all communication from bidders regarding specifications, requirements, competitive bid process, etc., must be directed to the buyer from MoDOT, unless the RFB specifically refers the bidder to another contact. Such communication should be received at least three (3) working days prior to the official bid opening date.

- b. Every attempt shall be made to ensure that the bidder receives an adequate and prompt response. However, in order to maintain a fair and equitable bid process, all bidders will be advised, via the issuance of an amendment to the RFB, of any relevant or pertinent information related to the procurement. Therefore, bidders are advised that unless specified elsewhere in the RFB, any questions received less than three (3) working days prior to the RFB opening date may not be answered.
- c. Bidders are cautioned that the only official position of the MoDOT is that which is issued by MoDOT in the RFB or an amendment thereto. No other means of communication, whether oral or written, shall be construed as a formal or official response or statement.
- d. MoDOT monitors all procurement activities to detect any possibility of deliberate restraint of competition, collusion among bidders, price-fixing by bidders, or any other anticompetitive conduct by bidders which appears to violate state and federal antitrust laws. Any suspected violation shall be referred to the Missouri Attorney General's Office for appropriate action.

### 3.1.5 Award:

This is a Multiple Award bid and there will be no 'one' bidder awarded each item within this bid. Each individual delivery destination will have sole responsibility and discretion for all purchasing decisions. After award, Districts shall use the following evaluation criteria to determine the awarded contract that would provide the "lowest and best" equipment purchase option:

- a. Base and Options Costs 50 Points
- b. Warranty Coverage/Unit Features that Improve Performance, Strength, Reliability & Longevity 20 Points
- c. Location of Parts and Servicing Dealers and their Past Performance 20 Points
- d. Delivery Timeline 5 Points
- e. Other response information 5 Points

### 3.1.6 Cost Evaluation:

The evaluation of base and options costs will be conducted using a scale of fifty (50) possible points based upon the following formula:

$$\frac{\text{Lowest Responsive Price}}{\text{Price of Bidder Being Evaluated}} \times 50 = \text{Points Awarded to Bidder Being Evaluated}$$

3.1.7 Bidder Compliance: The bidder must be in compliance with the laws regarding conducting business with MoDOT and as indicated in the Terms and Conditions.

3.1.8 Bidder Notification: Notification of award shall be at the time the tabulation is posted to the Internet. It is the sole responsibility for all bidders to check the website for bid results.

**4. PRICING PAGES**  
**MODOT MEDIUM DUTY VEHICLES**  
**REQUEST FOR BID 3-170105TV**

What MAKE(S) of vehicles are you bidding?\_\_\_\_\_

What is the Basic Warranty on the Make(s) that you are bidding?

---

---

---

---

What is the Powertrain Warranty on the Make(s) that you are bidding?

---

---

---

---

What is the Corrosion Protection Warranty on the MAKE(S) that you are bidding?

---

---

---

What is the Roadside Assistance Warranty on the MAKE(S) that you are bidding?

---

---

---

# **VEHICLE CLASS DESCRIPTIONS**

## **REQUEST FOR BID 3-170105TV**

**ITEM # 1** –New standard equipped **2017 or Newer Model Regular Cab ¾ Ton Pickup**

**ITEM # 2** - New standard equipped **2017 or Newer Model Extend Cab ¾ Ton Pickup**

**ITEM # 3** - New standard equipped **2017 or Newer Model Crew Cab ¾ Ton Pickup**

**ITEM #4** - New standard equipped **2017 or Newer Model Regular Cab 1 Ton Pickup**

**ITEM #5** - New standard equipped **2017 or Newer Model Extended Cab 1 Ton Pickup**

**ITEM #6** - New standard equipped **2017 or Newer Model Crew Cab 1 Ton Pickup**

**ITEM # 7** - New standard equipped **2017 or Newer Model 1 Ton Reg Cab Chassis-Cab 2WD/4WD with DRW and 60” CA**

**ITEM # 8** - New standard equipped **2017 or Newer Model 1 Ton Crew Cab Chassis-Cab 2WD/4WD with DRW and 60” CA**

**ITEM # 9** - New standard equipped **2017 or Newer Model 1 Ton Reg Cab Chassis-Cab 2WD/4WD with DRW and 84” CA**

**ITEM # 10** - New standard equipped **2017 or Newer Model 15,000 LB. GVWR Reg Cab Chassis-Cab with DRW and 60” CA.**

**ITEM # 11** - New standard equipped **2017 or Newer Model 15,000 LB. GVWR Crew Chassis-Cab with DRW and 60” CA**

**ITEM # 12** - New standard equipped **2017 or Newer Model 15000 LB. GVWR Reg Cab Chassis-Cab with DRW and 84” CA.**

**ITEM # 13** - New standard equipped **2017 or Newer Model 17,500 LB, GVWR Reg Cab Chassis-Cab with DRW and 60” CA**

**ITEM # 14** - New standard equipped **2017 or Newer Model 17,500 LB. GVWR Crew Chassis-Cab with DRW and 60” CA**

**ITEM # 15** - New standard equipped **2017 or Newer Model 17,500 GVWR Reg Cab Chassis-Cabs with DRW and 84” CA.**

**ITEM # 16** - New standard equipped **2017 or Newer Model 15 Passenger Van Extended Length**

**Snow Removal Equipment (Items may be bid directly by supplier):**

**Electric/Hydraulic Plows**

**Hydraulic Plows**

**Stainless Steel Salt Spreaders**



**ITEM # 1 - New standard equipped 2017 or Newer Model Regular Cab ¾ Ton Pickup**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 2WD/4WD with 8' BOX

Standard Chevrolet 2500 2WD/4WD with 8' BOX

Standard Dodge 2500 2WD/4WD with 8' BOX

**\*ONLY THE 4WD MODEL IS RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline.
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) 10 ply(minimum) light truck, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric brake controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL WITH 2WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL WITH 4WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICING, Item # 1**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

- |            |  |                        |
|------------|--|------------------------|
| Option 1A. | Exterior color to be Federal Standard #595C "DOT Highway Yellow"   | EACH \$ _____          |
| Option 1B. | 2 Full length cab steps or running boards<br>(one on drivers side, one on passenger side)  | SET \$ _____           |
| Option 1C. | Bluetooth Capability   | EACH \$ _____          |
| Option 1D. | Optional Rear Axle Ratio      Axle Ratio _____   | EACH \$ _____          |
| Option 1E. | Limited Slip Rear Axle      Axle Ratio _____   | EACH \$ _____          |
| Option 1F. | Commercial grade spray on bed lining to be applied on floors,<br>sides, front, tailgate and top of rail.   | EACH \$ _____          |
| Option 1G. | Bed/Tow Package delete (must include spare wheel and tire)   | EACH \$ _____ (Deduct) |
| Option 1H. | Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch.<br>Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV<br>style trailer plug and electric controller brake (needed if ordering bed delete, Option 1G) | EACH \$ _____          |

Option 1L1      Mounted 8' platform body meeting Specification E1320SRW  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 1L2      Mounted 8' aluminum platform body meeting Specification E1320SRW  
(Minimum 1" aluminum extruded floor instead of steel)  
MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 1J.      Permanently installed bulkhead to fit truck application  
(Minimum requirement to top of cab) EACH \$ \_\_\_\_\_

Option 1K.      Mounted standard utility tool body.  
Acceptable makes and models are:  
Knapheide 696J                      Stahl CHALLENGER II 96VVS - 48.5  
Reading Classic II 98A S.W.      RKI -L5680  
Omaha 96V                          RKI L5780 (for Dodge)

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess. Vendors may submit more than one brand/model of bed for this option.

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 1L.      Mounted *fiberglass* composite utility tool body.

Acceptable makes and models are:  
Brand FX Composite Service Body (Model 56LS)  
Equivalentents accepted if pre-approved at least 5 working days before bid opening.

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 1M.      Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum end gate cover to protect cargo area from weather and theft. EACH \$ \_\_\_\_\_

Option 1N.      Additional set of keys (Ignition and door locks) EACH \$ \_\_\_\_\_

Option 1O.      Auxiliary Upfitter Switches EACH \$ \_\_\_\_\_

Option 1P.      Standard diesel engine in lieu of gasoline engine (state size/horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 2 - New standard equipped 2017 or Newer Model Extended Cab ¾ Ton Pickup.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 2WD/4WD with 8' Box/Short Box

Standard Chevrolet 2500 2WD/4WD with 8' Box/Short Box

Standard Dodge 2500 2WD/4WD 8' with 8' Box/Short Box

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SHOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric brake controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL 2WD/SHORT BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD/SHORT BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 2**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 2A. Exterior color to be Federal Standard #595C "DOT Highway Yellow" EACH \$ \_\_\_\_\_

Option 2B. 2 Full length cab steps or running boards.  
(One on drivers side, one on passenger side) SET \$ \_\_\_\_\_

Option 2C. Bluetooth Capability EACH \$ \_\_\_\_\_

Option 2D. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 2E. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 2F. Commercial grade spray on bed lining to be applied on floors, sides,  
front, tailgate and top of rail. EACH \$ \_\_\_\_\_

- Option 2G.**      **Bed/Tow Package delete (must include spare wheel and tire)**      **EACH \$ \_\_\_\_\_ (Deduct)**
- 
- Option 2H.**      **Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch.**      **EACH \$ \_\_\_\_\_**  
**Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller (needed if ordering bed delete, Option 2G)**
- 
- Option 2I.1**      **Mounted 8' platform body meeting Specification E1320SRW**      **EACH \$ \_\_\_\_\_**  
**MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 2I.2**      **Mounted 8' aluminum platform body meeting Specification E1320SRW**      **EACH \$ \_\_\_\_\_**  
**(Minimum 1" aluminum extruded floor instead of steel)**  
**MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 2J.**      **Permanently installed bulkhead to fit truck application**      **EACH \$ \_\_\_\_\_**  
**(Minimum requirement to top of cab)**
- Option 2K.**      **Mounted standard utility tool body.**      **EACH \$ \_\_\_\_\_**  
**Acceptable makes and models are:**  
**Knapheide 696J                      Stahl CHALLENGER II 96VVS - 48.5**  
**Reading Classic II 98A S.W.      RKI -L5680**  
**Omaha 96V                          RKI L5780 (for Dodge)**
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 2L.**      **Mounted fiberglass composite utility tool body.**      **EACH \$ \_\_\_\_\_**
- Acceptable makes and models are:**  
**Brand FX Composite Service Body (Model 56LS)**  
**Equivalents accepted if pre-approved at least 5 working days before bid opening.**
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess**
- Option 2M.**      **Utility tool body 3 section, tempered steel telescopic sliding roof and two-piece rigid aluminum end gate cover to protect cargo area from weather and theft**      **EACH \$ \_\_\_\_\_**
- Option 2N.**      **Additional set of keys (Ignition and door locks)**      **EACH \$ \_\_\_\_\_**
- Option 2O.**      **Standard diesel engine in lieu of gasoline engine (state size/horsepower)**      **EACH \$ \_\_\_\_\_**  
**SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

**% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_**

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 3 - New standard equipped 2017 or Newer Model Crew Cab ¾ Ton Pickup.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-250 2WD/4WD with 8' Box/Short Box

Standard Chevrolet 2500 2WD/4WD with 8' Box/Short Box

Standard Dodge 2500 2WD/4WD with 8' Box/Short Box

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(4) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 8,600 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric brake controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL 2WD/SHORT BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD SHORT BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD/8' BOX \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 3**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 3A. Exterior color to be Federal Standard #595C "DOT Highway Yellow" EACH \$ \_\_\_\_\_

Option 3B. 2 Full length cab steps or running boards. SET \$ \_\_\_\_\_  
(One on drivers side, one on passenger side)

Option 3C. Bluetooth Capability EACH \$ \_\_\_\_\_

Option 3D. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 3E. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 3F. Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail. EACH \$ \_\_\_\_\_

- Option 3G.**      **Bed/Tow Package delete (must include spare wheel and tire)**      **EACH \$ \_\_\_\_\_ (Deduct)**
- Option 3H.**      **Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch.**      **EACH \$ \_\_\_\_\_**  
**Includes an adapter to reduce to 2" (Class III/IV) and a seven-wire**  
**RV style trailer plug and Electric Trailer Brake Controller**  
**(needed if ordering bed delete, Option 3H)**
- Option 3L1**      **Mounted 8' platform body meeting Specification E1320SRW**      **EACH \$ \_\_\_\_\_**  
**MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 3L2**      **Mounted 8' aluminum platform body meeting Specification E1320SRW**      **EACH \$ \_\_\_\_\_**  
**(Minimum 1" aluminum extruded floor instead of steel)**  
**MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 3J.**      **Permanently installed bulkhead to fit truck application**      **EACH \$ \_\_\_\_\_**  
**(Minimum requirement to top of cab)**
- Option 3K.**      **Mounted standard utility tool body.**      **EACH \$ \_\_\_\_\_**  
**Acceptable makes and models are:**  
**Knapheide 696J**      **Stahl CHALLENGER II 96VVS - 48.5**  
**Reading Classic II 98A S.W.**      **RKI -L5680**  
**Omaha 96V**      **RKI L5780 (for Dodge)**
- Body to include flush mounted LED tail, stop, turn, backup and clearance**  
**lights as required per FMVSS 108 standards. Unit must include a tread**  
**plate step bumper with pintle hook recess**  
**MAKE \_\_\_\_\_ MODEL \_\_\_\_\_**
- Option 3L.**      **Mounted fiberglass composite utility tool body.**      **EACH \$ \_\_\_\_\_**  
**Acceptable makes and models are:**  
**Brand FX Composite Service Body (Model 56LS)**  
**Equivalentents accepted if pre-approved at least 5 working days before bid opening.**
- Body to include flush mounted LED tail, stop, turn, backup and clearance**  
**lights as required per FMVSS 108 standards. Unit must include a tread**  
**plate step bumper with pintle hook recess**
- Option 3M.**      **Utility tool body 3 section, tempered steel telescopic sliding roof**      **EACH \$ \_\_\_\_\_**  
**and two-piece rigid aluminum end gate cover to protect cargo area**  
**from weather and theft**
- Option 3N.**      **Additional set of keys (Ignition and door locks)**      **EACH \$ \_\_\_\_\_**
- Option 3O.**      **Standard diesel engine in lieu of gasoline engine (state size and horsepower)**  
**SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_ EACH \$ \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

**% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_**

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 4 - New standard equipped 2017 or Newer Model Regular Cab 1 Ton Pickup**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Chevrolet 3500 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Dodge 3500 2WD/4WD, 8' Box/Short Box, SRW/DRW

**\*ONLY 4WD MODEL IS RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric trailer brake controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL 2WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 4**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 4A. Exterior color to be Federal Standard #595C "DOT Highway Yellow" EACH \$ \_\_\_\_\_

Option 4B. 2 Full length cab steps or running boards.  
(One on drivers side, one on passenger side) SET \$ \_\_\_\_\_

Option 4C. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 4D. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 4E.**      **Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail.**      **EACH \$ \_\_\_\_\_**

**Option 4F.**      **Bluetooth Capability**      **EACH \$ \_\_\_\_\_**

**Option 4G.**      **Additional set of keys (Ignition and door locks)**      **EACH \$ \_\_\_\_\_**

**Option 4H.**      **Standard diesel engine in lieu of gasoline engine**      **EACH \$ \_\_\_\_\_**  
**(State size and horsepower)**

**SIZE \_\_\_\_\_      HORSEPOWER \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**



**ITEM # 5 - New standard equipped 2017 or Newer Model Extended Cab 1 Ton Pickup**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Chevrolet 3500 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Dodge 3500 2WD/4WD, 8' Box/Short Box,

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) 10 ply (minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric brake trailer controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL 2WD/SHORT BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/SHORT BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 5**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

<b>Option 5A.</b>	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	<b>EACH \$</b> _____
<b>Option 5B.</b>	2 Full length cab steps or running boards. (One on drivers side, one on passenger side)	<b>SET \$</b> _____
<b>Option 5C.</b>	Optional Rear Axle Ratio      Axle Ratio _____	<b>EACH \$</b> _____
<b>Option 5D.</b>	Limited Slip Rear Axle      Axle Ratio _____	<b>EACH \$</b> _____
<b>Option 5E.</b>	Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail.	<b>EACH \$</b> _____
<b>Option 5F.</b>	Bluetooth Capability	<b>EACH \$</b> _____
<b>Option 5G.</b>	Additional set of keys (Ignition and door locks)	<b>EACH \$</b> _____
<b>Option 5H.</b>	Standard diesel engine in lieu of gasoline engine (State size and horsepower)	<b>EACH \$</b> _____
	<b>SIZE</b> _____ <b>HORSEPOWER</b> _____	

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount* \_\_\_\_\_

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 6 - New standard equipped 2017 or Newer Model Crew Cab 1 Ton Pickup**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Chevrolet 3500 2WD/4WD, 8' Box/Short Box, SRW/DRW

Standard Dodge 3500 2WD/4WD, 8' Box/Short Box, SRW/DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, minimum V8 fuel-injected gasoline engine
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Trailer towing package: Standard manufacturer's to include receiver hitch, 4/7 pin trailer wiring connection & electric trailer brake controller
9. Brakes, 4-wheel anti-lock braking system (ABS)
10. Daytime running lights
11. Speed control and tilt wheel
12. Vinyl/Rubber Flooring
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE:**

MAKE \_\_\_\_\_ MODEL 2WD/SHORT BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL 2WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/SHORT BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/8' BOX/SRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD 8' BOX/DRW \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 6**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

<b>Option 6A.</b>	<b>Exterior color to be Federal Standard #595C "DOT Highway Yellow"</b>	<b>EACH \$ _____</b>
<b>Option 6B.</b>	<b>2 Full length cab steps or running boards. (One on drivers side, one on passenger side)</b>	<b>SET \$ _____</b>
<b>Option 6C.</b>	<b>Optional Rear Axle Ratio      Axle Ratio _____</b>	<b>EACH \$ _____</b>
<b>Option 6D.</b>	<b>Limited Slip Rear Axle      Axle Ratio _____</b>	<b>EACH \$ _____</b>
<b>Option 6E.</b>	<b>Commercial grade spray on bed lining to be applied on floors, sides, front, tailgate and top of rail.</b>	<b>EACH \$ _____</b>
<b>Option 6F.</b>	<b>Bluetooth Capability</b>	<b>EACH \$ _____</b>
<b>Option 6G.</b>	<b>Additional set of keys (Ignition and door locks)</b>	<b>EACH \$ _____</b>
<b>Option 6H.</b>	<b>Option for Single Rear Wheels (SRW) in lieu of Dual Rear Wheels</b>	<b>EACH \$ _____</b>
<b>Option 6I.</b>	<b>Standard diesel engine in lieu of gasoline engine (State size and horsepower)</b>	<b>EACH \$ _____</b>
	<b>SIZE _____      HORSEPOWER _____</b>	

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 7 - New standard equipped 2017 or Newer Model 1 Ton Regular Chassis-Cab with DRW and 60" CA**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD, 60"CA/ 145"WB and DRW

Standard Chevrolet 3500HD/GMC 3500HD 2WD/4WD, 60" CA/137" WB and DRW

Standard Dodge 3500 2WD/4WD, 60" CA/143" WB and DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOWS\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 7**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 7A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 7A.2 Mounted aluminum 9' platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 7B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

<b>Option 7B.2</b>	<b>Mounted aluminum 9' platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)</b>		
	MAKE _____	MODEL _____	EACH \$ _____
	MAKE _____	MODEL _____	EACH \$ _____
<b>Option 7C.1</b>	<b>Mounted 9' dump body meeting Specification E1335</b>		
	MAKE _____	MODEL _____	EACH \$ _____
	MAKE _____	MODEL _____	EACH \$ _____
<b>Option 7C.2</b>	<b>Mounted 9' aluminum dump body meeting Specification E1335-ALUM</b>		
	MAKE _____	MODEL _____	EACH \$ _____
	MAKE _____	MODEL _____	EACH \$ _____
<b>Option 7D.</b>	<b>Permanently installed bulkhead to fit truck application (Minimum requirement to top of cab)</b>		<b>EACH \$ _____</b>
<b>Option 7E.</b>	<b>Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 7 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Valve shall be cable operated. Control valve must have a main relief and a relief for the hoist down function. This shall control the hoist only.</b>		<b>EACH \$ _____</b>
<b>Option 7F.</b>	<b>Provide hydraulics and controls 12VDC activated for dump hoist only</b>		<b>EACH \$ _____</b>
<b>Option 7G.</b>	<b>Mounted standard utility tool body</b>		
	Acceptable makes and models are: Knapheide 6108D54J,                      Stahl CHALLENGER II 108VVD- 54, Reading CLASSIC II 108A D.W.              RKI L60DW94. Omaha 108D54V,		
	<b>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.</b>		
	MAKE _____	MODEL _____	EACH \$ _____
	MAKE _____	MODEL _____	EACH \$ _____
<b>Option 7H.</b>	<b>Mounted fiberglass composite utility tool body.</b>		
	Acceptable makes and models are: Brand FX Composite Service Body (Model 60LS) Equivalentents accepted if pre-approved at least 5 working days before bid opening.		
	<b>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</b>		
	MAKE _____	MODEL _____	EACH \$ _____

Option 7I.	Six - 2" deep full width 250 lb. capacity, free-sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartment.	EACH \$ _____
Option 7J.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments.	EACH \$ _____
Option 7K.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.	EACH \$ _____
Option 7L.	One - double bottle gas drop well and retainers in lieu of three shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48".	EACH \$ _____
Option 7M.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy Roof Style).	EACH \$ _____
Option 7N.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover.	EACH \$ _____
Option 7O.	Raise Telescopic Roof to get 36" clearance for the above option.	EACH \$ _____
Option 7P.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 7Q.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 7R.	Heavy - duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 7S.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 7T.	Automatic transmission power take-off provision	EACH \$ _____
Option 7U.	2 Full length cab steps or running boards. (One on drivers side, one on passenger side.)	SET \$ _____
Option 7V.	Optional Rear Axle Ratio      Axle Ratio _____	EACH \$ _____
Option 7W.	Limited Slip Rear Axle      Axle Ratio _____	EACH \$ _____

Option 7X.      Bluetooth Capability      EACH \$ \_\_\_\_\_

Option 7Y.      Additional set of keys (Ignition and door locks)      EACH \$ \_\_\_\_\_

Option 7Z.      Standard gasoline engine in lieu of diesel engine with the highest cooling capacity      EACH \$ \_\_\_\_\_  
                  DEDUCT      (State size and horsepower)

                 SIZE \_\_\_\_\_      HORSEPOWER \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.



**ITEM # 8 - New standard equipped 2017 or Newer Model 1 Ton Crew Chassis-Cab with DRW and 60" CA**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD with 60"CA/179"WB and DRW

Standard Chevrolet 3500HD/GMC 3500HD 2WD/4WD with 60"CA/167"WB and DRW

Standard Dodge 3500 2WD/4WD with 60"CA/168"WB and DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) 10 ply(minimum) light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 8**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 8A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8A.2 Mounted aluminum 9' platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8B.2 Mounted aluminum 9' platform dump body meeting Specification E1327  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8C.1 Mounted 9' dump body meeting Specification E1335**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8C.2 Mounted 9' aluminum dump body meeting Specification E1335-ALUM**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8D. Permanently installed bulkhead to fit truck application  
(Minimum requirement to top of cab)**

EACH \$ \_\_\_\_\_

**Option 8E. Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 7 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Valve shall be cable operated. Control valve must have a main relief and a relief for the hoist down function.  
This shall control the hoist only.**

EACH \$ \_\_\_\_\_

**Option 8F. Provide hydraulics and controls 12VDC activated for dump hoist only**

EACH \$ \_\_\_\_\_

**Option 8G. Mounted standard utility tool body**

Acceptable makes and models are:

Knapheide 6108D54J,

Reading CLASSIC II 108A D.W.

Omaha 108D54V,

Stahl CHALLENGER II 108VVD- 54,

RKI L60DW94.

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8H. Mounted *fiberglass* composite utility tool body.**

Acceptable makes and models are:

Brand FX Composite Service Body (Model 60LS)

Equivalentents accepted if pre-approved at least 5 working days before bid opening.

Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 8I. Six - 2" deep full width 250 lb. capacity, free-sliding tool drawers mounted**

EACH \$ \_\_\_\_\_

approximately 1 ½” from top of compartment with approximately 2 ½” between trays in lieu of two shelves and dividers in one of the full height vertical compartment.

Option 8J.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4” centers with first tray mounted 5 ¼ “ from bottom of compartment with approximately 1 ½” between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments.	EACH \$ _____
Option 8K.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.	EACH \$ _____
Option 8L.	One - double bottle gas drop well and retainers in lieu of three shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48”.	EACH \$ _____
Option 8M.	Minimum 25” high panel extension cover with minimum 42” locking rear doors which will provide a minimum 48” interior height for storage and work area (Canopy Roof Style).	EACH \$ _____
Option 8N.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover.	EACH \$ _____
Option 8O.	Raise Telescopic Roof to get 36” clearance for the above option.	EACH \$ _____
Option 8P.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 8Q.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 8R.	Heavy - duty, Class V (2-1/2 “ square tube) receiver trailer hitch. Includes an adapter to reduce to 2” (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 8S.	Exterior color to be Federal Standard #595C “DOT Highway Yellow”	EACH \$ _____
Option 8T.	Automatic transmission power take-off provision	EACH \$ _____
Option 8U.	2 Full length cab steps or running boards. (One on drivers side, one on passenger side.)	SET \$ _____
Option 8V.	Optional Rear Axle Ratio                      Axle Ratio _____	EACH \$ _____
Option 8W.	Limited Slip Rear Axle                      Axle Ratio _____	EACH \$ _____
Option 8X.	Bluetooth Capability	EACH \$ _____

**Option 8Y.**      **Additional set of keys (Ignition and door locks)**      **EACH \$ \_\_\_\_\_**

**Option 8Z.**      **Standard gasoline engine in lieu of diesel engine with the highest cooling capacity**      **EACH \$ \_\_\_\_\_**

**DEDUCT (State size and horsepower)      SIZE \_\_\_\_\_      HORSEPOWER \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 9 - New standard equipped 2017 or Newer Model 1 Ton Regular Cab Chassis-Cab with DRW and 84" CA**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford F-350 2WD/4WD with 84"CA/169"WB and DRW

Standard Chevrolet 3500 HD/GMC 3500 HD 2WD/4WD with 84"CA/161"WB and DRW

Standard Dodge Ram 3500 2WD/4WD with 84"CA/167"WB and DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 11,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD/84" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/84" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 9**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 9A.1 Mounted 11' platform body meeting Specification E1320DRW:**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 9A.2 Mounted 11' aluminum platform body meeting Specification E1320DRW:  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 9B.1 Mounted 11' platform dump body meeting Specification E1327:**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

- Option 9B.2**      **Mounted 11' aluminum platform dump body meeting Specification E1327:  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 9C.**      **Permanently installed bulkhead to fit truck application  
(Minimum requirement to top of cab)** EACH \$ \_\_\_\_\_
- Option 9D.**      **Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 7 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Valve shall be cable operated. Control valve must have a main relief and a relief for the hoist down function. This shall control the hoist only.** EACH \$ \_\_\_\_\_
- Option 9E.**      **Provide hydraulics and controls 12VDC activated for dump hoist only** EACH \$ \_\_\_\_\_
- Option 9F.**      **Mounted standard utility tool body**
- Acceptable makes and models are:  
Knapheide 6132D54J      Stahl CHALLENGER 132VVD-54  
Reading CLASSIC II 132A DW      RKI L84DW94  
Omaha 132D54V
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 9G.**      **Mounted *fiberglass* composite utility tool body.**
- Acceptable makes and models are:  
Brand FX Composite Service Body (Model 84LS)  
Equivalents accepted if pre-approved at least 5 working days before bid opening.
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 9H.**      **Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments** EACH \$ \_\_\_\_\_
- Option 9I.**      **Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4" from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments** EACH \$ \_\_\_\_\_
- Option 9J.**      **Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.** EACH \$ \_\_\_\_\_

Option 9K.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 9L.	Body to have 3 sections, tempered steel telescopic sliding roof and two-piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 9M.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 9N.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 9O.	One - double bottle gas drop well with minimum 55" clearance height (for large Bottle use) and retainers in lieu of the interior 48" full height vertical compartment	EACH \$ _____
Option 9P.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 9Q.	Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 9R.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 9S.	Automatic transmission power take off provision	EACH \$ _____
Option 9T.	2 Full-length cab steps or running boards. (One on drivers side, one on passenger side)	SET \$ _____
Option 9U.	Optional Rear Axle Ratio                      Axle Ratio _____	EACH \$ _____
Option 9V.	Limited Slip Rear Axle                      Axle Ratio _____	EACH \$ _____
Option 9W.	Bluetooth Capability	EACH \$ _____
Option 9X.	Additional set of keys (Ignition and door locks)	EACH \$ _____
Option 9Y.	Standard gasoline engine <u>with the highest cooling capacity</u> in lieu of diesel engine- DEDUCT (State size and horsepower)  SIZE _____ HORSEPOWER _____	EACH \$ _____

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 10** - New standard equipped **2017 or Newer Model 15,000 LB. GVWR Chassis-Cab with DRW and 60" CA.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F450 2WD/4WD with 60"CA/145" WB and DRW

Standard Dodge 4500 2WD/4WD with 60"CA/144.5" WB and DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 15,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL**

MAKE \_\_\_\_\_ MODEL 2WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 10**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 10A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 10A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 10B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_



<b>Option 10B.2</b>	<b>Mounted 9' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 10C.1</b>	<b>Mounted 9' dump body meeting Specification E1335</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 10C.2</b>	<b>Mounted 9' aluminum dump body meeting Specification E1335-ALUM</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 10D.</b>	<b>Permanently installed bulkhead to fit truck application (minimum requirement to top of cab)</b>	EACH \$ _____
<b>Option 10E.</b>	<b>Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.</b>	EACH \$ _____
<b>Option 10F.</b>	<b>Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 13E specifications.</b>	EACH \$ _____
<b>Option 10G.</b>	<b>Provide hydraulics and controls 12VDC activated for dump hoist only</b>	EACH \$ _____
<b>Option 10H.</b>	<b>Mounted standard utility tool body. Acceptable makes and models are: Knapheide 6108D54J                      RKI L60DW94. Reading CLASSIC II 108A DW    Stahl CHALLENGER II 108VVD-54 Omaha 108D54V,  Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____

Option 10I.	<p>Mounted <i>fiberglass</i> composite utility tool body.  Acceptable makes and models are:  Brand FX Composite Service Body (Model 84LS)  Equivalents accepted if pre-approved at least 5 working days before bid opening.</p> <p>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>	
Option 10J.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 10K.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments	EACH \$ _____
Option 10L.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment	EACH \$ _____
Option 10M.	One - double bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48"	EACH \$ _____
Option 10N.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 10O.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 10P.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 10Q.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 10R.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 10S.	Heavy duty, Class V (2-1/2 " square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 10T.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 10U.	Automatic transmission power take-off provision	EACH \$ _____

Option 10V. 2 Full length cab steps or running boards.  
(One on drivers side, one on passenger side) SET \$ \_\_\_\_\_

Option 10W. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 10X. Limited Slip Rear Axle Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 10Y. Bluetooth Capability EACH \$ \_\_\_\_\_

Option 10Z. Additional set of keys (Ignition and door locks) EACH \$ \_\_\_\_\_

Option 10AA. Standard gasoline engine with the highest cooling capacity in lieu of  
diesel engine– DEDUCT (State size and horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount* \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 11 - New standard equipped 2017 or Newer Model 15,000 LB. GVWR Crew Cab Chassis Cab with DRW and 60" CA.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F450 2WD/4WD with 60"CA/179"WB with DRW

Standard Dodge 4500 2WD/4WD with 60"CA/173.4" WB and DRW

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires: (6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 15,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL**

MAKE \_\_\_\_\_ MODEL 2WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/60" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 11**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 11A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 11A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 11B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 11B.2	<p><b>Mounted 9' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 11C.1	<p><b>Mounted 9' dump body meeting Specification E1335</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 11C.2	<p><b>Mounted 9' aluminum dump body meeting Specification E1335-ALUM</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 11D.	<p><b>Permanently installed bulkhead to fit truck application (minimum requirement to top of cab)</b></p> <p>EACH \$ _____</p>
Option 11E.	<p><b>Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.</b></p> <p>EACH \$ _____</p>
Option 11F.	<p><b>Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 13E specifications.</b></p> <p>EACH \$ _____</p>
Option 11G.	<p><b>Provide hydraulics and controls 12VDC activated for dump hoist only</b></p> <p>EACH \$ _____</p>
Option 11H.	<p><b>Mounted standard utility tool body. Acceptable makes and models are: Knapheide 6108D54J                      RKI L60DW94. Reading CLASSIC II 108A DW    Stahl CHALLENGER II 108VVD-54 Omaha 108D54V,</b></p> <p><b>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>

Option 11I.	<p>Mounted <i>fiberglass</i> composite utility tool body.  Acceptable makes and models are:  Brand FX Composite Service Body (Model 84LS)  Equivalents accepted if pre-approved at least 5 working days before bid opening.</p> <p>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>	
Option 11J.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 11K.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4" from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments	EACH \$ _____
Option 11L.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment	EACH \$ _____
Option 11M.	One - double bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments, maintaining an interior height of 48"	EACH \$ _____
Option 11N.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 11O.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, end gate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 11P.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 11Q.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 11R.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 11S.	Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 11T.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 11U.	Automatic transmission power take-off provision	EACH \$ _____

<b>Option 11V.</b>	<b>2 Full length cab steps or running boards.</b> <b>(One on drivers side, one on passenger side)</b>	<b>SET \$</b> _____
<b>Option 11W.</b>	<b>Optional Rear Axle Ratio      Axle Ratio</b> _____	<b>EACH \$</b> _____
<b>Option 11X.</b>	<b>Limited Slip Rear Axle      Axle Ratio</b> _____	<b>EACH \$</b> _____
<b>Option 11Y.</b>	<b>Bluetooth Capability</b>	<b>EACH \$</b> _____
<b>Option 11Z.</b>	<b>Additional set of keys (Ignition and door locks)</b>	<b>EACH \$</b> _____
<b>Option 11AA.</b>	<b>Standard gasoline engine <u>with the highest cooling capacity</u> in lieu of diesel engine – DEDUCT (State size and horsepower)</b>	<b>EACH \$</b> _____
	<b>SIZE</b> _____ <b>HORSEPOWER</b> _____	

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount* \_\_\_\_\_

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 12 - New standard equipped 2017 or Newer Model 15000 LB. GVWR Reg Cab Chassis-Cab 84" CA with DRW.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Standard Ford Super Duty F450 2WD/4WD with 84"CA/169" WB and DRW

Standard Dodge 4500 with 168.5" Wheelbase, Cab to Axle 84"

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 15,000 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD/84" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD/84" CA \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 12**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 12A.1 Mounted 12' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 12A.2 Mounted 12' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 12B.1 Mounted 11' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_



- Option 12B.2**    **Mounted 11' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 12C.**    **Permanently installed bulkhead to fit truck application (minimum requirement to top of cab)** EACH \$ \_\_\_\_\_
- Option 12D.**    **Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.** EACH \$ \_\_\_\_\_
- Option 12E.**    **Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 14D specifications.** EACH \$ \_\_\_\_\_
- Option 12F.**    **Provide hydraulics and controls 12VDC activated for dump hoist only** EACH \$ \_\_\_\_\_
- Option 12G.**    **Mounted standard utility tool body.**
- Acceptable makes and models are:  
Knapheide 6132D54J ,                      Stahl CHALLENGER II 132VVD-54  
Reading CLASSIC II 132A DW   Omaha 132D54V  
RKI L84DW94
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 12H.**    **Mounted *fiberglass* composite utility tool body.**
- Acceptable makes and models are:  
Brand FX Composite Service Body (Model 84LS)  
Equivalents accepted if pre-approved at least 5 working days before bid opening.
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 12I.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 12J.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments	EACH \$ _____
Option 12K.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.	EACH \$ _____
Option 12L.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 12M.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 12N.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. capacity crane (with nomounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 12O.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 12P.	One - double bottle gas drop well with minimum 55" clearance height (for large bottle use) and retainers	EACH \$ _____
Option 12Q.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 12R.	Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric trailer brake controller	EACH \$ _____
Option 12S.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 12T.	Automatic transmission power take-off provision	EACH \$ _____
Option 12U.	2 Full-length cab steps or running boards. (one on drivers side, one on passenger side)	SET \$ _____
Option 12V.	Optional Rear Axle Ratio                      Axle Ratio _____	EACH \$ _____
Option 12W.	Limited Slip Rear Axle.                      Axle Ratio _____	EACH \$ _____

<b>Option 12X.</b>	<b>Bluetooth Capability</b>	<b>EACH \$ _____</b>
<b>Option 12Y.</b>	<b>Additional set of keys (Ignition and door locks)</b>	<b>EACH \$ _____</b>
<b>Option 12Z.</b>	<b>Standard gasoline engine <u>with the highest cooling capacity</u> in lieu of diesel engine– DEDUCT (state size and horsepower)</b>	<b>EACH \$ _____</b>
	<b>SIZE _____ HORSEPOWER _____</b>	

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

**ITEM # 13 - New standard equipped 2017 or Newer Model 17,500 LB, GVWR Reg Cab Chassis-Cab 60" CA and DRW**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Ford Super Duty F550 2WD/4WD with 60" CA/145" WB and DRW

Dodge 55002WD/4WD with 60 "CA/144.5" WB and DRW

Freightliner M2106 2WD/4WD with 61.4"CA/130" WB and DRW (Installation of a body may require modifications)

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity Size\_\_\_\_\_ Horsepower\_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size\_\_\_\_\_)
7. Minimum 17,500 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

\*MAKE \_\_\_\_\_ MODEL 4WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 13**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 13A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 13A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 13B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 13B.2	<p><b>Mounted 9' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 13C.1	<p><b>Mounted 9' dump body meeting Specification E1335</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 13C.2	<p><b>Mounted 9' aluminum dump body meeting Specification E1335-ALUM</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>
Option 13D	<p><b>Permanently installed bulkhead to fit truck application (minimum requirement to top of cab)</b></p> <p>EACH \$ _____</p>
Option 13E.	<p><b>Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.</b></p> <p>EACH \$ _____</p>
Option 13F.	<p><b>Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 15E specifications.</b></p> <p>EACH \$ _____</p>
Option 13G.	<p><b>Provide hydraulics and controls 12VDC activated for dump hoist only</b></p> <p>EACH \$ _____</p>
Option 13H.	<p><b>Mounted standard utility tool body. Acceptable makes and models are: Knapheide 6108D54J,                      Stahl CHALLENGER II 108VVD- 54 Reading CLASSIC II 108A DW   Omaha 108D54V RKI L60DW94.</b></p> <p><b>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.</b></p> <p>MAKE _____ MODEL _____ EACH \$ _____</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>

Option 13I.	<p>Mounted <i>fiberglass</i> composite utility tool body.  Acceptable makes and models are:  Brand FX Composite Service Body (Model 60LS)  Equivalents accepted if pre-approved at least 5 working days before bid opening.</p> <p>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>	
Option 13J.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 13K.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments.	EACH \$ _____
Option 13L.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.	EACH \$ _____
Option 13M.	One full- length (or from crane mounting point) 4" deep top opening compartment with release located inside side compartment, automatic up position latch and metal dividers with slots on 4" centers in addition to the standard tool compartments. The top opening compartment will not protrude more than 2" into side compartment (The side compartment shall be 27" from floor to top of side body plus excess for flip top compartment)	EACH \$ _____
Option 13N.	One double- bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 13O.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 13P.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 13Q.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 13R.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. cap. crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 13S.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, side's tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 13T.	Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric brake controller	EACH \$ _____

- Option 13U. Exterior color to be Federal Standard #595C “DOT Highway Yellow” EACH \$ \_\_\_\_\_
- Option 13V. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_
- Option 13W. 2 cab steps. (One on driver’s side, one on passenger side) SET \$ \_\_\_\_\_
- Option 13X. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 13Y. Limited Slip Rear Axle. Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 13Z. Bluetooth Capability EACH \$ \_\_\_\_\_
- Option 13AA. Additional set of keys (Ignition and door locks) EACH \$ \_\_\_\_\_
- Option 13BB. Standard gasoline engine with the highest cooling capacity in lieu (Deduct) of diesel engine– DEDUCT (state size and horsepower) EACH \$ \_\_\_\_\_
- SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer’s Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 14 - New standard equipped 2017 or Newer Model 17,500 LB. GVWR Crew Chassis-Cab with DRW and 60" CA**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Ford Super Duty F550 2WD/4WD with 60"CA/179" WB and DRW

Dodge 5500 2WD/4WD with 60"CA/173.4" WB and DRW

Freightliner M2106 2WD/4WD with 60.2"CA/176" WB and DRW (Installation of a body may require modifications)

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 17,500 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item # 14**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 14A.1 Mounted 9' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 14A.2 Mounted 9' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 14B.1 Mounted 9' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_



<b>Option 14B.2</b>	<b>Mounted 9' aluminum platform dump body meeting Specification E1327 (Minimum 1 1/4" aluminum extruded floor instead of steel)</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 14C.1</b>	<b>Mounted 9' dump body meeting Specification E1335</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 14C.2</b>	<b>Mounted 9' aluminum dump body meeting Specification E1335-ALUM</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____
<b>Option 14D</b>	<b>Permanently installed bulkhead to fit truck application (minimum requirement to top of cab)</b>	<b>EACH \$ _____</b>
<b>Option 14E.</b>	<b>Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.</b>	<b>EACH \$ _____</b>
<b>Option 14F.</b>	<b>Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 15E specifications.</b>	<b>EACH \$ _____</b>
<b>Option 14G.</b>	<b>Provide hydraulics and controls 12VDC activated for dump hoist only</b>	<b>EACH \$ _____</b>
<b>Option 14H.</b>	<b>Mounted standard utility tool body. Acceptable makes and models are: Knapheide 6108D54J,                      Stahl CHALLENGER II 108VVD- 54 Reading CLASSIC II 108A DW   Omaha 108D54V RKI L60DW94.</b>	
	<b>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.</b>	
	MAKE _____	MODEL _____ EACH \$ _____
	MAKE _____	MODEL _____ EACH \$ _____

Option 14I.	<p>Mounted <i>fiberglass</i> composite utility tool body.  Acceptable makes and models are:  Brand FX Composite Service Body (Model 60LS)  Equivalents accepted if pre-approved at least 5 working days before bid opening.</p> <p>Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess</p> <p>MAKE _____ MODEL _____ EACH \$ _____</p>	
Option 14J.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 14K.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments.	EACH \$ _____
Option 14L.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment.	EACH \$ _____
Option 14M.	One full- length (or from crane mounting point) 4" deep top opening compartment with release located inside side compartment, automatic up position latch and metal dividers with slots on 4" centers in addition to the standard tool compartments. The top opening compartment will not protrude more than 2" into side compartment (The side compartment shall be 27" from floor to top of side body plus excess for flip top compartment)	EACH \$ _____
Option 14N.	One double- bottle gas drop well and retainers in lieu of two shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 14O.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 14P.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 14Q.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 14R.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. cap. crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 14S.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, side's tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 14T.	Heavy duty, Class V (2-1/2" square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), seven-wire RV style trailer plug and electric brake controller	EACH \$ _____
Option 14U.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____

Option 14V. Automatic transmission power take-off provision EACH \$ \_\_\_\_\_

Option 14W. 2 cab steps. (One on driver's side, one on passenger side) SET \$ \_\_\_\_\_

Option 14X. Optional Rear Axle Ratio Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 14Y. Limited Slip Rear Axle. Axle Ratio \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 14Z. Bluetooth Capability EACH \$ \_\_\_\_\_

Option 14AA. Additional set of keys (Ignition and door locks) EACH \$ \_\_\_\_\_

Option 14BB. Standard gasoline engine with the highest cooling capacity in lieu (Deduct of diesel engine– DEDUCT (state size and horsepower) EACH \$ \_\_\_\_\_

SIZE \_\_\_\_\_ HORSEPOWER \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

*% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_*

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.

**ITEM # 15 - New standard equipped 2017 or Newer Model 17,500 GVWR Reg Cab Chassis-Cab 84" CA and DRW.**

**EXAMPLES OF ACCEPTABLE MAKES AND MODELS:**

Ford Super Duty F550 2WD/4WD with 84"CA/169" WB and DRW

Dodge 5500 2WD/4WD with 94"CA/168.5" WB and DRW

Freightliner M2 106 2WD/4WD with 84.4"CA/153" WB and DRW (Installation of a body may require modifications)

**\*ONLY THE 4WD MODELS ARE RECOMMENDED FOR SNOW PLOW\***

**All units bid must contain the following options:**

1. Standard, diesel engine with the highest cooling capacity Size \_\_\_\_\_ Horsepower \_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds \_\_\_\_\_)
4. Air conditioning
5. LH & RH manual mirrors
6. Tires:(6) Minimum 10 ply light truck, highway all season, plus full size spare and wheel (Size \_\_\_\_\_)
7. Minimum 17,500 lbs. GVWR
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Back up alarm
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL 2WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**\*MAKE \_\_\_\_\_ MODEL 4WD CA/WB as noted above \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_**

FUEL MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_ ENGINE SIZE \_\_\_\_\_ HP \_\_\_\_\_ E-85 COMPATIBLE? \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item #15**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

**Option 15A.1 Mounted 12' platform body meeting Specification E1320DRW**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 15A.2 Mounted 12' aluminum platform body meeting Specification E1320DRW  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

**Option 15B.1 Mounted 11' platform dump body meeting Specification E1327**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

- Option 15B.2**    **Mounted 11' aluminum platform dump body meeting Specification E1327  
(Minimum 1 1/4" aluminum extruded floor instead of steel)**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 15C.**    **Permanently installed bulkhead to fit truck application  
(minimum requirement to top of cab)** EACH \$ \_\_\_\_\_
- Option 15D.**    **Provide live hydraulics with under hood clutch pump. Pump shall be cast iron design capable of 3500 PSI; aluminum pumps will not be accepted. Reservoir shall be 15 gallon with filtered breather cap, suction strainer, sight gauge and in tank return filter rated to 25 GPM. Control valve shall be 3 section mobile stack valve for hoist, plow and spreader. Valve shall be 12VDC activated capable of a minimum 12 GPM and installed in a valve enclosure. Control valve must have a main relief and a relief for the hoist down function. The hoist, plow and spreader functions shall be controlled by a Certified Power Freedom 2.0 12VDC control console with automated spreading for mounted dump body in specification E1335 or mounted platform body in specification E1327. This package shall be capable of driving the auger, spinner motor in a salt spreader, and power to raise angle plow. All hoses shall be provided from front to rear of truck.** EACH \$ \_\_\_\_\_
- Option 15E.**    **Hydraulic system to run body, plow and spreader, hoist and plow controls to be manual cable controlled and the spreader control shall be a Certified Power Freedom 2.0 automated spreader control. The hydraulic system requirements shall match the 16D specifications.** EACH \$ \_\_\_\_\_
- Option 15F.**    **Provide hydraulics and controls 12VDC activated for dump hoist only** EACH \$ \_\_\_\_\_
- Option 15G.**    **Mounted standard utility tool body.  
Acceptable makes and models are:  
Knapheide 6132D54J                      Stahl CHALLENGER II 132 VVD-54  
Reading CLASSIC II 132A DW           RKI L84DW94  
Omaha 132D54V**
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess.**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_
- Option 15H.**    **Mounted *fiberglass* composite utility tool body.  
Acceptable makes and models are:  
Brand FX Composite Service Body (Model 84LS)  
Equivalentents accepted if pre-approved at least 5 working days before bid opening.**
- Body to include flush mounted LED tail, stop, turn, backup and clearance lights as required per FMVSS 108 standards. Unit must include a tread plate step bumper with pintle hook recess**
- MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 15I.	Six - 2" deep full width 250 lbs. capacity free sliding tool drawers mounted approximately 1 1/2" from top of compartment with approximately 2 1/2" between trays in lieu of three shelves and dividers in one of the full height vertical compartments	EACH \$ _____
Option 15J.	Two full length 250 lbs. capacity free sliding tool trays with metal dividers with slots on 4" centers with first tray mounted 5 1/4 " from bottom of compartment with approximately 1 1/2" between trays with second tray mounted above first in lieu of shelf and dividers in one of the horizontal compartments	EACH \$ _____
Option 15K.	Flip top for Utility Body: Top of compartment opens for storage. Can be either side or both sides. Telescopic roof and crane mounting kit will impact flip top application. Latch is located in center horizontal compartment	EACH \$ _____
Option 15L.	Minimum 25" high panel extension cover with minimum 42" locking rear doors which will provide a minimum 48" interior height for storage and work area (Canopy roof style).	EACH \$ _____
Option 15M.	Body to have 3 section, tempered steel telescopic sliding roof and two piece, rigid aluminum, endgate cover to protect cargo area from weather and theft. A mechanical type seal will be placed on the telescopic sliding roof and end gate cover	EACH \$ _____
Option 15N.	Raise Telescopic Roof to get 36" clearance for the above option	EACH \$ _____
Option 15O.	Crane mount reinforced rigidly while maintaining full compartment space on top rear corner of body either left or right for a 3500 lbs. cap. crane (with no mounting holes or bolt holes, we will drill to suit ourselves)	EACH \$ _____
Option 15P.	One - double bottle gas drop well with minimum 55" clearance height (for large bottle use) and retainers in lieu of the interior 48" full height vertical compartment	EACH \$ _____
Option 13Q.	Heavy duty, Class V (2-1/2 "square tube) receiver trailer hitch. Includes an adapter to reduce to 2" (Class III/IV), a seven - wire RV style trailer plug and electric brake controller	EACH \$ _____
Option 15R.	Exterior color to be Federal Standard #595C "DOT Highway Yellow"	EACH \$ _____
Option 15S.	Automatic transmission power take-off provision	EACH \$ _____
Option 15T.	2 Full-length cab steps or running boards. (one on drivers side, one on passenger side)	SET \$ _____
Option 15U.	Optional Rear Axle Ratio                      Axle Ratio _____	EACH \$ _____
Option 15V.	Limited Slip Rear Axle.                      Axle Ratio _____	EACH \$ _____
Option 15W.	Commercial grade spray on bed lining to be applied in the cargo area of the utility body, to include floor, sides tailgate, front, and horizontal surface of bumper	EACH \$ _____
Option 15X.	Bluetooth Capability	EACH \$ _____



**Item #16 – New standard equipped 2017 or Newer Model 15 Passenger Van**

**ACCEPTABLE MAKES AND MODELS:**

Ford Transit Wagon Wheelbase 148" with Extended Body

Chevrolet / GMC Model Extended Wheelbase 155" Model G33706

**All units bid must contain the following options:**

1. Standard minimum gas engine (Size\_\_\_\_\_ Horsepower\_\_\_\_\_)
2. Manufacturer's standard rear end axle ratio (Ratio: \_\_\_\_\_)
3. Automatic Transmission (Speeds\_\_\_\_\_)
4. Factory installed front and rear heat/air conditioning
5. LH & RH manual mirrors
6. Tires:(4) Minimum 10 ply light truck, highway all season, plus standard size spare and wheel (Size\_\_\_\_\_)
7. Deep tinted windows (privacy glass)
8. Brakes, 4-wheel anti-lock braking system (ABS)
9. Daytime running lights
10. Speed control and tilt wheel
11. Vinyl/Rubber Flooring
12. Minimum GVWR 9000 lb
13. Vinyl seats
14. 2 sets of keys

**DEALER COMPLETE IN DETAIL:**

MAKE \_\_\_\_\_ MODEL \_\_\_\_\_ GVWR \_\_\_\_\_ EACH \$ \_\_\_\_\_

GAS MPG: CITY \_\_\_\_\_ HWY \_\_\_\_\_

**OPTIONAL EQUIPMENT PRICES, Item #16**

Indicate the cost or deduction for the below listed options. Price should include all required options and special equipment.

Option 16A. Sliding side door EACH \$ \_\_\_\_\_

Option 16B. Exterior color to be Federal Standard #595C "DOT Highway Yellow" EACH \$ \_\_\_\_\_

Option 16C. Bluetooth Capability EACH \$ \_\_\_\_\_

Option 16D. Back-up Camera EACH \$ \_\_\_\_\_

Option 16E. Larger gas engine Size\_\_\_\_\_ HP \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 16F. Diesel engine in lieu of standard gas engine Size\_\_\_\_\_ HP \_\_\_\_\_ EACH \$ \_\_\_\_\_

Option 16G. Additional set of keys (Ignition and door locks) EACH \$ \_\_\_\_\_

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all vehicle options available in your data book or pricing guides.

% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_

Delivery will be made approximately \_\_\_\_\_ days after receipt of order.



## **RFB 3-170105TV Snow Removal Equipment Options**

**These items may be bid directly by the supplier.**

### **Electric/Hydraulic Plows**

**Item A – 7' 6" Electric/Hydraulic Front End Snow Plow**

**EACH \$ \_\_\_\_\_**

Minimum 12 gauge construction

In cab command with on/off switch

Light Kit

Note: Compatible with Items 1, 2 & 3

**Item B – 8' Electric/Hydraulic Front End Snow Plow**

**EACH \$ \_\_\_\_\_**

Minimum 12 gauge construction

In cab command with on/off switch

Light Kit

Note: Compatible with Items 1, 2 & 3

**Item C – 8' 6" Electric/Hydraulic Front End Snow Plow**

**EACH \$ \_\_\_\_\_**

Minimum 12 gauge construction

In cab command with on/off switch

Light Kit

Note: Compatible with Items 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 & 15

### **Hydraulic Plows**

**Item D – 8'6" Hydraulic Front End Snow Plow**

**EACH \$ \_\_\_\_\_**

Minimum 12 gauge construction

In cab command

Quick couplers for all hose connections

Light Kit

Note: Central Hydraulics option needed for this item

Note: Compatible with Items 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 & 15

**Item E – 9' Hydraulic Front End Snow Plow**

**EACH \$ \_\_\_\_\_**

Minimum 12 gauge construction

In cab command

Quick couplers for all hose connections

Light Kit

Note: Central Hydraulics option needed for this item

Note: Compatible with Items 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 & 15

### **Stainless Steel Salt Spreader**

**Item F – 9' Stainless Steel Salt Spreader (3.5 cubic yard capacity)**

**Electric power EACH \$ \_\_\_\_\_**

Note: Compatible with Items 7, 8, 9, 10, 11, 12, 13, 14 & 15

**Hydraulic power EACH \$ \_\_\_\_\_**

**Gas engine power EACH \$ \_\_\_\_\_**

**Item G – 10' Stainless Steel Salt Spreader (4.5 cubic yard capacity)**

**Electric power EACH \$ \_\_\_\_\_**

Note: Compatible with Items 12 and 15

**Hydraulic power EACH \$ \_\_\_\_\_**

**Gas engine power EACH \$ \_\_\_\_\_**

Please indicate below the percent (%) discount off Manufacturer's Suggested Retail Prices (MSRP) for all plow/spreader/bed items, options or accessories available in your data book or pricing guides that were not specifically included in this bid.

**% discount off MSRP for all Data Book or Pricing Guide Options: - % Discount \_\_\_\_\_**

**Delivery will be made approximately \_\_\_\_\_ days after receipt of order.**

## **Body Equipment Supplier Information**

For each Body Company Supplier that is included in Bid Items 1 - 15, please complete below the location of the service center(s), company contact information and any available MSRP discount % for the purchase of any additional equipment options or accessories for the equipment that is to be provided.

Body Company\_\_\_\_\_

Service Location(s)\_\_\_\_\_

Contact Name\_\_\_\_\_ Contact Number\_\_\_\_\_

Supplier Offered Discount off MSRP Data Book or Pricing Guide Options - % Discount \_\_\_\_\_

Body Company\_\_\_\_\_

Service Location(s)\_\_\_\_\_

Contact Name\_\_\_\_\_ Contact Number\_\_\_\_\_

Supplier Offered Discount off MSRP Data Book or Pricing Guide Options - % Discount \_\_\_\_\_

Body Company\_\_\_\_\_

Service Location(s)\_\_\_\_\_

Contact Name\_\_\_\_\_ Contact Number\_\_\_\_\_

Supplier Offered Discount off MSRP Data Book or Pricing Guide Options - % Discount \_\_\_\_\_

Body Company\_\_\_\_\_

Service Location(s)\_\_\_\_\_

Contact Name\_\_\_\_\_ Contact Number\_\_\_\_\_

Supplier Offered Discount off MSRP Data Book or Pricing Guide Options - % Discount \_\_\_\_\_

## 5. VENDOR INFORMATION & PREFERENCE CERTIFICATION FORM

### Vendor Information

All bidders must furnish **ALL** applicable information requested below

<b>Vendor Name/Mailing Address:</b>  Email Address:	<b>Vendor Contact Information (including area codes):</b> Phone #: Cellular #: Fax #:
<b>Printed Name of Responsible Officer or Employee:</b>	<b>Signature:</b>
<b>For Corporations</b> - State in which incorporated:	<b>For Others</b> - State of domicile:
If the address listed in the Vendor Name/Mailing Address block above is not located in the State of Missouri, list the address of Missouri offices or places of business:  <i>If additional space is required, please attach an additional sheet and identify it as <b>Addresses of Missouri Offices or Places of Business.</b></i>	
<b>M/WBE INFORMATION:</b> List all certified Minority or Women Business Enterprises ( <b>M/WBE</b> ) utilized in the fulfillment of this bid. Include <u>percentages</u> for subcontractors and identify the M/WBE certifying agency:  <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <span><u>M/WBE Name</u></span> <span><u>Percentage of Contract</u></span> <span><u>M/WBE Certifying Agency</u></span> </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <span>_____</span> <span>_____</span> <span>_____</span> </div> <div style="display: flex; justify-content: space-between; margin-top: 10px;"> <span>_____</span> <span>_____</span> <span>_____</span> </div>	
<i>If additional space is required, please attach an additional sheet and identify it as <b>M/WBE Information</b></i>	

### Preference Certification

All bidders must furnish **ALL** applicable information requested below

<b>GOODS/PRODUCTS MANUFACTURED OR PRODUCED IN USA:</b> If any or all of the goods or products offered in the attached bid which the bidder proposes to supply to the MHTC are <b>not</b> manufactured or produced in the "United States", or imported in accordance with a qualifying treaty, law, agreement, or regulation, list below, by item or item number, the country other than the United States where each good or product is manufactured or produced.	
Item (or item number)	Location Where Item is Manufactured or Produced
<i>If additional space is required, please attach an additional sheet and identify it as <b>Location Products are Manufactured or Produced.</b></i>	
<b>MISSOURI SERVICE-DISABLED VETERAN BUSINESS:</b> Please complete the following if applicable. Additional information may be requested if preference is applicable. See below definitions for qualification criteria:  <b>Service-Disabled Veteran</b> is defined as any individual who is disabled as certified by the appropriate federal agency responsible for the administration of veterans' affairs.  <b>Service-Disabled Veteran Business</b> is defined as a business concern: <div style="margin-left: 20px;">           a. Not less than fifty-one (51) percent of which is owned by one or more service-disabled veterans or, in the case of any publicly owned business, not less than fifty-one (51) percent of the stock of which is owned by one or more service-disabled veterans; and            b. The management and daily business operations of which are controlled by one or more service-disabled veterans.         </div>	
<u>Veteran Information</u>	<u>Business Information</u>
Service-Disabled Veteran's Name (Please Print)	Service-Disabled Veteran Business Name
Service-Disabled Veteran's Signature	Missouri Address of Service Disabled Veteran Business

## **6. NOTICE OF COOPERATIVE PURCHASING**

**MODOT IS INTERESTED IN ASSISTING MISSOURI GOVERNMENTAL ENTITIES, ETC. IN PURCHASING EQUIPMENT, VARIOUS MATERIALS, AND SUPPLIES THAT MEET THE MISSOURI DEPARTMENT OF TRANSPORTATION SPECIFICATIONS.**

Each bidder is asked to indicate below whether they would be willing to offer **medium duty vehicles** listed in the attached "Request for Bid" for sale to these local political entities at the same bid price offered to MoDOT.

It is understood MoDOT will not issue purchase orders, accept delivery nor make payment for these items ordered by any of these agencies. It is further understood the price is based on the medium duty vehicle meeting MoDOT specifications. Any added options, deletions, or extra freight costs would be negotiated between the local agency and the successful vendor.

Indicate below whether your company is willing to offer such cooperative purchasing for Missouri counties, cities or other political entities.

YES \_\_\_\_\_

NO \_\_\_\_\_

If the price varies throughout the state on MoDOT bids because of different delivery destinations, please indicate the price F.O.B. your location that would be offered as described.

F.O.B. Location \_\_\_\_\_

Indicate the deadline date that orders will be accepted. \_\_\_\_\_

COMPANY NAME \_\_\_\_\_

ADDRESS \_\_\_\_\_

E-MAIL \_\_\_\_\_

PHONE NUMBER \_\_\_\_\_

SIGNATURE \_\_\_\_\_

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

Missouri Highways and Transportation Commission  
Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions

**STANDARD SOLICITATION PROVISIONS**

- a. The solicitation for the procurement of the supplies referenced therein, to which these "Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions" are attached, is being issued under, and governed by, the provisions of Title 7 – Missouri Department of Transportation, Division 10 – Missouri Highways and Transportation Commission, Chapter 11 – Procurement of Supplies, of the Code of State Regulations. The Missouri Highways and Transportation Commission (**MHTC**), acting by and through its operating arm, the Missouri Department of Transportation (**MoDOT**), draws the Bidder's attention to said 7 CSR 10-11 for all the provisions governing solicitation and receipt of bids/quotes and the award of the contract pursuant to this solicitation.
- b. All bids/quotes must be signed with the firm name and by a responsible officer or employee. Obligations assumed by such signature must be fulfilled.

**GENERAL TERMS AND CONDITIONS**

**Definitions**

Capitalized terms as well as other terms used but not defined herein shall have the meaning assigned to them in section 7 CSR 10-11.010 Definition of Terms.

**Nondiscrimination**

- a. The Contractor shall comply with all state and federal statutes applicable to the Contractor relating to nondiscrimination, including, but not limited to, Chapter 213, RSMo; Title VI and Title VII of Civil Rights Act of 1964 as amended (42 U.S.C. Sections 2000d and 2000e, *et seq.*); and with any provision of the "Americans with Disabilities Act" (42 U.S.C. Section 12101, *et seq.*).
- b. **Sanctions for Noncompliance:** In the event of the Contractor's noncompliance with the nondiscrimination provisions of this contract, MHTC shall impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to:
  - i. withholding of payments to the Contractor under the contract until the Contractor complies, and/or,
  - ii. cancellation, termination or suspension of the contract, in whole or in part.

**Contract/Purchase Order**

- a. By submitting a bid/quote, the Bidder agrees to furnish any and all equipment, supplies and/or services specified in the solicitation documents, at the prices quoted, pursuant to all requirements and specifications contained therein.
- b. A binding contract shall consist of: (1) the solicitation documents, amendments thereto, and/or Best and Final Offer (BAFO) request(s) with any changes/additions, (2) the Contractor's bid response, and (3) the MHTC's acceptance of the bid by post-award contract or purchase order.
- c. A notice of award does not constitute an authorization for shipment of equipment or supplies or a directive to proceed with services. Before providing equipment, supplies and/or services, the Contractor must receive a properly authorized notice to proceed and/or purchase order.

**Applicable Laws and Regulations**

- a. The contract shall be construed according to the laws of the State of Missouri. The Contractor shall comply with all local, state, and federal laws and regulations related to the performance of the contract. The exclusive venue for any legal proceeding relating to or arising, out of the contract shall be in the Circuit Court of Cole County, Missouri.
- b. The Contractor must be registered and maintain good standing with the Secretary of State of the State of Missouri, Missouri Department of Revenue, and other regulatory agencies, as may be required by law or regulations. Prior to the issuance of a purchase order and/or notice to proceed, the Contractor may be required to submit to MHTC a copy of their current Authority Certificate from the Secretary of State of the State of Missouri and/or a copy of their Certificate of No Tax Due from the Missouri Department of Revenue.
- c. Prior to the issuance of a purchase order and/or notice to proceed, all **out-of-state** Contractors **providing services** within the state of Missouri must submit to MHTC a copy of their current Transient Employer Certificate from the Missouri Department of Revenue, in addition to a copy of their current Authority Certificate from the Secretary of State of the State of Missouri.

**Executive Order:**

The Contractor shall comply with all the provisions of Executive Order 07-13, issued by the Honorable Matt Blunt, Governor of Missouri, on the sixth (6<sup>th</sup>) day of March, 2007. This Executive Order, which promulgates the State of Missouri's position to not tolerate persons who contract with the state engaging in or supporting illegal activities of employing individuals who are not eligible to work in the United States, is incorporated herein by reference and made a part of this Agreement.

- 1) "By signing this Agreement, the Contractor hereby certifies that any employee of the Contractor assigned to perform services under the contract is eligible and authorized to work in the United States in compliance with federal law."
- 2) In the event the Contractor fails to comply with the provisions of the Executive Order 07-13, or in the event the Commission has reasonable cause to believe that the contractor has knowingly employed individuals who are not eligible to work in the United States in violation of federal law, the Commission reserves the right to impose such contract sanctions as it may determine to be appropriate, including but not limited to contract cancellation, termination or suspension in whole or in part or both.
- 3) The Contractor shall include the provisions of this paragraph in every subcontract. The Contractor shall take such action with respect to any subcontract as the Commission may direct as a means of enforcing such provisions, including sanctions for noncompliance.

**Preferences**

- a. In the evaluation of bids/quotes, preferences shall be applied in accordance with 7 CSR 10-11.020(7). Contractors should apply the same preferences in selecting subcontractors. The attached document entitled "**VENDOR INFORMATION AND PREFERENCE CERTIFICATION FORM**" must be completed and returned with the solicitation documents.
- b. Bidders are encouraged to obtain minority business enterprise (MBE) and women business enterprise (WBE) participation in this work through the use of subcontractors, suppliers, joint ventures, or other arrangements that afford meaningful participation for M/WBEs. Bidders are encouraged to obtain 10% MBE and 5% WBE participation.

Missouri Highways and Transportation Commission  
Standard Bid Provisions, General Terms and Conditions and Special Terms and Conditions

**Cancellation of Contract**

The MHTC may cancel the Contract at any time for a material breach of contractual obligations or for convenience by providing Contractor with written notice of cancellation. Should the MHTC exercise its right to cancel the contract for such reasons, cancellation will become effective upon the date specified in the notice of cancellation sent to the Contractor.

**Bankruptcy or Insolvency**

Upon filing for any bankruptcy or insolvency proceeding by or against the Contractor, whether voluntarily, or upon the appointment of a receiver, trustee, or assignee, for the benefit of creditors, the Commission reserves the right and sole discretion to either cancel the Agreement or affirm the Agreement and hold the Contractor responsible for damages.

**Warranty**

The Contractor expressly warrants that all equipment, supplies, and/or services provided shall: (1) conform to each and every specification, drawing, sample or other description which was furnished to or adopted by the MHTC, (2) be fit and sufficient for the purpose expressed in the solicitation documents, (3) be merchantable, (4) be of good materials and workmanship, and (5) be free from defect.

**Status of Independent Contractor**

The Contractor represents itself to be an independent Contractor offering such services to the general public and shall not represent itself or its employees to be an employee of the MHTC. Therefore, the Contractor shall assume all legal and financial responsibility for taxes, FICA, employee fringe benefits, workers' compensation, employee insurance, minimum wage requirements, overtime, etc., and agrees to indemnify, save and hold the MHTC, its officers, agents and employees harmless from and against any and all losses (including attorney fees) and damage of any kind related to such matters.

**Non-Waiver**

If one of the parties agrees to waive its right to enforce any term of this Contract, that party does not waive its right to enforce such term at any other time or to enforce any or all other terms of this Contract.

**Indemnification**

The Contractor shall defend, indemnify and hold harmless MHTC, including its members and department employees, from any claim or liability whether based on a claim for damages to real or personal property or to a person for any matter relating to or arising out of the Contractor's performance of its obligations under the contract awarded pursuant to this solicitation.

Missouri Highways and Transportation Commission  
Standard Bid/Proposal Provisions, General Terms and Conditions and Special Terms and Conditions

**SPECIAL TERMS AND CONDITIONS**

**Tax Exempt Status:**

MHTC is exempt from paying Missouri Sales Tax, Missouri Use Tax and Federal Excise Tax. However, the Contractor may themselves be responsible for the payment of taxes on materials they purchase to fulfill the contract. A Project Tax Exemption Certificate will be furnished to the successful Bidder upon request if applicable.

**Liquidated Damages**

- a. In the event the successful Contractor fails to deliver the material within the time specified, the Department and the public will sustain damages because of such delay in delivery, the exact extent of which would be difficult to ascertain, and in order to liquidate such damage in advance it is agreed that the **sum of \$50 per day, per item**, for each assessable calendar day on which the delivery has not been completed, is reasonable and the best estimate which the parties can arrive at as liquidated damages, and it is therefore agreed that said amount will be withheld from payments due the Contractor or otherwise collected from the Contractor as liquidated damages.
- b. **Saturdays, Sundays, holidays and days whereas the Department has suspended work** shall not be assessable days.