

105 West Capitol Avenue P.O. Box 270 Jefferson City, Missouri 65102

Missouri Department of Transportation Patrick K. McKenna. Director 573.751.2551 Fax: 573.751.6555 1.888.ASK MODOT (275.6636)

ADDENDUM 001 Transit Vehicles – Narrow Body Cutaway Request for Bid 3-160824TVB

Bidders should acknowledge receipt of Addendum 001 (ONE) by **signing** and **including it** with the original bid. The due date for receipt of bids has been extended to **August 31, 2016** @ **12:30pm** by this Addendum. Accordingly, the following clarifications are believed to be of general interest to all potential bidders. All other terms and conditions remain unchanged and in full force.

Name and Title of Signer (Print or type)	Name and Title of Department Authority	
	Name: Tom Veasman Title: Sr. General Services Specialist	
Contractor/Bidder Signature	Department of Transportation	
(Signature of person authorized to sign)	(Authorizing Signature)	
Date Signed:	Date Signed:8-/0-//	

ADDENDUMS AND CLARIFICATIONS
TRANSIT VEHICLES 2017 MODEL YEAR

The due date for receipt of bids has been extended to Wednesday, August 31, 2016 at 12:30 PM at the same location as given in the Request for Bid. The deadline for receipt of questions is Wednesday, August 17, 2016 at 2:00 PM. If an addendum is necessary after the deadline for questions, it is anticipated that it will be issued by noon on Thursday, August 18, 2016.

3-160824TVB - Narrow Body Cutaway

CHANGES TO SPECIFICATIONS:

Remove:

Wheelchairs and mobility aids must be oriented as follows:

• For vehicles greater than 22 feet in length, at least one securement position must be forward facing. Other securement areas can be either forward or rear facing. Note – MoDOT only specifies forward facing securement positions.

Replace with:

Wheelchairs and mobility aids must be oriented as follows:

• For vehicles greater than 22 feet in length, at least two securement positions must be forward facing. Other securement areas can be either forward or rear facing. Note – MoDOT only specifies forward facing securement positions.

Remove:

Clipboard:

Mounted clipboard within drivers reach.

Remove:

Batteries (2):

HD with adequate CCA and reserve capacity (Minimum 600 CCA) each for operating chassis and wheelchair lift components. One battery will be relocated so access can be gained through a door on the passenger side of the bus. Battery will be mounted on a slide out-tray to allow easy access. This tray will be sealed to prevent road debris from entering but also vented well enough to allow gases to escape. Stepwell mounted batteries are also acceptable.

Replace with:

Batteries (2):

HD with adequate CCA and reserve capacity (Minimum 625 CCA) each for operating chassis and wheelchair lift components. One battery will be relocated so access can be gained through a door on the passenger side of the bus. Battery will be mounted on a slide out-tray to allow easy access. This tray will be sealed to prevent road debris from entering but also vented well enough to allow gases to escape. Stepwell mounted batteries are also acceptable.

Remove:

Tires:

Tires will be a major brand (not Firestone), factory installed, metric sized, and meeting manufacturer's specifications. Seven (front, rear and spare), approximate size 225/75R 16E blackwall tubeless or tube type highway tread. Spare tire and wheel will be furnished. Spare tire is to be permanently mounted under vehicle unless weight or fuel tank is an issue. If tire is not mounted under vehicle, the exhaust will be discharged out driver's side. All tires including spare to meet or exceed GVW requirements, and be of radial design. A jack (rated for vehicle GVW) and all tire changing tools will

Addendum 001 RFB 3-160824TVB be included with vehicle. All tire changing tools will be securely mounted anywhere in the passenger compartment, as long as they do not impede operation or safety. The jack and tire tools may be chassis supplied OEM. Tire size may be 225/75R 16D, 8 ply rating. Tires will be mounted so air pressure can be easily checked on ALL tires. Tire valve stem extenders will be installed so operators can check tire pressure on BOTH rear duals with gauge while kneeling by rear tires.

Replace with:

Tires:

Tires will be a major brand, factory installed, standard OEM sized, and meeting manufacturer's specifications. Spare tire and wheel will be furnished. Spare tire is to be mounted on rim and mounted on a tire carrier (lockable) under the rear of the vehicle unless weight, fuel tank or discharge of exhaust out driver's side of vehicle is an issue. In this case, spare tire shall be shipped loose. All tires including spare to meet or exceed GVW requirements, and be of radial design. A jack (rated for vehicle GVW) and all tire changing tools will be included with vehicle. All tire changing tools will be securely mounted anywhere in the passenger compartment, as long as they do not impede operation or safety. The jack and tire tools may be chassis supplied OEM. Tires will be mounted so air pressure can be easily checked on ALL tires. Tire valve stem extenders will be installed so operators can check tire pressure on BOTH rear duals with gauge while kneeling by rear tires.

Remove:

On-Site Repair Calls: After the final acceptance of the delivered vehicle (which includes the thorough inspection and verification of equipment ordered and condition of the vehicle), and during the 3 year/36,000 miles after delivery bumper-to-bumper warranty period, the purchasing agency is allowed a maximum of two "on-site repair calls" as follows: if warranty work is required that cannot be repaired through normal efforts by a local dealer at the purchasing agency's location, the purchasing agency will call the vendor, and the vendor must either:

Replace with:

On-Site Repair Calls: After the final acceptance of the delivered vehicle (which includes the thorough inspection and verification of equipment ordered and condition of the vehicle), and during the 3 year/36,000 miles after delivery bumper-to-bumper warranty period, the purchasing agency is allowed a maximum of two "on-site repair calls" as follows: if warranty work is required that cannot be repaired through normal efforts by a local OEM dealership within a 50 mile radius of the vehicles assigned home or regional office, the purchasing agency will call the vendor, and the vendor must either:

Add:

Power-Inverter 12V to 110V: Shall be OEM Standard.

Add:

USB Ports:

Shall be located in both the instrument panel and rear passenger area of vehicle.

Addendum 001 RFB 3-160824TVB Page 3

Add:

Back-up Alarm:

• Back-Up Warning Device: Shall be equipped with an audible warning device in compliance with SAEJ994b that is activated when the vehicle transmission is engaged in reverse and continues as the vehicle is being backed up. This should be located behind the rear axle of the vehicle and all wires must be enclosed and secured. An audible adjustable signal, with a minimum range of 87 dBA, shall be included.

Options:

Remove:

1) REI COS Camera System, Safety Vision SV 5000, Backing Vision BV 1350, Angeltrax GDA-7010 (or approved equal) backing vision system. The backing display may be integrated into the interior rear view mirror as long as that mirror conforms to the existing dimensional specification for the interior rear view mirror of approximate 6" x 12", 8" convex is acceptable.

Replace with:

2) Backing vision system. The backing display shall be integrated into the interior rear view mirror and conform to the existing dimensional specification for the interior rear view mirror of approximate 6" x 12", 8" convex.

CHANGES TO TERMS & CONDITIONS:

FTA and Standard Agreements

Remove:

Incorporation of Federal Transit Administration (FTA) Terms - The preceding provisions include, in part, certain Standard Terms and Conditions required by DOT, whether or not expressly set forth in the preceding contract provisions. All contractual provisions required by DOT, as set forth in FTA Circular 4220.1E are hereby incorporated by reference. Anything to the contrary herein notwithstanding, all FTA mandated terms shall be deemed to control in the event of a conflict with other provisions contained in this Agreement. The Contractor shall not perform any act, fail to perform any act, or refuse to comply with any (name of grantee) requests which would cause (name of grantee) to be in violation of the FTA terms and conditions.

Replace with:

Incorporation of Federal Transit Administration (FTA) Terms - The preceding provisions include, in part, certain Standard Terms and Conditions required by DOT, whether or not expressly set forth in the preceding contract provisions. All contractual provisions required by DOT, as set forth in FTA Circular 4220.1E are hereby incorporated by reference. Anything to the contrary herein notwithstanding, all FTA mandated terms shall be deemed to control in the event of a conflict with other provisions contained in this Agreement. The Contractor shall not perform any act, fail to perform any act, or refuse to comply with any Missouri Department of Transportation requests which would cause Missouri Department of Transportation to be in violation of the FTA terms and conditions.

FTA and Standard Agreements

Remove:

<u>Americans With Disabilities Act Accessibility Standards</u> - The Bidder hereby certifies that the vehicle bid, if so required by the specifications, has been modified and equipped in accordance with all accessible requirements and standards as required by the American With Disabilities Act of 1990, 49 CFR Part 38 (Appendix A Subsection G, "Van and Small Buses").

Replace with:

<u>ADA Accessibility</u> - Contractor agrees that coaches will be designed and constructed in accordance with the Americans with Disabilities Act of 1990 (ADA), as amended, 42 U.S.C. Sections 12101 et seq., which requires that services be made available to individuals with disabilities, and with applicable implementing Federal regulations, including 49 CFR Part 38 "Americans with Disabilities (ADA) Accessibility Specifications for Transportation Vehicles."

CHANGES TO PRICING PAGES:

Remove the **PRICING PAGES** from the Request for Bid and **Replace** with the attached **REVISED PRICING PAGE**. The REVISED PRICING PAGE includes revised language for the Options.

.

4. REVISED PRICING PAGE

	nipped (MAKE & MODEL)	ached Missouri Department of T	ransportation Specification
Questions concern	ning specifications should be directed	to Dion Knipp at (573) 751-252	3.
PURCHASE ORI	DERS MAY BE ISSUED FOR VAR	IOUS ORGANIZATIONS IN TI	HE STATE OF MISSOURI.
	T DELIVERED PRICE, MEETING T IN THE STATE OF MISSOURI.	THE ATTACHED SPECIFICAT	IONS, TO ANY
Floor Plan MM	\$	_ Per Unit	
Floor Plan QQ	\$	_Per Unit	
Floor Plan SS	\$ <u></u>	_Per Unit	
Option 1: Backi	ing vision system	Price \$	Per Unit
Option 2: Four	(4) camera video recording system	Price \$	Per Unit
Option 3: Overl	head storage shelf	Price \$	Per Unit
Option 4: Single	e Integrated Child Seat	Price \$	Per Unit
Option 5: Whee	lchair lift mounted – 1,000 lb capac	city Price \$	Per Unit
at the time of rene	RCENTAGE INCREASE FOR REAL wal (maximum to be determined by a percentages are not provided, the price	pplying % to current contract pri	ices at time of renewal). If
Maximum % of i	ncrease for: First Renewal	Second Renewal	Third Renewal
Delivery will be m	nade	days after receipt of order.	
Name of the Bidde Addendum 00 RFB 3-160824	1	zed Representative	Date Signed

Page 6