

105 West Capitol Avenue P.O. Box 270 Jefferson City, Missouri 65102

Missouri Department of Transportation Patrick K. McKenna, Director 573.751.2551 Fax: 573.751.6555 1.888.ASK MODOT (275.6636)

ADDENDUM 001 Transit Vehicles – Light Duty Cutaway - Wide Body Request for Bid 3-160824TVC

Bidders should acknowledge receipt of Addendum 001 (ONE) by **signing** and **including it** with the original bid. The due date for receipt of bids has been extended to **August 31, 2016** @ **12:30pm** by this Addendum. Accordingly, the following clarifications are believed to be of general interest to all potential bidders. All other terms and conditions remain unchanged and in full force.

| Name and Title of Signer (Print or type) | Name and Title of Department Authority |
|--|---|
| | Name: Tom Veasman Title: Sr. General Services Specialist |
| Contractor/Bidder Signature | Department of Transportation |
| (Signature of person authorized to sign) | Jon Veasman (Authorizing Signature) |
| Date Signed: | Date Signed: 8-10-16 |

ADDENDUMS AND CLARIFICATIONS TRANSIT VEHICLES 2017 MODEL YEAR

The due date for receipt of bids has been extended to Wednesday, August 31, 2016 at 12:30 PM at the same location as given in the Request for Bid. The deadline for receipt of questions is Wednesday, August 17, 2016 at 2:00 PM. If an addendum is necessary after the deadline for questions, it is anticipated that it will be issued by noon on Thursday, August 18, 2016.

CHANGE TO REQUEST FOR BID:

Remove:

3.1.1 All bids must be received in a sealed envelope/packaging clearly marked "3-160824TVB – Transit Vehicles - Light Duty Cutaway – Wide Body"

Replace:

3.1.1 All bids must be received in a sealed envelope/packaging clearly marked "3-160824TVC - Transit Vehicles - Light Duty Cutaway - Wide Body"

CHANGES TO SPECIFICATIONS:

Remove:

Wheelchairs and mobility aids must be oriented as follows:

• For vehicles greater than 22 feet in length, at least one securement position must be forward facing. Other securement areas can be either forward or rear facing. Note – MoDOT only specifies forward facing securement positions.

Replace with:

Wheelchairs and mobility aids must be oriented as follows:

• For vehicles greater than 22 feet in length, at least two securement positions must be forward facing. Other securement areas can be either forward or rear facing. Note – MoDOT only specifies forward facing securement positions.

Remove:

Clip Board Holder:

Shall be mounted within drivers reach.

Remove:

Batteries (2):

HD with adequate CCA and reserve capacity (Minimum 625 CCA) each for operating chassis and wheelchair lift components. One battery will be relocated so access can be gained through a door on the passenger side of the bus. Battery will be mounted on a slide out-tray to allow easy access. This tray will be sealed to prevent road debris from entering. This battery tray may need to be relocated in CNG applications due to undercarriage space limitations in order to accommodate the CNG fuel tanks.

Replace with:

Batteries (2):

HD with adequate CCA and reserve capacity (Minimum 625 CCA) each for operating chassis and wheelchair lift components. One battery will be relocated so access can be gained through a door on the passenger side of the bus. Battery will be mounted on a slide out-tray to allow easy access. This

Addendum 001 RFB 3-160824TVC

Page 2

tray will be sealed to prevent road debris from entering. This battery tray may need to be relocated in CNG applications due to undercarriage space limitations in order to accommodate the CNG fuel tanks. Stepwell mounted batteries are also acceptable.

Remove:

Tires:

Tires will be a major brand (not Firestone), factory installed, metric sized, and meeting manufacturer's specifications. Seven (front, rear and spare), approximate size 225/75R 16E blackwall tubeless or tube type highway tread. Spare tire and wheel will be furnished. Spare tire is to be permanently mounted under vehicle unless weight or fuel tank is an issue. If tire is not mounted under vehicle, the exhaust will be discharged out driver's side. All tires including spare to meet or exceed GVW requirements, and be of radial design. A jack (rated for vehicle GVW) and all tire changing tools will be included with vehicle. All tire changing tools will be securely mounted anywhere in the passenger compartment, as long as they do not impede operation or safety. The jack and tire tools may be chassis supplied OEM. Tire size may be 225/75R 16D, 8 ply rating. Tires will be mounted so air pressure can be easily checked on ALL tires. Tire valve stem extenders will be installed so operators can check tire pressure on BOTH rear duals with gauge while kneeling by rear tires.

Replace with:

Tires:

Tires will be a major brand, factory installed, standard OEM sized, and meeting manufacturer's specifications. Spare tire and wheel will be furnished. Spare tire is to be mounted on rim and mounted on a tire carrier (lockable) under the rear of the vehicle unless weight, fuel tank or discharged of exhaust out driver's side of vehicle is an issue. In this case, spare tire shall be shipped loose. All tires including spare to meet or exceed GVW requirements, and be of radial design. A jack (rated for vehicle GVW) and all tire changing tools will be included with vehicle. All tire changing tools will be securely mounted anywhere in the passenger compartment, as long as they do not impede operation or safety. The jack and tire tools may be chassis supplied OEM. Tires will be mounted so air pressure can be easily checked on ALL tires. Tire valve stem extenders will be installed so operators can check tire pressure on BOTH rear duals with gauge while kneeling by rear tires.

Remove:

On-Site Repair Calls: After the final acceptance of the delivered vehicle (which includes the thorough inspection and verification of equipment ordered and condition of the vehicle), and during the 3 year/36,000 miles after delivery bumper-to-bumper warranty period, the purchasing agency is allowed a maximum of two "on-site repair calls" as follows: if warranty work is required that cannot be repaired through normal efforts by a local dealer at the purchasing agency's location, the purchasing agency will call the vendor, and the vendor must either:

Replace with:

On-Site Repair Calls: After the final acceptance of the delivered vehicle (which includes the thorough inspection and verification of equipment ordered and condition of the vehicle), and during the 3 year/36,000 miles after delivery bumper-to-bumper warranty period, the purchasing agency is allowed a maximum of two "on-site repair calls" as follows: if warranty work is required that cannot be

Addendum 001 RFB 3-160824TVC Page 3 repaired through normal efforts by a local OEM dealership within a 50 mile radius of the vehicles assigned home or regional office, the purchasing agency will call the vendor, and the vendor must either:

Add:

Power-Inverter 12v to 110v: Shall be OEM Standard.

Add:

USB Ports:

Shall be located in both the instrument panel and rear passenger area of vehicle.

Add:

Back-up Alarm:

<u>Back-Up Warning Device</u>: Shall be equipped with an audible warning device in compliance
with SAEJ994b that is activated when the vehicle transmission is engaged in reverse and
continues as the vehicle is being backed up. This should be located behind the rear axle of the
vehicle and all wires must be enclosed and secured. An audible adjustable signal, with a
minimum range of 87 dBA, shall be included.

Options:

Remove:

1) REI COS Camera System, Safety Vision SV 5000, Backing Vision BV 1350, Angeltrax GDA-7010 (or approved equal) backing vision system. The backing display may be integrated into the interior rear view mirror as long as that mirror conforms to the existing dimensional specification for the interior rear view mirror of approximate 6" x 12", 8" convex is acceptable.

Replace with:

2) Backing vision system. The backing display shall be integrated into the interior rear view mirror and conforms to the existing dimensional specification for the interior rear view mirror of approximate 6" x 12", 8" convex.

CHANGES TO TERMS & CONDITIONS:

FTA and Standard Agreements

Remove:

<u>Incorporation of Federal Transit Administration (FTA) Terms</u> - The preceding provisions include, in part, certain Standard Terms and Conditions required by DOT, whether or not expressly set forth in the preceding contract provisions. All contractual provisions required by DOT, as set forth in FTA Circular 4220.1E are hereby incorporated by reference. Anything to the contrary herein

Addendum 001 RFB 3-160824TVC Page 4 notwithstanding, all FTA mandated terms shall be deemed to control in the event of a conflict with other provisions contained in this Agreement. The Contractor shall not perform any act, fail to perform any act, or refuse to comply with any (name of grantee) requests which would cause (name of grantee) to be in violation of the FTA terms and conditions.

Replace with:

Incorporation of Federal Transit Administration (FTA) Terms - The preceding provisions include, in part, certain Standard Terms and Conditions required by DOT, whether or not expressly set forth in the preceding contract provisions. All contractual provisions required by DOT, as set forth in FTA Circular 4220.1E are hereby incorporated by reference. Anything to the contrary herein notwithstanding, all FTA mandated terms shall be deemed to control in the event of a conflict with other provisions contained in this Agreement. The Contractor shall not perform any act, fail to perform any act, or refuse to comply with any Missouri Department of Transportation requests which would cause Missouri Department of Transportation to be in violation of the FTA terms and conditions.

FTA and Standard Agreements

Remove:

Americans With Disabilities Act Accessibility Standards - The Bidder hereby certifies that the vehicle bid, if so required by the specifications, has been modified and equipped in accordance with all accessible requirements and standards as required by the American With Disabilities Act of 1990, 49 CFR Part 38 (Appendix A Subsection G, "Van and Small Buses").

Replace with:

<u>ADA Accessibility</u> - Contractor agrees that coaches will be designed and constructed in accordance with the Americans with Disabilities Act of 1990 (ADA), as amended, 42 U.S.C. Sections 12101 et seq., which requires that services be made available to individuals with disabilities, and with applicable implementing Federal regulations, including 49 CFR Part 38 "Americans with Disabilities (ADA) Accessibility Specifications for Transportation Vehicles."

CHANGES TO PRICING PAGES:

Remove the PRICING PAGES from the Request for Bid and Replace with the attached REVISED PRICING PAGES. The REVISED PRICING PAGES includes revised language for the Options.

4. **REVISED** PRICING PAGES

| New standard equipped Light Duty Cutaway Specification MM-C. | d (MAKE & MODEL) | e attached Missouri Department of Trans | portation |
|--|--|---|------------|
| Questions concerning | specifications should be directed to Dior | n Knipp at (573) 751-2523. | |
| PURCHASE ORDERS | MAY BE ISSUED FOR VARIOUS C | RGANIZATIONS IN THE STATE OF I | MISSOURI. |
| | LIVERED PRICE, MEETING THE AT IE STATE OF MISSOURI. | TACHED SPECIFICATIONS, TO ANY | , |
| Floor Plan CC | \$J | Per Unit | |
| Floor Plan GG | \$ | Per Unit | |
| Floor Plan HH | \$ | Per Unit | |
| Floor Plan II | \$] | Per Unit | |
| OPTIONS: | | | |
| Option 1: Backing | Vision System | Price \$ | _Per Unit |
| Option 2: Four (4) | camera video recording system | Price \$ | _Per Unit |
| Option 3: Overhead storage shelf | | Price \$ | _Per Unit |
| Option 4: Single Int | tegrated Child Seat | Price \$ | _ Per Unit |
| Option 5: ADA Com | pliance Package (Floor Plan CC Only | v) Price \$ | _ Per Unit |

| Option 6: | CNG engine in lieu of gasol | ine engine | Price \$ | Per Unit |
|----------------|--|---------------------|------------------------|--------------------------------|
| | Applicable to Floor Plan Co | C only (provide de | etails as follows): | |
| | ENGINE: SIZE I | HP MAKE_ | | MODEL |
| | TRANSMISSION: MAK | E | MODEL | |
| | CNG TANK: GGE CAPA | .CITY | TANK LOCATIO | N |
| Option 7: | Wheelchair lift mounted – 1 | ,000 lb capacity | Price \$ | Per Unit |
| Delivery will | be made | days a | fter receipt of order. | |
| at the time of | PERCENTAGE INCREASE renewal (maximum to be determate percentages are not provided and. | nined by applying 9 | % to current contract | prices at time of renewal). If |
| Maximum % | 6 of increase for: First Renew | al Seco | nd Renewal | Third Renewal |
| | | | | |
| Name of the l | Bidder's Firm Sign | ature of Authorized | d Representative | Date Signed |