	PAVEMENT	MARK I	NG PARI	KING LOT			
	PERMANENT PA	VEMENT	MARK ING				
	4"WHITE ACRY	LIC WAT	ERBORNE	TYPE 2	TYPE 2	TYPE 2	
	4 IN.	4 IN.	24"	PERFORMED	PERFORMED	PREFORMED	
	WHITE	DOUBLE	PVMT	LEFT	STRAIGHT	STRAIGHT/RT	
	MARKING	YELLOW	MARK ING	ARROW	ARRPW	ARROW	
LOCATION	L.F.	L.F.	L.F.	EACH	EACH	EACH	REMARKS
ADA AREAS			360.00				ALSO BETWEEN THE BUILDINGS ON TOP LOT & INTERSECTION
TOP LOT	1735.00	70.00		1.00	2.00	1.00	TOP LOT AND INTERSECTION
MIDDLE SECTION NORTH SIDE	528.00						FACING NORTH
MIDDLE SECTION SOUTH SIDE	119.00						MIDDLE SOUTH SIDE SECTION
LOWER SECTION	1463.00						LOWER LOT SECTION
SUBTOTAL	3845.00	70.00	360.00	1.00	2.00	1.00	
PAY TOTAL	3845	70	360	1	2	1	

	1" CLC PARKING LOT								
						1 "			
	FACTOR	FACTOR	FACTOR	6"	TACK	CLC			
AREA	TACK	BP-1	PMBB	PMBB	COAT	PAVEMENT			
S.F.	COAT	PAVEMENT	PAVEMENT	TONS	TONS	TONS	REMARKS		
89194.5569	0.08	1.97			792.84	542.11	PARKING LOT		
133.5464		1.97				87.70	WEDGE ON LOWER PARKING LOT		
13.7811		1.97				3.46	WEDGE ON MIDDLE PARKING LOT		
70.0000			1.99	2.58			CAN SUB COMMERCIAL MIX AS DIRECTED BY ENGINEER		
	SUBTOTAL			2.58	792.84	633.26			
	PAY TOTAL			2.6	792.8	633.3			

	CONCRETE DRIVE								
		8 "	8"						
		GROUP C	CONCRETE						
AREA		PIPE	DRIVE						
S.F.		L. F.	S.Y.			REMA	RKS		
949.54	87	40	105.51	MIDDLE	SECTION	NORTH	SIDE	DRIVE	
SUBTOT	AL	40.00	105.51	,	,				
PAY TO	TAL	40.0	105.5						

COLDMILL PARKING LOT								
PARK ING	MODIFIED							
LOT	COLDMILL	MODIFIED	1 "					
AREA	AREAS	COLDMILL	COLDMILL					
S.F.	S.F.	SY	SY	REMARKS				
29015.8858			3223.99	COLDMILL PARKING LOT				
	2097.5	233.05						
	SUBTOTAL	233.05	3223.99	STOCK PILE ALL MILLINGS IN				
	PAY TOTAL	233.1	3224.0	LOWER PARKING LOT AS DIRECTED BY ENGINEER				

"THIS MEDIA SHOULD NOT BE CONSIDERED A CERTIFIED DOCUMENT." DATE PREPARED

12/6/2013

ROUTE STATE

NW MO

DISTRICT SHEET NO.

NW 3 COUNTY BUCHANAN JOB NO. CABG101A CONTRACT ID. PROJECT NO. BRIDGE NO.

002_QU_CABG101A_PARKING.dgn 12:50:11 PM 12/6/2013

SUMMARY SHEET SHEET 1 OF 1 NOTE: ALL CONSTRUCTION SHALL BE DONE IN ACCORDANCE WITH THE LATEST EDITION OF THE MISSOURI STANDARD SPECIFICATONS FOR HIGHWAY CONSTRUCTION MISSOURI STANDARD PLANS AND SPECIFICATIONS PREPARED BY MODOT.




GENERAL NOTES:

REMOVE 10' X 7' OF CONCRETE FILL WITH 6" PMBB OR AS DIRECTED BY ENGINEER BEFORE THE OVERLAY


ALL RESUFACING SHOULD MAINTAIN DRAINAGE AWAY FROM LOT WHILE ENSURING NO POOLING OF SURFACE WATER COLDMILL ALL AREAS NECESSARY TO MAINTAIN INTEGRITY OF DOORS, SIDEWALKS, DRAINS, ETC.


ANY DAMAGE TO ADJACENT SIDEWALKS OR OTHER STRUCTURES CAUSED BY THE CONTRACTOR'S DEPENATIONS SHALL BE REPAIRED BY THE CONTRACTOR AT THE CONTRACTOR SEXENDED.

SURVEYING AND STAKING IF NEEDED WILL BE DONE BY CONTRACTOR



CONSTRUCTION DRAINAGE PROFILE





DRAWING NOT TO SCALE

12/6/2013 ROUTE STAT N.W. M.C.

> JOB NO. CABG101A

