

Product Specifications

Style Name	Crete
Style Number	0203V
Construction	High Performance Luxury Vinyl Tile
Class / ASTM F 1700	Class III Printed Film Vinyl Tile, Type A (smooth), Type B (embossed)
Wearlayer Thickness	20 mil or 0.020" (0.5 mm)
Overall Thickness	3 mm or nominal 0.125"
Nominal Dimensions	18" wide x 18" long
Actual Size / ASTM F 536	Width: 17.72" or 450 mm, Length: 17.72" or 450 mm
Finish	ExoGuard™ Quartz-Enhanced Urethane
Backing Class	Commercial Grade
Installation	Glue Down
Recommended Adhesive	Shaw 4100 or S150

Packaging

Square Feet per Carton	34.88 sf
Pieces per Carton	16 pcs
Weight per Carton	37.84 lbs

Testing

Slip Resistance / ASTM D 2047	>0.65 (wet/dry)
Static Load Limit / (modified) ASTM F 970	1500 psi
Flexibility / ASTM F 137	Passes
Resistance to Heat / ASTM F 1514	Passes
Resistance to Light / ASTM F 1515	Passes
Resistance to Chemicals / ASTM F 925	Passes
Radiant Flux / ASTM 648	Passes, >0.45 watts/cm ² , NFPA Class I
Smoke Density / ASTM E 662	Passes, <450

Warranty

10 year limited commercial wear warranty. 10 year under bed warranty when installed with Shaw 4100 or Shaw S150 spray adhesive. Please visit www.shawhardsurface.com for the most current warranty information.

Environmental

Recycled Content	Post-consumer – 0% Pre-consumer – 0%
Indoor Air Quality	FloorScore® certified
LEED Scorecard	EQ4.1, EQ4.3



Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.