## Specification Sheet

Etnyre

Quote : 0027816-01

**Custom Built For:** 

Date

: 02/17/2016

MISSOURI DOT		
	A DOOR DANKE AND A DOOR	

LIVE BOTTOM		
MODEL	LB236 FALCON TRAILER MOUN'T	
BODY CONSTRUCTION:		
CAPACITY	36 CUBIC YARDS	
LENGTH	36'	
ALUMINUM BIN EXTENSION	12"	
SIDES	ABRASION RESISTANT STEEL, 1/8" HARD OX STEEL	
INSULATION	COVERED WITH SMOOTH .040 ALUMINUM	
SIDE STIFFENERS	10 GAUGE "J" CHANNELS	
FRAME	10 GAUGE, 16" DEEP	
CROSSMEMBERS	10 GAUGE	
PRODUCT DOORS	TWIN DOORS WITH INDIVIDUAL AIR CYLINDERS (AIR CONTROL VALVE INCLUDES MANUAL OVERRIDE).	
LIGHTS	L.E.D. TYPE, 12 VOLT SEALED SYSTEM	
PAINT	BLACK ENAMEL	
REAR FENDERS	ALUMINUM DIAMOND PLATE	
FRONT FENDERS	ALUMINUM DIAMOND PLATE	
HYDRAULICS AND PRODUCT BELT:		
PLANETARY GEAR	DOUBLE REDUCTION, 30:1 RATIO, 100,000 IN. LBS. TORQUE	
HYDRAULIC MOTOR	15,2 C.I.D.	
CONTROL VALVE	NONE	
CHAIN	(6) STEEL PINTLE CHAINS, 12,500 LB. RATED	
LADDER	MOUNTED ON ROADSIDE	
CHAIN ADJUSTMENT	INDEPENDENT TENSIONING MECHANISM	
CHAIN GUIDANCE SYSTEM	ULTRA-HIGH MOLECULAR POLYETHELENE TO REDUCE FRICTION AND WEAR	
PRODUCT BELT	42" WIDE, CHEMICAL AND HEAT RESISTANT, CONTINUOUS-NO SLATS	

## Specification Sheet

Etnyre

Quote : 0027816-01

Date

: 02/17/2016

## Custom Built For: MISSOURI DOT

BELT ADJUSTMENT	INDEPENDENT ADJUSTMENT AND TENSIONING MECHANISM	
BELT RETAINER	"V" STYLE BELT CENTERING FOR POSITIVE ALIGNMENT	
CHASSIS:		
LANDING GEAR	TELESCOPIC PIN TYPE	
SUSPENSION	INTRAAX AA230 AIR RIDE TANDEM (NO MANUAL EXHAUST DUMP VALVE)	
AIR BRAKES	16.5" X 7" W/SPRING BRAKE AND AUTO SLACK ADJUSTERS	
OIL SEALS	STEMCO	
HUBS	10-STUD, HUB PILOTED STEEL	
DRUMS	CAST	
WHEELS	10-HOLE, HUB PILOTED STEEL, PAINTED WHITE	
TIRES	(8) 11R22.5-G	
MISCELLANEOUS:		
TARP	SHURCO ELECTRIC FRONT TO REAR W/ MANUAL OVERRIDE	
STROBE LIGHTS	AT REAR (SET OF 2)	
WORK LIGHTS	AT REAR (SET OF 2)	
HYDRAULIC JUMPER HOSES	TRAILER TO TRACTOR	